

Identify® MicroSemi Edition Reference

December 2015

SYNOPSYS®

Copyright Notice and Proprietary Information

© 2015 Synopsys, Inc. All rights reserved. This software and documentation contain confidential and proprietary information that is the property of Synopsys, Inc. The software and documentation are furnished under a license agreement and may be used or copied only in accordance with the terms of the license agreement. No part of the software and documentation may be reproduced, transmitted, or translated, in any form or by any means, electronic, mechanical, manual, optical, or otherwise, without prior written permission of Synopsys, Inc., or as expressly provided by the license agreement.

Destination Control Statement

All technical data contained in this publication is subject to the export control laws of the United States of America. Disclosure to nationals of other countries contrary to United States law is prohibited. It is the reader's responsibility to determine the applicable regulations and to comply with them.

Disclaimer

SYNOPSYS, INC., AND ITS LICENSORS MAKE NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS MATERIAL, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

Trademarks

Synopsys and certain Synopsys product names are trademarks of Synopsys, as set forth at

<http://www.synopsys.com/Company/Pages/Trademarks.aspx>.

All other product or company names may be trademarks of their respective owners.

Third-Party Links

Any links to third-party websites included in this document are for your convenience only. Synopsys does not endorse and is not responsible for such websites and their practices, including privacy practices, availability, and content.

December 2015

Contents

Chapter 1: Command Reference Introduction

Manual Conventions	8
Text Conventions	8
Syntax Conventions	8
Symbol Conventions	9
Tool Conventions	10
File System Conventions	10
Design Hierarchy Conventions	11

Chapter 2: Startup Modes

Synplify Pro Pointer	16
Configuring the Synplify Pro Synthesis Tool	16
License Types	18
Synplify Pro Command-Line Options	19
Custom Initialization Script	20
Scripting Priority	20
Sample Initialization File	20

Chapter 3: Command Concepts

General Commands	23
File System Commands	24
Design Hierarchy Commands	24
Design Instrumentation Commands	25
Design Debugging Commands	26

Chapter 4: Alphabetical Command Reference

activation	30
breakpoints	31
cd	33
chain	34

clear	36
com	36
compile	38
device	39
encryption	41
exit	42
help	42
hierarchy	43
idcode	48
iice	50
jtag_server	58
licenseinfo	60
log	61
project	62
pwd	63
remote_trigger	64
run	66
searchpath	68
set_synplify_configuration	69
setsys	70
show	71
signals	72
source	76
statemachine	77
stop	81
transcript	83
watch	84
waveform	87
write instrumentation	89
write samples	90
write vcd	92
write vhdlmodel	93

CHAPTER 1

Command Reference Introduction

The Identify[®] Microsemi Edition tool set consists of the Identify instrumentor and the Identify debugger. These two tools allow you to debug your HDL design:

- In the target system
- At the target speed
- At the VHDL/Verilog RTL Source level

The Identify tool set increases your debugging capabilities of high-end FPGA designs, FPGA-based prototypes, and system-on-a-chip designs. For the first time you will be able to debug live hardware with the internal design visibility you need while using intuitive debugging techniques.

To efficiently use the system and its underlying tools, this manual provides you with a comprehensive listing of all the commands the Identify tool set accepts. You can access this command information by concept listing or alphabetically.

In addition to easy look-up access to the commands, this manual also contains conventions that help display the command information easily and quickly. These manual conventions organize each command so that the information can be attained easily.

The remainder of this chapter describes:

- [Manual Conventions](#)
- [Tool Conventions](#)

Manual Conventions

There are several conventions this manual uses in order to organize command information effectively. These conventions are:

This convention...	Organizes this information....
Text convention	Text containing paths, directories, command names, and menu selections. All system specific command and path information has its own text convention to make is decipherable throughout the manual.
Syntax convention	Symbols used to separate command examples and other important system text. Syntax conventions include any type of brackets and parentheses that separate commands and functions from the rest of the text.

Text Conventions

There are several text conventions this manual uses to organize command, path and directory information. These conventions or text styles are:

This convention...	Organizes this information...
Bold	command titles
Monospacing type	command examples
Sans-serif type	commands, paths, literals, and keywords
<i>Italics</i>	variable arguments

Syntax Conventions

There are several conventions this manual uses to convey command syntax. These conventions are:

This convention...	Organizes this information...
bold	Commands and literal arguments entered as shown.
<i>italics</i>	User-defined arguments or example command information.
[]	Optional information or arguments for command use. Do not enter these brackets with the command within the command line.
...	Items that can be repeated any number of times.
	Choices you can make between two items or commands. The items are located on either side of this of this symbol.
#	Comments concerning the code or information within the command line.
{ }	Escape characters for search strings; also entered in bold font as a literal in some commands

Symbol Conventions

This manual contains symbol conventions detailing the tools that use these commands. These symbols are located adjacent to the command name in any of the command listing chapters. These symbols are:

This convention...	Organizes this information...
	Any command that is used in the Identify instrumentor only. This symbol is located underneath any Identify instrumentor command in the command listing chapters.
	Any command that is used in the Identify debugger only. This symbol is located underneath any Identify debugger command in the command listing chapters.
	Any command that is used in both the Identify instrumentor and Identify debugger tools. This symbol is located underneath the commands that have applications in both tools in the command listing chapters.

Tool Conventions

There are tool concepts you must familiarize yourself with when using the Identify tool set. These concepts help you to decipher structural and HDL-related information.

File System Conventions

The term file system refers to any command that uses file, directory, or path name information in its argument. A file system command must contain specific conventions.

Path Separator “/”

All file system commands that contain a directory name use only forward slashes, regardless of the underlying operating system:

```
/usr/data.dat
```

```
c:/Synopsys/data.dat
```

Wildcards

A wildcard is a command element you can use to search for specific file information. You can use these wildcards in combination with the file system commands. Conventions for wildcards are as follows:

Syntax	Description
*	Matches any sequence of characters
?	Matches any single character

Square brackets are used in pattern matching as follows:

Syntax	Description
[abcd]	Matches any character in the specified set.
[a-d]	Matches any character in a specified range.

To use square brackets in wildcard specifications, you must delimit the entire name with curly braces {}. For example

```
{ [a-d] 1 }
```

matches any character in the specified range (a-d) preceding the character 1.

Design Hierarchy Conventions

Design hierarchy refers to the structure of your design. Design hierarchy conventions define a way to refer to objects within the design hierarchy.

The Identify tool set supports VHDL and Verilog. These languages vary in their hierarchy conventions. The VHDL and Verilog languages contain design units and hierarchies of these design units. In VHDL, these design units are entity/architecture pairs, in Verilog they are modules. VHDL and Verilog design units are organized hierarchically. Each of the following HDL design units creates a new level in the hierarchy:

VHDL

- The top-level entity
- Architectures
- Component instantiation statements
- Process statements
- Control flow statements: if-then-else, and case
- Subprogram statements
- Block statements

Verilog

- The top-level module
- Module instantiation statements
- Always statements
- Control flow statements: if-then-else, and case
- Functions and tasks

Design Hierarchy References

A reference to an element in the design hierarchy consists of a path made up of references to design units (similar to a file reference described earlier). Regardless of the underlying HDL (VHDL or Verilog) the path separator character is always “/”:

```
/inst/reset_n
```

Absolute path names begin with a path separator character. The top-level design unit is represented by the initial “/”. Thus, a port on the top-level design unit would be represented:

```
/port_name
```

The architecture of the top-level VHDL design unit is represented:

```
/arch
```

Relative path names do not start with the path separator, and are relative to the current location in the design hierarchy. Initially, the current location is the top-level design unit, but commands exist that allow you to change the location.

Note: Design unit and hierarchy information can be case sensitive depending on the HDL language. VHDL names are not case sensitive. In contrast, all Verilog names are case sensitive.

Wildcards

A wildcard is a command element you can use to search for specific design hierarchy information. You can use these wildcards in combination with the design hierarchy commands. Conventions for wildcards are as follows:

Syntax	Description
*	Matches any sequence of characters
?	Matches any single character

Square brackets are used in hierarchy pattern matching as follows:

Syntax	Description
[abcd]	Matches any character in the specified set.
[a-d]	Matches any character in a specified range.

To use square brackets in pattern matching, you must delimit the entire name with curly braces {}. For example

```
{ [a-d] 1 }
```

matches any character in the specified range (a-d) preceding the character 1.

CHAPTER 2

Startup Modes

The Identify instrumentor and the Identify debugger can be started in any of three execution modes as outlined below:

- `identify_instrumentor`

Opens the Identify instrumentor in the graphical interface

- `identify_instrumentor -f fileName.tcl`

Runs a Tcl startup file and then opens the Identify instrumentor in the graphical user interface.

- `identify_instrumentor_shell [-version]`

Opens the Identify instrumentor in the shell and/or script mode. If the optional `-version` argument is included, reports the software version without opening the Identify instrumentor.

- `identify_debugger`

Opens the Identify debugger in the graphical interface.

- `identify_debugger -f fileName.tcl`

Runs a Tcl startup file and then opens the Identify debugger in the graphical user interface.

- `identify_debugger_shell [-version]`

Opens the Identify debugger in the shell and/or script mode. If the optional `-version` argument is included, reports the software version without opening the Identify debugger.

Note: Depending on the command shell, you may be required to provide the full path name to the program executable as well as the full path name to the files specified in any of the filename arguments.

Synplify Pro Pointer

When the Identify instrumentor or the Identify debugger is started from the command line, an additional argument can be passed to the tool to identify the location of the Synplify Pro executable associated with the project.

Note: The path to the Synplify Pro synthesis tool can also be defined after the Identify instrumentor or Identify debugger has been started as described in [Command Line Configuration, on page 18](#).

The syntax of the command-line argument is:

-synplify_install *synthesisToolPath*

Configuring the Synplify Pro Synthesis Tool


When the Identify instrumentor or Identify debugger is launched from the Synplify Pro GUI, the path to the executable is automatically defined. When the Identify instrumentor or Identify debugger is started independently and then opens a synthesis project file, the path to the Synplify Pro executable must be defined either when starting the Identify instrumentor or Identify debugger (see [Synplify Pro Pointer](#) above) or after the tool is started as defined in the following subsections.

Note: The Identify instrumentor uses the Synplify Pro compiler to compile the design.

GUI Configuration

To set the path to the Synplify Pro synthesis tool from the Identify GUI:

1. Select Options->Configure Synplify from the menu to display the Configure Synplify dialog box.



2. In the dialog box:
 - Select the Locate Synplify Installation radio button and enter the path to the Synplify Pro installation in the Synplify Installation section. The path to the Synplify installation is saved in the userprefs.cfg file located in one of the following directories based on your platform:
 - `c:\Users\userName\AppData\Roaming\Identify\userprefs.cfg` (Windows)
 - `userHome/.identify` (Linux)
 - On Windows platforms, the AppData directory may be hidden.
 - Select the appropriate license radio button in the License section.
3. Click the OK button to accept the values and close the dialog box.

Command Line Configuration

The path to the Synplify Pro synthesis tool can also be set from the command line with a `set_synplify_configuration` command. The syntax for the command is:

```
set_synplify_configuration -type synplify_pro {-locate installPath |-current}  
-license identify|synplify [-help]
```

In the syntax, *installPath* is the path to the Synplify Pro installation directory.

License Types

All of the startup execution mode commands accept an optional `-licensetype` argument to specify a license type other than the default. The license type can be either a vendor-specific license or a full license.

Note: The `-licensetype` argument is required when initially starting the Identify instrumentor or Identify debugger in the shell mode.

The following values are accepted by the `-licensetype` argument:

<code>identinstrumentor</code>	requests a full Identify instrumentor license
<code>identinstrumentor_actel</code>	requests a Microsemi-only Identify instrumentor license
<code>identdebugger</code>	requests a full Identify debugger license
<code>identdebugger_actel</code>	requests a Microsemi-only Identify debugger license

The following examples illustrate using the `-licensetype` argument. The first example opens the Identify instrumentor in the graphical interface with a full license, and the second example opens the Identify debugger in the shell mode with a Microsemi-only license.

```
identify_instrumentor -licensetype identinstrumentor
```

```
identify_debugger_shell -licensetype identdebugger_actel
```

To verify the license currently being used by the Identify instrumentor or Identify debugger, enter the command `licenseinfo` in the console window or at the shell prompt.

Note: Changing the license type with the `-licensetype` argument is valid only for the current session and does not change the default license type defined in the Select available license dialog box.

License-Type Environment Variables

License-type environment variables can be used in place of the `-licensetype` argument to set the default license type and offer the advantage of not having to specify a license type for each session. The following environment variables are supported:

```
IDENTIFYINSTRUMENTOR_LICENSE_TYPE=licenseType
```

```
IDENTIFYDEBUGGER_LICENSE_TYPE=licenseType
```

The *licenseType* argument in the above environment variables is the same as the `-licensetype` arguments listed in the previous table.

Synplify Pro Command-Line Options

When starting the Synplify Pro synthesis tool from the command line, an additional argument can be included to specify the location of the Identify installation directory. For example, the command

```
pathToSynplifyInstall/synplify_pro -identify_dir pathToIdentifyInstall
```

starts Synplify Pro in the GUI and sets the default installation path for launching the Identify tool set. The installation path specified appears in the Configure Identify Launch dialog box (Options->Configure Identify Launch) in the Synplify Pro GUI.

The `-identify_dir` argument overrides any `SYN_IDENTIFY_EXE` environment variable default setting.

Custom Initialization Script

The Identify tool set can be customized using a TCL-style initialization script. This script is sourced on tool startup and allows you to define custom procedures and variables, or to program start-up behavior.

The Identify software first looks for initialization scripts, titled `synrc.tcl`, in the `/etc` directory of the Identify installation path and then in the user's home directory. On a Linux-based platform, this is the standard home directory. On Windows, the value of the environment value `USERPROFILE` is used. On a standard Windows installation, this path is generally represented as:

```
c:/Documents and Settings/userName/synrc.tcl
```

Scripting Priority

The script is first sourced from the installation directory and then from the home directory. Since the format is Tcl, a second user-specific script overrides Tcl procedures and variables previously defined.

Sample Initialization File

A sample `synrc` file is distributed with the software. The file resides in the `/etc` directory of the installation path. The file is named `synrc.template.tcl` and must be renamed to `synrc.tcl` to enable its functionality. This file contains some sample functions and can be used as an example of how to provide a custom waveform viewer for use in the Identify debugger.

CHAPTER 3

Command Concepts

All commands that the Identify Microsemi Edition tool set uses are divided into several specific categories. These categories, or concepts, separate the commands in terms of how these commands impact the system and also in terms of the tools within the system that utilize them. These concepts are defined in their respective sections below.

Each section in this chapter also contains a table that lists the commands alphabetically. The tables separate the commands into three different columns of information. These columns are:

- Tool Usage – describes in symbol form the tools that can utilize the specific commands. The symbols are:



Command available only in Identify instrumentor



Command available only in Identify debugger



Command available in both Identify instrumentor and Identify debugger

- Use this command... – lists the command name or command example.
- To do this... – defines the uses of the command and lists command conventions and standards.

This chapter contains:

- [General Commands](#), on page 23
- [File System Commands](#), on page 24
- [Design Hierarchy Commands](#), on page 24
- [Design Instrumentation Commands](#), on page 25
- [Design Debugging Commands](#), on page 26

General Commands

A general command is any command that allows you to control and access aspects of both the Identify instrumentor and Identify debugger. These commands access aspects of these tools, such as accessing the online command help and exiting the program.

	Use this command...	To do this...
	<code>clear</code>	Remove all the console output in the graphical user interface.
	<code>exit</code>	Exit the program and close its window.
	<code>help</code>	Display the online help system and a help topic about a command, if given.
	<code>licenseinfo</code>	Display product version and license status.
	<code>log</code>	Record commands and their output into a log file.
	<code>project</code>	Create, open, and save projects.
	<code>searchpath</code>	Set a search path to find HDL design files.
	<code>setsys</code>	Manipulate internal customization variables.
	<code>source</code>	Run a TCL script.
	<code>transcript</code>	Record commands into a transcript file.

File System Commands

File system commands allow you to navigate through the file system on your computer.

	Use this command...	To do this...
	<code>cd</code>	Change the working directory.
	<code>pwd</code>	Display the present working directory

Design Hierarchy Commands

Design hierarchy handling commands allow you to navigate through the design hierarchy of your HDL design.

	Use this command...	To do this...
	<code>hierarchy</code>	Navigate through the design hierarchy of your HDL design. A find option allows you to search for specific HDL design units within an HDL design.
	<code>show</code>	Display the HDL source code in the source window.

Design Instrumentation Commands

Design entry and instrumentation commands allow you to manipulate and instrument your HDL design and to insert the IICE™.

	Use this command...	To do this...
	breakpoints	Instrument breakpoints as HDL source level trigger conditions of the IICE.
	compile	Import and compile HDL design files.
	device	Describe device-specific parameters used to implement your design.
	encryption	Set the current password to use before encrypting or decrypting a file.
	iice	Duplicate IICE Configuration dialog box functions including defining sample clock, setting counter width for complex triggering, defining trigger conditions and states, and sampling method.
	signals	Instrument signals for sampling and/or triggering in the IICE.
	write instrumentation	Write the instrumented HDL design files to a specified directory.

Design Debugging Commands

Design debugging commands allow you to debug your HDL design, interacting with the IICE and analyzing sample data at the RTL HDL source level.

	Use this command...	To do this...
	activation	Save or reload a set of trigger settings
	chain	Set up the JTAG chain of devices to be debugged.
	com	Set up the communication to the on-chip hardware, including cable and port settings.
	device	Query the type of target device(s) used to implement your design.
	encryption	Set the current password to use before encrypting or decrypting a file.
	idcode	Set up and maintain a table of device ID codes.
	iice	Query the IICE Configuration dialog box settings selected during the instrumentation phase including sample clock, counter width for complex triggering, trigger conditions and states, and selected sampling method.
	remote_trigger	Sets/resets events on a specified debugger instantiation, on all debugger tools in a multiple debugger configuration, or on specific IICE units in a multi-IICE configuration.
	run	Arm the IICE with currently activated trigger conditions and wait for a trigger. When the trigger occurs, acquire and display the sample data.
	statemachine	Define the behavior of the state machine triggering hardware.

	Use this command...	To do this...
	<code>stop</code>	Activate or deactivate a HDL source level breakpoint.
	<code>watch</code>	Activate or deactivate a HDL source level watchpoint.
	<code>waveform</code>	Implement a waveform viewer
	<code>write samples</code>	Write the sample data in text format.
	<code>write vcd</code>	Write the sample data to a Verilog Change Dump (vcd) format.
	<code>write vhdlmodel</code>	Write the sample data in a VHDL model format.

CHAPTER 4

Alphabetical Command Reference

All commands are listed alphabetically in this chapter. Each command contains syntax, argument return values, default values, and examples.

activation	idcode	show
breakpoints	iice	signals
cd	jtag_server	source
chain	licenseinfo	statemachine
clear	log	stop
com	project	transcript
compile	pwd	watch
device	remote_trigger	waveform
encryption	run	write instrumentation
exit	searchpath	write samples
help	set_synplify_configuration	write vcd
hierarchy	setsys	write vhdlmodel

activation

Allows you to save or reload a set of trigger settings (enabled watchpoints and breakpoints). Including the `-sample` option causes the sample data to be loaded or saved with the trigger settings. If the optional *activationName* argument is included, the named activation is loaded or saved; if *activationName* is omitted, `last_run.adb` is used as the default activation name. The `activation clear` and `activation list` commands clear the current trigger settings and list all of the saved activations for the current instrumentation, respectively.

Syntax

```
activation load|save [-sample] [activationName]
```

```
activation clear|list
```

Command Example

```
activation load -sample instr_trial1
```

breakpoints

Instructs the Identify instrumentor to add or delete special debug logic to or from the specified IICE. This debug logic implements breakpoint-style RTL source-level trigger conditions.

Syntax

```
breakpoints add|delete [-iice iiceID|all] breakpointName [breakpointName ...]
```

Arguments and Options

For the add and delete options, one or more breakpoints can be added or deleted at the same time.

```
add breakpointName [breakpointName ...]
```

```
delete breakpointName [breakpointName ...].
```

A breakpoint name consists of two components:

- The full hierarchical path of the HDL design unit that denotes the underlying control statement of the breakpoint.
- The HDL source code location given by the filename and the line number of the breakpoint.

The combination of these two components ensures that each breakpoint has a unique name for identification purposes.

-iice *iiceID*|all

Used when more than one IICE is defined to specify the IICE (*iiceID*) where the breakpoint is to be added or deleted. If the argument *all* is specified, the corresponding breakpoint is added to or deleted from each IICE.

Command Example

```
breakpoints add /beh/arb_inst/beh/process_83/case_88/arb.vhd:90
breakpoints delete -iice trap2
                 /beh/blk_xfer_inst/beh/process_85/case_97/xfer.vhd:107
```

See Also

- [stop, on page 81](#)

cd 

Changes the present working directory in the file system to a different designated directory.

Syntax

`cd directory`

Arguments and Options

directory

Specifies the designated directory name. You must use forward slashes to describe relative and absolute path names irrespective of the operating system. On a Windows-based platform, the directory may include a drive letter followed by a colon.

Command Example

```
cd c:/temp  
cd ../homedirs/adam
```

See Also

- [pwd, on page 63](#)

chain

Sets up and manipulates the JTAG chain of devices. Because more than one device can be connected in a JTAG chain, the commands allows you to setup the JTAG chain representation in the Identify debugger to select the particular device to be debugged.

Syntax

chain add *deviceName instructionRegisterWidth*

chain clear

chain info [**-raw** | **-active**]

chain replace *position chipID instructionRegisterLength*

chain select *chipID*

Arguments and Options

add *deviceName instructionRegisterWidth*

Creates and labels a device and assigns that device with an instruction register width. Every device attached to the JTAG must be identified by a unique name. This device name can include any alpha-numeric characters. Spaces and other characters cannot be used.

The instruction register is an N-bit register that holds the OPCODE for the JTAG controller. Every device has a specific instruction register width, which can be found in the device's Data Book.

clear

Deletes the current chain description.

info -raw|-active

Displays the chain description. The **-raw** argument returns a machine readable JTAG chain description. The chain is represented by a Tcl list of chain elements where each element is a two-item Tcl list specifying the device name and instruction register width. Example:

```
{{device_a 8} {device_b 10}}
```

The `-active` argument returns the name of the device that is currently selected for debugging.

chain replace *position chipID instructionRegisterLength*

Changes the name or register length of a device that has been previously defined using the `chain add` command. In the command syntax, *position* is the value shown by the `chain info` command for the device to be replaced.

select *deviceName*

Selects a device for system debugging. Only devices added and labeled using `chain add` can be selected.

Command Example

```
chain add fpga 5
chain select fpga
chain info -active
chain replace 1 new_fpga 8
```

See Also

- [device](#), on page 39
- [com](#), on page 36

clear

Removes all the console output in the graphical user interface. This command is only supported in the graphical modes.

Syntax

```
clear
```

Arguments and Options

None

com

Sets up and manipulates communication settings between the Identify debugger and the Intelligent In-Circuit Emulator (IICE).

Syntax

```
com cabletype [type]
```

```
com cableoptions option [value]
```

```
com check
```

```
com port [lpt1|lpt2|lpt3|lpt4]
```

Arguments and Options

cabletype [type]

Describes the type of cable connecting the system to the hardware being analyzed. The supported cable types are `Microsemi_BuiltinJTAG`, which is compatible with the `flashPro`, `flashProLite`, and `flashPro3` cables, and `demo`.

cableoptions *option* [*value*]

Specifies or reports cable-specific option settings:

flashPro_trst [*string*] – specifies the setting of the TRST (tristate) pin. Accepted values (*string*) are *off*, *toggle*, *low*, and *hi*; the default is *off*.

flashProLite_trst [*string*] – specifies the setting of the TRST (tristate) pin. Accepted values (*string*) are *off*, *toggle*, *low*, and *hi*; the default is *off*.

flashPro3_trst [*string*] – specifies the setting of the TRST (tristate) pin. Accepted values (*string*) are *off*, *toggle*, *low*, and *hi*; the default is *off*.

check

Performs a connectivity check on the JTAG cable connection.

port [*lpt1*|*lpt2*|*lpt3*|*lpt4*]

Specifies the host computer parallel port to which the JTAG cable is connected. The supported ports are *lpt1*, *lpt2*, *lpt3*, and *lpt4*.

Command Example

```
com cabletype microsemi
com cableoptions flashPro_trst toggle
com port lpt1
```

See Also

- [chain](#), on page 34

compile

Prints a list of the design files and the respective order in which they are read.

Syntax

`compile list`

Arguments and Options

`list [-vhdl|-verilog]`

Prints a list of the design files and the respective order in which they are read. If the `-vhdl` or `-verilog` option is included, limits the list to only the specified file type.

Command Example

```
compile list -vhdl
```

See Also

- [searchpath](#), on page 68

device 

Defines device-specific parameters used to implement the instrumented HDL design.

Syntax

```
device estimate [-iice all|iiceName] [-resources |-noresources |-raw]
```

```
device jtagport [builtin|soft]
```

```
device technologydefinitions [0|1]
```

Arguments and Options

estimate or **estimate -iice all**

Reports total number of instrumented signals and estimated resource utilization for the current implementation.

estimate -iice *iiceName*

Reports total number of instrumented signals and estimated resource utilization for the named IICE (*iiceName*) for the current implementation.

estimate -resources or **estimate -resources -iice all**

Reports only the estimated resource utilization for current implementation.

estimate -resources -iice *iiceName*

Reports only estimated resource utilization for the named IICE (*iiceName*) for the current implementation.

estimate -noresources or **estimate -noresources -iice all**

Reports only the number of instrumented signals for current implementation.

estimate -resources -iice *iiceName*

Reports only the number of instrumented signals for the named IICE (*iiceName*) for the current implementation.

estimate -raw

Displays the instrumented signal information and estimated resource utilization for the current implementation in a machine-readable format.

jtagport [builtin|soft]

Determines if the built-in JTAG port of the target device is used for the IICE connection or if the Synopsys test port is used. Selection can only be set in the Identify instrumentor. With no argument specified, the current setting is displayed. The following selections are available:

builtin

Specifies that the JTAG port built into the target device is the port used. No extra user pin is required. This is the default value when the device family specified is other than generic.

soft

Specifies that the IICE communicates through a JTAG TAP controller that is automatically inserted by the Identify instrumentor. The Synopsys JTAG port requires four additional user pins.

technologydefinitions [0|1]

Disables/enables the generation of black boxes for undefined module definitions. This option is available only in Identify instrumentor and is enabled by default.

Note: Valid values must be set for these options before you instrument your design.

Command Example

```
device estimate -iice IICE -noresources
device jtagport builtin
```

See Also

- [chain](#), on page 34
- [com](#), on page 36

encryption

Sets the current password to use before encrypting or decrypting a file. In the Identify instrumentor, this command sets the password to be used when writing out an encrypted file with the `write instrumentation` command. In the Identify debugger, this command is used to set the password to enable encrypted files to be displayed.

Note: Setting the password with this command displays the password on the screen and in any log files that you create. If this is a concern, use only the graphical interface when instrumenting and debugging designs that use the encryption feature.

Syntax

```
encryption set_passwd password
```

Arguments and Options

`set_passwd` *password*

The `set_passwd` argument requires a single string (*password*) entry. The new password is stored for decrypting/encrypting until it is changed or until the Identify instrumentor or Identify debugger is shut down.

Note: Passwords are the user's responsibility; Synopsys cannot recreate a lost or forgotten password.

Command Example

```
encryption set_passwd xyzzy
```

See Also

- [write instrumentation, on page 89](#)
- [project, on page 62](#)

exit

Exits the program and closes the window.

Syntax

`exit`

Arguments and Options

None

Command Example

```
exit
```

help

Displays the online help system and a help topic about a command.

Syntax

`help [commandName]`

Arguments and Options

commandName

Displays help text about the specified command. If the *commandName* argument is omitted, help descriptions for all commands are printed to the screen.

hierarchy

Navigates through the design hierarchy and shows design and hierarchy elements in the HDL design. These design elements include the following types, depending on the HDL language used to describe the design:

- Entity – VHDL design unit type.
- Module – Verilog design unit type.
- Instance – VHDL or Verilog design unit type.

Syntax

```
hierarchy add [options] element [element ...]
```

```
hierarchy cd hierarchyPath
```

```
hierarchy delete [options] element [element ...]
```

```
hierarchy find [options] [hierarchyPath]
```

```
hierarchy ls [-long] [-recursive] [-all] [hierarchyPath]
```

```
hierarchy pwd
```

```
hierarchy toplevel
```

Arguments and Options

```
add [options] element [element ...]
```

Connects all signals or breakpoints in the specified hierarchical element to the IICE. The add argument applies only to the Identify instrumentor.

The following add argument options are available:

-iice *iiceID* | all

Used when more than one IICE is defined to specify which IICE (*iiceID*) to connect. If the argument *all* is specified, the signals or breakpoints are connected to each IICE.

-sample

Connects all signals in the specified hierarchical element to the IICE sample buffer.

-trigger

Connects all signals in the specified hierarchical element to the IICE trigger logic.

-breakpoint

Connects all breakpoints in the specified hierarchical element to the IICE.

-recursive

Allow hierarchies to be traversed when a wildcard is included in the *element* argument.

Note: The *-sample*, *-trigger*, *-breakpoint*, and *-recursive* options can be combined in a single add argument.

cd *hierarchyPath*

Changes the current design hierarchy to the one specified by *hierarchyPath*. Either a relative or an absolute hierarchical path name can be used.

cd /

Changes the current design hierarchy to the top level of the hierarchy.

cd ..

Changes the current design hierarchy to next higher level.

delete [*options*] *element* [*element* ...]

Disconnects all signals or breakpoints in the specified hierarchical element from the IICE. The **delete** argument applies only to the Identify instrumentor.

The following **delete** argument options are available:

-iice *iiceID*|**all**

Used when more than one IICE is defined to specify which IICE (*iiceID*) to disconnect. If the argument **all** is specified, the signals or breakpoints are disconnected from each IICE.

-signal

Disconnects all sample and trigger signals in the specified hierarchical element from the IICE.

-breakpoint

Disconnects all breakpoints in the specified hierarchical element from the IICE.

Note: The **-signal** and **-breakpoint** options can be combined in a single **delete** argument.

find [*options*] [*hierarchyPath*]

Searches for specific HDL design units and lists those elements. Use this command to locate specified design units in the compiled HDL design file. The search is started from the specified hierarchical path. If you do not provide *hierarchyPath*, the search starts from the current working hierarchy.

The following **find** options are available:

-iice *iiceID*|**all**

Used when more than one IICE is defined to specify the IICE (*iiceID*) to be searched. If the argument **all** is specified, each IICE is searched.

-name *elementName*

The HDL element name to be located.

-noequiv

Limits the search to named path only and does not search equivalent paths.

-type instance|breakpoint|signal|*

The type of HDL element for the target search. If * is entered, search includes all elements.

-ls

Prints verbose information for each HDL element found.

-stat status|*

Serves as a filter to search for an HDL element with a specific instrumentation status. If * is entered, any instrumentation status is included in the search. The *status* argument takes the following options:

- **disabled** – limits search to disabled watchpoints, breakpoints, and other disabled HDL design units (available only in Identify debugger).
- **enabled** – limits search to enabled watchpoints, breakpoints, and other enabled HDL design units (available only in Identify debugger).
- **instrumented** – limits search to the sampling clock, and watchpoints and breakpoints that have been marked as instrumented (available only in Identify instrumentor).
- **not-instrumented** – limits search to watchpoints and breakpoints that have not been instrumented (available only in Identify instrumentor).
- **sample_only** – limits search to sample-only watchpoints (available only in Identify instrumentor).
- **trigger_only** – limits search to trigger-only watchpoints (available only in Identify instrumentor).

-maxdepth integer

Limits search to a maximum depth within the hierarchy tree.

-all

Lists “hidden” HDL design units, such as signals/breakpoints within dead code or, in the Identify debugger, breakpoints that were not instrumented. By, default, HDL elements with enabled status are searched.

ls [-long] [-recursive] [-all] [*hierarchyPath*]

Displays all information about the HDL design units within the current design hierarchy. You can display this design unit information in a long listing using the `-long` option or you can display this information recursively using the `-recursive` option. The `-all` option shows all HDL elements including hidden elements.

pwd

Lists the current HDL design hierarchy.

toplevel

Shows top-level hierarchy name.

Command Example

```
hierarchy cd ..
hierarchy cd /top/u1/arui
hierarchy ls -recursive
hierarchy find -type breakpoint -stat instrumented
```

See Also

- [show, on page 71](#)

idcode

Sets up and maintains a table of device ID codes. The ID code information is used for auto-detection of the devices on the JTAG chain during debugging. If the chain can be successfully detected, you do not need to manually specify the chain using the chain command.

Syntax

```
idcode add [-quiet] idcode deviceName instructionRegisterWidth
```

```
idcode clear
```

```
idcode info [-raw]
```

Arguments and Options

```
add [-quiet] idcode deviceName instructionRegisterWidth
```

Creates an entry in the device table for a given device.

The *idcode* argument should be a binary representation of a 32-bit number in the form of a string. The string can contain 'x' entries for bits that are irrelevant.

The *deviceName* argument can be any descriptive string. The string must be quoted if it includes spaces.

The *instructionRegisterWidth* argument takes an integer value. Every device has a specific instruction register width, which can be found in the device's Data Book.

The -quiet option adds the device, but does not display a user notification.

clear

Deletes the entire ID code table.

info [-raw]

Returns a description of the device table. The table is represented by a Tcl list of device elements where each element is a three item Tcl list specifying the ID code, device name, and instruction register width. Example:

```
{11001100110011001100110011001100 device_a 8}  
{00001100110011001100110011001111 device_b 10}
```

The optional `-raw` option generates the description in a machine-readable format.

Command Example

```
idcode add 0010000000111000100010001000 device_type 8  
idcode add -quiet 0010000000111000100010001000 "device type" 8  
idcode clear
```

See Also

- [device, on page 39](#)
- [chain, on page 34](#)

iice 

Duplicates the functionality of the IICE Configuration dialog box.

Syntax

```
iice clock|controller|current|delete|info|list|new|rename |  
sampler [option]
```

Arguments and Options

```
iice clock [options] [signalName]
```

Defines the signal to be used for the IICE sample clock. The *signalName* is the full hierarchical path name to the signal. You can select any signal within the HDL design as the sample clock. However, this signal cannot be sampled itself while used as the sample clock. This option can only be used during instrumentation. If *signalName* is not specified, the option returns the name of the IICE clock.

-edge positive|negative

Specifies the active edge of the clock (positive or negative) when an IICE sample clock is specified. The `-edge` option is only available in the Identify instrumentor; the default edge is rising (positive).

-iice *iiceID*|all

Used when more than one IICE is defined to specify/report the controller parameters for the specified IICE (*iiceID*). If the argument `all` is specified, the controller parameters apply to each IICE.

```
iice controller [options] [none|counter|statemachine]
```

Specifies IICE controller configuration; simple triggering (`none`), complex triggering (`counter`), or `statemachine`. The following options are supported:

-iice *iiceID*|all

Used when more than one IICE is defined to specify/report the controller parameters for the specified IICE (*iiceID*). If the argument `all` is specified, the controller parameters apply to each IICE.

-countermode [events|cycles|watchdog|pulsewidth]

Selects the complex counter mode. The value n referenced below is the value set by the `countvalue` option (applies only to Identify debugger).

events

Stops sampling after the trigger condition occurs for the $n+1$ 'th time. This is the default value for `-countermode`.

cycles

Stops sampling n cycles after the trigger condition occurs.

watchdog

Stops sampling if the trigger condition does not occur for n consecutive cycles.

pulsewidth

Stops sampling when the trigger condition has met n consecutive cycles. The number n is controlled by the current setting of `countvalue`.

If no argument is given, the current mode is returned.

-counterval *unsignedInteger*

Sets a value for the complex counter (applies only to Identify debugger).
unsignedInteger

Load the given value into the complex counter. This value must fit into the complex counter width as defined in the Identify instrumentor. The default value for the complex counter is 0 which disables the counter.

If no value is given, the current setting is returned.

-counterwidth *integer*

Instruments a versatile counter of variable size for complex triggering (applies only to Identify instrumentor). If no argument is given, the command shows the current counter width. An integer parameter in the range between 1 and 32 specifies a new counterwidth. 0 suppresses the creation of any counter. All other values are invalid. The default value for the counterwidth is 16 (the IICE contains a 16-bit complex counter).

-triggerconditions *integer*

Used when instrumenting a design for state-machine triggering (applies only to Identify instrumentor). This command specifies the number of trigger conditions available for state-machine triggering. The range is from 1 to 16. The default value is 4. If no argument is given, the command shows the current pattern-tree setting.

This option is a critical setting with respect to instrumentation cost. Choosing a trigger setup with the minimum amount of trigger conditions is recommended to reduce resource usage in the instrumentation. Choosing a trigger-condition value greater than 1 requires that multiple trigger states be created. Use the `triggerstates` option to specify the desired number of states.

-triggerstates [*integer*]

Used when instrumenting a design to use state-machine triggering (applies only to Identify instrumentor). This option specifies the maximum number of states instrumented in the state machine. The range is 2 to 16; powers of 2 are preferable as other integers limit functionality and do not provide any cost savings. The default is 4. If no argument is given, the option shows the current `triggerstates` setting.

-exporttrigger 0|1

Determines if the master trigger signal of the IICE hardware is exported to the top-level of the instrumented design (applies only to Identify instrumentor). Enables (1) or disables the creation of a trigger port. Export trigger port creation is disabled by default.

-importtrigger *integer*

Determines if the master trigger signal of the active IICE hardware includes any triggers received from external sources (applies only to Identify instrumentor). Specifying a value between 1 and 8 creates a corresponding number of input ports.

Note: When using an external trigger, the pin assignment for the corresponding input port must be defined in the synthesis or place and route tool.

-crosstrigger 0|1 [-iice *iiceID*]

Enables (1) or disables an IICE to include trigger signals from other IICE units when determining its trigger condition (applies only to Identify instrumentor). If the *-iice* argument is omitted, the command applies to the current IICE.

-crosstriggermode disabled|any|all|after -crosstriggeriice *iiceID*|all

Determines the trigger conditions in the Identify debugger when the IICE controller is set to simple or complex-counter triggering. The following options are supported:

disabled

Destination IICE triggers normally (triggers from source IICE units are ignored).

any

Destination IICE triggers when any source IICE triggers or on its own internal trigger.

all

Trigger occurs when all events, irrespective of order, occur at all IICE units including local IICE unit.

after -crosstriggeriice *iiceID*|all

Trigger occurs after source IICE triggers coincident with next destination IICE trigger. The *-crosstriggeriice* argument specifies a specific source IICE unit (*iiceID*) or all source IICE units (*all*).

***iice current* [*iiceID*]**

Used when more than one IICE is defined to select the active IICE (*iiceID*). If the *iiceID* argument is omitted, reports the ID of the currently active IICE. Note that *iiceID* is case sensitive.

iice delete* *iiceID

Deletes the specified IICE (*iiceID*). The *iice delete* command is only available in the Identify instrumentor.

iice info [*iiceID*]

Reports the status of the specified IICE (*iiceID*). If the *iiceID* argument is omitted, reports the status of the currently active IICE.

iice list

Lists the IDs (names) of each defined IICE.

iice new [*iiceID*]

Creates a new IICE with the name *iiceID*. If the *iiceID* argument is omitted, the new IICE is named IICE_*n* where *n* is the next sequential integer. The **iice new** command is only available in the Identify instrumentor.

iice rename *iiceID*

Renames the currently active IICE to the name specified (*iiceID*). The **iice rename** command is only available in the Identify instrumentor.

iice sampler [*options*]

The following **iice sampler** options are supported in the Identify instrumentor:

- iice** {*iiceID*|all} [*bufferType*]
- compression** 0|1
- depth** *depthValue*
- qualified_sampling** 0|1
- always_armed** 0|1

The following **iice sampler** options are supported in the Identify debugger:

- triggertime** early|middle|late
- samplemode** normal|qualified_fill|qualified_intr|always_armed
- datacompression** 0|1
- enablemask** 0|1 [-msb *integer* -lsb *integer*] *signalName*
- group** *interger*

Identify Instrumentor iice sampler Options

-iice *iiceID*[**all**] [*bufferType*]

Used when more than one IICE is defined to specify/report the IICE sampler parameters for the specified IICE (*iiceID*). If the argument **all** is specified, the IICE sampler parameters apply to each qualified IICE. The *bufferType* argument specifies the type of RAM used to capture the sample data; the only supported type of RAM is `internal_memory`.

-compression **0**|**1**

When enabled (**1**) adds compression logic to the IICE in the Identify instrumentor to support sample data compression in the Identify debugger. The default setting for the **-compression** option is **0** (no logic added). An internal default is set to force an update after 64 cycles of unchanging data. Note that there is a logic data overhead associated with data compression and that this option should not be set (**1**) unless sample data compression is to be used in the Identify debugger.

-depth *depthValue*

Changes the default sample depth of the IICE sample buffer to an assigned value *depthValue*. This option can only be used during instrumentation. The default setting for *depthValue* is 128.

-qualified_sampling **0**|**1**

Enables/disables qualified sampling. When enabled (**1**), causes the Identify instrumentor to build an IICE block that is capable or performing qualified sampling. With qualified sampling, one data value is sampled each time the trigger condition is true so that you can follow the operation of the design over a longer period of time (for example, you can observe the addresses in a number of bus cycles by sampling only one value for each bus cycle instead of a full trace). Using qualified sampling includes a minimal area and clock-speed penalty.

-always_armed **0**|**1**

Enables/disables always-armed sampling. When enabled (**1**), the Identify instrumentor saves the sample buffer for the most recent trigger and waits for the next trigger or until interrupted. With always-armed sampling, a snapshot is taken each time the trigger condition becomes true so that you always acquire the data associated with the last trigger condition prior to the interrupt. Using always-armed sampling includes a minimal area and clock-speed penalty.

Identify Debugger iice sampler Options

-triggertime [early|middle|late]

Controls how a detected trigger affects data sampling (applies only to Identify debugger).

early

Approximately 10 percent of the sample data is pre-trigger and approximately 90 percent is post-trigger.

middle

Approximately 50 percent of the sample data is pre-trigger and approximately 50 percent is post-trigger. This is the default sample trigger.

late

Approximately 90 percent of the sample data is pre-trigger and approximately 10 percent is post-trigger.

-samplemode [normal|qualified_fill|qualified_intr|always_armed]

Selects the trigger mode (applies only to Identify debugger).

qualified_fill

Performs qualified sampling until the buffer is full.

qualified_intr

Performs qualified sampling until interrupted.

always_armed

Always-on triggering.

-datacompression 0|1

Compresses debugger data when the sample data is unchanged between cycles (the data is automatically decompressed when viewed). A value of 1 enables data compression. An internal default is set to force an update after 64 cycles of unchanging data.

-enablemask 0|1 [-msb *integer* -lsb *integer*] *signalName*

Used when -datacompression option is enabled to selectively mask individual bits or buses from being considered as changing values within the sample data.

-group *integer*

Selects multiplexed group of instrumented signals defined in the Identify instrumentor for activation in the Identify debugger. *Integer* is the number of the multiplexed group which ranges from 1 to 8.

Command Example

```
iice controller -counterwidth 8 statemachine
iice current IICE_2
iice sampler -triggertime late
iice sampler -datacompression 1
iice sampler -enablemask 1 -msb 3 -lsb 0 ctrlbus1a
iice sampler -group 4
```

jtag_server

Configures the JTAG server.

Syntax

```
jtag_server set -addr {hostName|IP_address} -port {serverPort} -logf {logFileName}
```

```
jtag_server get
```

```
jtag_server start -standalone 0|1 -cabletype validType
```

```
jtag_server stop -forced 0|1
```

Arguments and Options

set

Configures the JTAG server

-addr {hostName|IP_address}

The IP address or the name of the server.

-port {serverPort}

The port number over which the client and server communicate.

-logf {logFileName}

The name of the log file.

get

Returns the server host name or IP address, port number, and log file name.

start

Selects the server startup mode.

-standalone 0|1

Selects the server startup mode. If set to 1, the debugger application is closed, and the JTAG server runs in the background.

-cabletype *validType*

Selects the cable type.

stop

Stops the server.

Command Example

```
jtag_server -set -addr myhost -port 58015 -logf servercom.log
jtag_server get
INFO: addr 127.0.0.1 port 58015 logf ipc_tcp_microsemi.log
jtag_server start -standalone 1
jtag_server stop
```

licenseinfo

Displays information about the product version and license status.

Syntax

licenseinfo

Arguments and Options

None

log 

Allows logging the console output in the graphical user interface to a file.

Syntax

```
log fileName|on|off
```

Arguments and Options

fileName

Starts logging to the specified file.

on

Starts logging to the last specified file or to the default files `syn_di.log` or `syn_hhd.log`.

off

Stops logging.

Command Example

```
log on
```

```
log off
```

```
log mylog.log
```

See Also

- [transcript, on page 83](#)

Note: This command is not supported in the command-line tools. Use the operating system capability to pipe the console input into a file.

project

Opens existing projects and displays project information.

Syntax

```
project open [-password password] [fileName]  
project name [-path]
```

Arguments and Options

open [-password *password*] *SynopsysFPGAprojectFile*

Performs a simple import of a Synplify Pro project (*prj*) file by extracting the design files, the device technology, and the design top level. This data is used to create an Identify implementation (applies only to Identify instrumentor). After extracting the files, the design is automatically compiled.

-password *password*

Specifies the password to use to decrypt an encrypted source file (applies only to Identify debugger). Note that setting the password with this command displays the password on the screen and in any log files that you create. If this is a concern, use only the graphical interface when instrumenting and debugging designs that use the encryption feature.

name [-path]

Returns the name of the current project. If the **-path** option is specified, includes the full path to the project.

Command Example

```
project open C:/space/designs/mydesign.prj  
project open -password xyzzy demo_design.prj
```

See Also

- [encryption, on page 41](#)

pwd

Displays the current working directory.

Syntax

```
pwd
```

See Also

- [cd](#), on page 33

remote_trigger

Triggers the event (stops data collection and downloads data).

Syntax

```
remote_trigger [-all|-info|-pid processID|-iice iiceID ]
```

```
remote_trigger -set|-reset [-pid processID|-iice iiceID ]
```

Arguments and Options

-all

Triggers the event for every IICE in all debugger instantiations on the corresponding machine.

-info

Lists the names of the triggers in the current debugger instantiation.

-pid *processID*

Triggers every IICE on the debugger instantiation identified by *processID*. To identify the process ID of the active debugger instantiation, enter *pid* at the command prompt. The default is to trigger every IICE in all debugger instantiations (-all).

-iice *iiceID*

Triggers the event only on the specified IICE in the current debugger instantiation. The default is to trigger every IICE in all debugger instantiations (-all).

-set [-pid *processID*|-iice *iiceID*]

Sets the trigger. If the *-pid* argument is specified, sets the trigger on every IICE on the debugger instantiation identified by *processID*; if the *-iice* argument is specified, sets the trigger only on the IICE unit specified by *iiceID*.

-reset [-pid *processID* |-iice *iiceID*]

Clears the trigger. If the -pid argument is specified, resets the trigger on every IICE on the debugger instantiation identified by *processID*; if the -iice argument is specified, resets the trigger only on the IICE unit specified by *iiceID*.

Command Example

```
remote_trigger
remote_trigger -info
remote_trigger -set -pid 12
remote_trigger -reset -pid 12
remote_trigger -set -iice IICE0
```

See also

- triggermode option – [iice, on page 50](#)
- triggertime option – [iice, on page 50](#)

run 

Arms the IICE with the current trigger settings and waits until the trigger condition has occurred and has been detected by the IICE. Once the trigger condition has occurred, the sample data is downloaded from the IICE and is displayed on the screen.

Syntax

```
run -iice iiceID|all
```

```
run -timeout integer
```

```
run -wait
```

```
run -remote_trigger pid|0
```

Arguments and Options

-iice *iiceID*|all

Used when more than one IICE is defined to specify the active IICE (*iiceID*) for triggering. If the argument *all* is specified, triggering applies to each IICE.

-timeout *integer*

Specifies the number of seconds that the Identify debugger waits for a trigger before stopping. Whenever a time-out occurs, the data buffer is automatically updated. A value of 0 disables the time-out feature.

-wait

Causes the IICE to wait for the hardware to stop running before returning.

-remote_trigger *pid*|0

Used when running multiple debugger instantiations to send a trigger to either the debugger instantiation identified by *pid* or to all debugger instantiations if 0 is specified when a local trigger condition is detected. To identify the process ID of the active debugger instantiation, enter *pid* at the command prompt.

Note: The run command does not stop running until the trigger occurs. If the trigger does not occur, the run command does not stop. To cancel the run command, you must click the Stop button in the Identify debugger menu bar. There is no stop command in the command shell.

Command Example

```
run -remote_trigger 1336
```

searchpath

Sets a search path to find HDL design files during instrumentation or debugging.

Syntax

```
searchpath [ directoryList ]
```

Arguments and Options

Without an argument, the current search path is displayed.

[*directoryList*]

Searches the specified directories, in order, for design files. *DirectoryList* can take the form of the following:

- On a Windows platform: a semicolon-separated list of valid directories. Note that the Windows “\” separator is not allowed in path names.
- On a Linux platform: a colon-separated list of valid directories.

Default Value

By default, the search path is the current working directory.

Command Example

```
searchpath {C:/temp;D:/user/joe}  
searchpath {/home/john:/home/designs}
```

See Also

- add option – [compile, on page 38](#)

set_synplify_configuration

Defines the Synplify configuration for the instrumentor.

Syntax

```
set_synplify_configuration -type|-locate|-current|-license
```

Arguments and Options

-type *synplify_pro*

Specifies the synthesis tool type.

-locate *synplifyPath*

The path to the Synplify installation.

-current

Use the current path to the Synplify installation.

-license *synplify|identify*

Use either the Synplify or Identify license to launch the tool.

setsys

Sets and queries user customization variables.

Syntax

setsys list

setsys variables

setsys set lpt_address [value]

Arguments and Options

list

Lists all available variables with their respective values.

variables

Lists all available variables with a short description explaining their function.

set lpt_address [value]

Specifies the device address for the parallel port. This setting overrides the operating system defaults. *Value* ranges from 0 to 65535; the default value is “0”. If no value is supplied, returns the current value.

Command Example

```
setsys set lpt_address 4095
```

show 

Displays an HDL source code context on the command line.

Syntax

```
show [-integer] [+integer] fileName:lineNumber
```

```
show hierarchyPath
```

Arguments and Options

[-integer]

Displays a designated number (*integer*) of lines before the *lineNumber* listed. The default number of lines displayed is 5.

[+integer]

Displays a designated number (*integer*) of lines after the *lineNumber* listed. The default number of lines displayed is 5.

fileName:lineNumber

Displays an HDL design file at the selected *lineNumber*.

hierarchyPath

Displays the HDL design unit described by the given hierarchical path.

Command Example

```
show -8 +16 cpu.vhd:29
```

```
show /top/u1/reset_n
```

signals

Instructs the Identify instrumentor to create special debug logic for the IIICE to sample a signal from your HDL design or to delete the debug logic and return the signal to its “not instrumented” status. The group options assign and report signals in multiplexed groups.

Syntax

```
signals add [options] sigName [sigName ... ]  
signals add [options] -msb value [-lsb value] sigName  
  
signals delete [options] sigName [sigName ... ]  
signals delete [options] -msb value [-lsb value] sigName  
  
signals group {groupNumber} sigName [sigName ...]  
signals group -show all|sigName [sigName ...]  
signals group -show_tab all|sigName [sigName ...]
```

Arguments and Options

```
add sigName [sigName ...]  
add -msb value [-lsb value] sigName
```

SigName is the full hierarchical path name of the signal. In the first syntax statement, more than one signal can be specified for sampling or triggering by including additional signal names separated by spaces. In the second syntax statement, the **-msb** and **-lsb** arguments specify a bit or bit range of a bus. Note that when specifying partial buses:

- Use the **-msb** argument (without an **-lsb** argument) to specify a single bit
- Observe the index order of the bus. For example, when defining a partial bus range for bus [63:0] (or “63 downto 0”), the MSB value specified must be greater than the LSB value. Similarly, for bus [0:63] (or “0 upto 63”), the MSB value specified must be less than the LSB value.

The following options are available with the `add` argument:

-iice *iiceID* | **all**

Used when more than one IICE is defined to specify the active IICE (*iiceID*) for signal sampling/triggering. If the argument `all` is specified, signal sampling/triggering applies to each IICE.

-sample

Connects the specified signal or signals to the IICE sample buffer.

-silent

Suppresses resource estimation display when a signal is added (by default, adding a signal automatically updates the total instrumentation requirements in the console window).

-field *fieldName*

Instrument the named field or record for the specified signal (partial instrumentation).

-trigger

Connects the specified signal or signals to the IICE trigger logic.

Note: The `-sample` and `-trigger` options can be combined or both options can be omitted to specify a signal for both sampling and triggering.

delete *sigName* [*sigName* ...]

delete -msb *value* [**-lsb** *value*] *sigName*

SigName is the full hierarchical path name of the signal. In the first syntax statement, more than one signal can be specified for deletion by including additional signal names. In the second syntax statement, the `-msb` and `-lsb` arguments identify a previously specified bit or bit range of a bus.

Note: When a partial bus is defined, you must explicitly delete the individual bus segments to return their status to non-instrumented.

The following options are available with the `delete` argument:

-iice *iiceID* | all

Used when more than one IICE is defined to specify the active IICE (*iiceID*) for sample signal deletion. If the argument `all` is specified, sample signal deletion applies to each IICE.

-field *fieldName*

Removes the instrumentation from the named field or record for the specified signal (partial instrumentation).

group {*groupNumber* [*groupNumber*]} *sigName* [*sigName* ...]

group -show all|*sigName* [*sigName* ...]

group -show_tab all|*sigName* [*sigName* ...]

In the first syntax statement, *groupNumber* is an integer value specifying the assigned multiplexed group number from 1 through 8, and *sigName* is the full hierarchical path name of the instrumented signal to be assigned to that group. Multiple signals can be assigned to a group by separating the signal names with spaces, and signals can be assigned to more than one group by including additional group numbers separated by spaces and enclosed in curly braces.

The following options are available with the `group` argument:

-show all|*sigName* [*sigName* ...]

Lists the group or groups assigned to *sigName*. If the `all` argument is included, lists all of the signals that have been assigned to groups and their group numbers.

-show_tab all|*sigName* [*sigName* ...]

Lists the group or groups assigned to *sigName* in tabular format. If the `all` argument is included, lists all of the signals that have been assigned to groups and their group numbers.

Command Example

```
signals add -iice IICE_2 -trigger /top/u1/clken
signals add -iice IICE_2 -trigger /top/u1/clken
signals add -sample -field iport_mem {/Struc_P_Signed_LDDT_iport}
signals delete -msb 63 -lsb 32 /top/data_in
signals group {2 3} /top/data_in top_data_out
signals group -show_tab all
```

See Also

- [breakpoints, on page 31](#)
- [clock option – iice, on page 50](#)

source

Runs a TCL script of commands.

Syntax

```
source fileName
```

Arguments and Options

FileName contains a script of TCL commands plus commands for the Identify debugger.

Command Example

```
source /home/joe/syn.tcl  
source E:/counter/load.tcl
```

statemachine

Configures the state machine with the desired behavior.

Syntax

```
statemachine addtrans -from state [-iice iiceID|all] [-to state]
  [-cond "equation|triggerInID"] [-cntval integer] [-cnten] [-trigger]
```

```
statemachine clear [-iice iiceID|all] -all|state [state ...])
```

```
statemachine info [-iice iiceID|all] [-raw] -all|state [state ...])
```

Arguments and Options

addtrans -from state

Specifies the state from which the transition is exiting. This option is required to add a transition to the state machine.

addtrans -iice iiceID|all

Used when more than one IICE is defined to specify the active IICE (*iiceID*) for state-machine configuration. If the argument *all* is specified, state-machine configuration applies to each IICE.

addtrans [-to state]

Specifies the state to which the transition goes. If the *-to* option is not given, the state defaults to the state given by the *-from* option, thus creating a transition back to the *-from* state.

addtrans [-cond "equation|triggerInID"]

Specifies the condition or external trigger under which the transition is to be taken. The default is "true" (that is, the transition is taken regardless of any input data).

The conditions are specified using boolean expressions comprised of variables and operators. The available variables are:

- **c0, ... cn**: where *n* is the number of trigger conditions instrumented. These variables represent the trigger output of the respective trigger condition.

- **cntnull**: true whenever the counter is equal to '0' (only available if a counter has been instrumented using the `-counterwidth` option of the `iice` controller command).
- **iiceID**: this variable is used with cross triggering to define the source IICE units to be included in the equation for the destination IICE trigger.
- **titriggerInID**: the ID (0 thru 7) of an external trigger input.

Operators are:

- Negation: `not`, `!`, `~`
- AND operators: `and`, `&&`, `&`
- OR operators: `or`, `||`, `|`
- XOR operators: `xor`, `^`
- NOR operators: `nor`, `~|`
- NAND operators: `nand`, `~&`
- XNOR operators: `xnor`, `~^`
- Equivalence operators: `==`, `=`
- Constants: `0`, `false`, `1`, `true`

Parentheses `(', ')` are recommended whenever the operator precedence is in question. Use the `state info` command to verify the conditions specified.

addtrans [`-cntval` *integer*]

Specifies that in the case when the transition is taken, the counter must be loaded with the given value. This option is only valid if a counter was instrumented using the `iice` controller `-counterwidth` option.

addtrans [`-cnten`]

If this flag is given, the counter is decremented by '1' during this transition. This flag is only valid if a counter was instrumented using the `iice` controller `-counterwidth` option.

addtrans [`-trigger`]

If this flag is given, the trigger occurs during this transition.

clear [-iice *iiceID*|all] -all|state [*state* ...]

Deletes state transitions.

-iice *iiceID*|all

Used when more than one IICE is defined to specify the active IICE (*iiceID*) for state-machine transition deletion. If the argument **all** is specified, transition deletion applies to each IICE.

-all|state [*state* ...]

Deletes the state transitions from the states given in the argument, or from all states if the argument **-all** is specified.

info [-iice *iiceID*|all] [-raw] -all|state [*state* ...]

Prints the current state-machine settings.

-iice *iiceID*|all

Used when more than one IICE is defined to specify the active IICE (*iiceID*) reporting the state-machine settings. If the argument **all** is specified, the settings for each IICE are reported.

-all|state [*state* ...]

Reports the settings for the states given in the argument or, if the option **-all** is specified, for the entire state machine.

-raw

Reports the settings in a machine-processible form.

Command Example

```

statemachine addtrans -from 0 -to 1 -cntval 9
statemachine addtrans -from 0 -cond "(c1 | c2)" -trigger
statemachine addtrans -from 1 -cond "c1 && c2" -cnten
statemachine addtrans -from 2 -cond "c2 && cntnull" -trigger
statemachine addtrans -from 0 -cond "IICE_1 and IICE_2" -trigger
statemachine info -all

```

See Also

- `iice controller -counterwidth` option – [iice, on page 50](#)
- `iice controller -triggerconditions` option – [iice, on page 50](#)
- `iice controller -crosstrigger` option – [iice, on page 50](#)

Note: The order in which the transitions are added is important. In each state, the first transition condition that matches the current data, is taken. There may be other transitions later in the list that also match the current data, but they are ignored.

stop 

Activates/deactivates an HDL source-level breakpoint that has been added by the Identify instrumentor. All activated breakpoints are used to form the trigger condition of the IICE. Only breakpoints that have been instrumented using the breakpoints add command can be activated. One or more breakpoints can be activated/deactivated at the same time. A breakpoint name consists of two components:

- The fully hierarchical path of the HDL design unit that denotes the underlying control statement of the breakpoint.
- The HDL source code location given by the file name and the line number of the breakpoint.

The combination of these two components ensures that each breakpoint has a unique name.

Syntax

stop disable [*options*] *breakpointName* [*breakpointName* ...]

stop enable [*options*] *breakpointName* [*breakpointName* ...]

stop info [-raw] *breakpointName*

Arguments and Options

disable [*options*] *breakpointName* [*breakpointName* ...]

Deactivates one or more HDL source-level breakpoints.

-iice *iiceID*|**all**

Used when more than one IICE is defined to specify the active IICE (*iiceID*) containing the breakpoint to be disabled. If the argument **all** is specified, disabling the breakpoint applies to each IICE.

-condition all | {*conditionlist*}

Specifies a list of trigger conditions in which to disable the breakpoint or breakpoints. If only one trigger condition exists in the current design, this option can be omitted, otherwise it is required. The identifier **all** disables the breakpoints from all trigger conditions.

enable [*options*] *breakpointName* [*breakpointName* ...]

Activates one or more HDL source-level breakpoints.

-iice *iiceID*|**all**

Used when more than one IICE is defined to specify the active IICE (*iiceID*) containing the breakpoint to be enabled. If the argument **all** is specified, enabling the breakpoint applies to each IICE.

-condition **all**|{*conditionlist*}

Specifies a list of trigger conditions in which to enable the breakpoint(s). If only one trigger condition exists in the current design, this option can be omitted, otherwise it is required. The identifier **all** enables the breakpoints from all trigger conditions.

info [**-raw**] *breakpointName* [*breakpointName* ...]

Displays information about the settings for the given HDL breakpoint. The **-raw** option provides the information in a machine-readable format.

Command Example

```
stop disable -condition 1 /top/u1/case_128/cpu.vhd:29
```

See also

- [breakpoints, on page 31](#)
- [iice, on page 50](#)

transcript

Controls recording of all typed commands into a transcript file.

Syntax

```
transcript [fileName]
```

```
transcript [off]
```

```
transcript [on]
```

Arguments and Options

transcript *fileName*

Saves all typed commands to the file specified by *fileName*.

transcript off

Commands system to stop recording commands.

transcript on

Commands system to start recording all typed commands and to store them to the default transcript file. The default file is `syn_di.scr` for the Identify instrumentor and `syn_hhd.scr` for the Identify debugger.

Default Value

By default, command recording is off.

Command Example

```
transcript on
```

See Also

- [log, on page 61](#)

watch 

Activates/deactivates a watchpoint as a trigger condition for the IICE. A watchpoint triggers when the sample value of the watched signal matches the watch value. Only signals that have been instrumented using the signals add command can be used for watchpoints.

Syntax

```
watch disable [options] signalName [signalName ...]
watch disable [options] -msb value [-lsb value] signalName

watch enable [options] signalName {value}|{valueFrom} {valueTo}
watch enable [options] -msb value [-lsb value]
  signalName {value}| {valueFrom} {valueTo}

watch info [-raw] signalName

watch radix [options] signalName [default|binary|octal|integer|unsigned|hex]

watch width signalName
```

Arguments and Options

Deactivates an HDL source-level watchpoint. One or more watchpoints can be deactivated at the same time.

```
disable [options] signalName [signalName ...]
disable [options] -msb value [-lsb value] signalName
```

SigName is the full hierarchical path name of the signal. In the first syntax statement, more than one signal can be deactivated for sampling or triggering by including additional signal names separated by spaces. In the second syntax statement, the **-msb** and **-lsb** arguments specify a bit or bit range of a bus. When specifying partial buses:

- Use the **-msb** argument (without an **-lsb** argument) to specify a single bit
- Observe the index order of the bus. For example, when defining a partial bus range for bus [63:0] (or “63 downto 0”), the MSB value specified must be greater than the LSB value. Similarly, for bus [0:63] (or “0 upto 63”), the MSB value specified must be less than the LSB value.

-iice *iiceID*|all

Used when more than one IICE is defined to specify the active IICE (*iiceID*) containing the watchpoint to be disabled. If the argument **all** is specified, disabling the watchpoint applies to each IICE.

-condition all|{*conditionlist*}

Specifies a list of trigger conditions in which to disable the watchpoint. If only one trigger condition exists in the current design, then this option can be omitted, otherwise it is required. The identifier **all** can be used to disable the watchpoint from all trigger conditions.

enable [*options*] *signalName* {*value*}|{*valueFrom*} {*valueTo*}

enable [*options*] **-msb** *value* [**-lsb** *value*] *signalName* {*value*}|{*valueFrom*} {*valueTo*}

When only *value* is specified for *signalName*, gives the watchpoint signal an exact value that the system watches for, and enables that watchpoint for triggering. When *valueFrom*/*valueTo* is specified, gives the watchpoint signal two values that the system watches for, and enables the watchpoint for triggering. These formats allow you to specify a trigger condition on the value transition of a signal. In the second syntax statement, the **-msb** and **-lsb** arguments specify a bit or bit range of a bus. Note that when specifying partial buses:

- Use the **-msb** argument (without an **-lsb** argument) to specify a single bit
- Observe the index order of the bus. For example, when defining a partial bus range for bus [63:0] (or “63 downto 0”), the MSB value specified must be greater than the LSB value. Similarly, for bus [0:63] (or “0 upto 63”), the MSB value specified must be less than the LSB value.

-iice *iiceID*|all

Used when more than one IICE is defined to specify the active IICE (*iiceID*) containing the watchpoint to be enabled. If the argument **all** is specified, enabling the watchpoint applies to each IICE.

-condition all|{*conditionlist*}

Specifies a list of trigger conditions in which to enable the one or more watchpoints. If only one trigger condition exists in the current design, this option can be omitted, otherwise it is required. The identifier **all** enables the watchpoints from all trigger conditions.

info [-raw] *breakpointName* [*breakpointName* ...]

Displays information about the settings for the given HDL watchpoint. The -raw option provides the information in a machine readable format.

radix [*options*] *signalName* [default|binary|octal|integer|unsigned|hex]

Displays or changes the radix of the specified watchpoint signal for the sampled data. Specifying **default** resets the radix to its initial intended value. Note that the radix value is maintained in the “activation database” and that this information will be lost if you fail to save or reload your activation. Also, the radix set on a signal is local to the Identify debugger and is not propagated to any of the waveform viewers. Note that with partial buses, the radix applies to the entire bus.

-iice *iiceID*|all

Used when more than one IICE is defined to specify the active IICE (*iiceID*) containing *signalName*. If the argument **all** is specified, the radix is reported/changed for each IICE.

width *signalName*

Reports the width of a vectored (bused) signal. Note that with partial buses, the width reported always applies to the entire bus.

Command Example

```
watch enable /top/u2/current_state {red}
watch enable -condition all /top/done {1'b0} {1'b1}
watch enable -condition {1 2} /top/u1/count {"0X01"} {"0010"}
watch enable /top/bx {4'b0010}
watch enable -msb 3 -lsb 0 /top/u2/data_sel {4'h0}
watch radix current_state hex
```

See also

- [signals, on page 72](#)
- controller -triggerconditions option – [iice, on page 50](#)

waveform

Configures the waveform preferences and launches the desired waveform viewer once the Identify debugger has uploaded data from the instrumented design.

Syntax

waveform custom [*userProcedure*]

waveform period [*period_in_ns*]

waveform show [*options*]

waveform viewer [*options*] **aldec|debussy|dve|gtkwave|modelsim|custom**

Arguments and Options

custom [*userProcedure*]

Sets/gets user-defined TCL procedure (*userProcedure*) that is used to launch a custom waveform viewer. This procedure must be defined in the TCL window or sourced through a startup script prior to launching the waveform viewer. The default value is `custom_waveform`. This procedure is called by `waveform show` with the following five arguments:

- *lang* – the language the design is written in -- Verilog or VHDL
- *toplevel* – the name of the top-level module or entity
- *firstcycle* – the cycle number of the first cycle
- *sampledepth* – the total number of samples
- *period* – the period for the waveform display independent of the design speed

period [*period_in_ns*]

Sets/gets the period with which to display the debug data in the waveform viewer. Since the debugger has no information about the timing of the user design, this setting is merely used for customizing the display.

show

Launches the waveform viewer that is currently selected with the current set of sample data.

-iice *iiceID*|all

Used when more than one IICE is defined to specify the active IICE (*iiceID*) containing the sample data to be displayed. If the argument **all** is specified, the sample data is displayed for each IICE.

-showequiv

Includes all equivalent signals in the sample data.

viewer [*options*] **aldec|debussy|dve|gtkwave|modelsim|custom**

Selects the user preference for the waveform viewer. The selection **custom** causes the **waveform show** command to call the procedure specified by the **waveform custom** command.

-list

Lists the available waveform viewer choices. An asterisk preceding the waveform viewer name in the list indicates the currently selected viewer.

Command Example

```
waveform viewer -list
```

```
waveform show -showequiv
```

write instrumentation

Writes the instrumented design files to the project directory.

Syntax

```
write instrumentation [-pretty|-save_orig_src|-encrypt_orig_src]
```

Options

-pretty

Instrument HDL with human-readable formatting

-save_orig_src

Create an “orig_sources” directory in the project directory and copy the user's original sources into this directory.

-encrypt_orig_src

Encrypt the original sources in the “orig_sources” directory. The encryption is based on a password which must previously be set with the `encryption set_passwd` command. Attempting to use this flag without a valid password set results in an error. Note that the `-encrypt_orig_src` flag implies and overrides the `-save_orig_src` flag. When neither flag is set, no `orig_sources` directory is created in the project directory.

Command Example

```
write instrumentation -encrypt_orig_src  
write instrumentation -save_orig_src  
write instrumentation
```

See Also

- [encryption, on page 41](#)

write samples

Writes the sample data of each specified signal.

Syntax

```
write samples [options] signalName [signalName ...]  
write samples [options] -msb value [-lsb value] signalName
```

In the above syntax statements, *sigName* is the full hierarchical path name of the signal. In the first syntax statement, sample data can be written for more than one signal by including additional signal names separated by spaces. In the second syntax statement, the **-msb** and **-lsb** arguments specify a bit or bit range of a bus. Note that when specifying partial buses:

- Use the **-msb** argument (without an **-lsb** argument) to specify a single bit
- Observe the index order of the bus. For example, when defining a partial bus range for bus [63:0] (or “63 downto 0”), the MSB value specified must be greater than the LSB value. Similarly, for bus [0:63] (or “0 upto 63”), the MSB value specified must be less than the LSB value.

Arguments and Options

-iice *iiceID*

Used when more than one IICE is defined to specify the active IICE (*iiceID*) containing the sample data for the specified signal.

-cycle {*cycleFirst cycleLast*}

Specifies the range of sample data displayed. You can view the data at different points of the trigger event. Enter a negative cycle value to view data sampled before the triggered event. Enter a positive cycle value to view data samples after the trigger event. Enter a zero cycle value to view data sampled during the trigger event.

-file *fileName*

Writes the sample data to a specified output file. If no file is given, the data is displayed on the screen.

-force

Overwrite *fileName* if it exists

-raw

Return machine-readable samples. For each signal specified, the command returns a Tcl list formatted as shown:

```
{{signalName cycleFirst cycleLast} {sampleValuesList}}
```

Command Example

```
write samples -file D:/tmp/samples.txt /top/u1/count
write samples -cycle { -10 10 } /top/u2/current_state
write samples -msb 31 -lsb 0 /top/u3/data_outA
```

write vcd

Writes the sample data of each specified signal to a Verilog Change Dump (vcd) format.

Syntax

```
write vcd [options] fileName
```

Arguments and Options

-iice *iiceID*

Used when more than one IICE is defined to specify the active IICE (*iiceID*) containing the sample data for the specified signal.

-comment *commentText*

Inserts a text comment into a file. Use curly braces ‘{}’ to group a multi-word comment.

-gtkwave

Creates a GTKWave control file for the VCD output file.

-showequiv

Includes the sample data for all equivalent signals.

fileName

Writes the sample data to the specified output file.

Command Example

```
write vcd -gtkwave D:/tmp/b.vcd
```

write vhdlmodel

Creates a VHDL model from sample data. This command is not supported in Verilog-based designs or in mixed-language designs when the top-level is a Verilog module.

Syntax

```
write vhdlmodel [options] fileName
```

Arguments and Options

-iice *iiceID*

Used when more than one IICE is defined to specify the active IICE (*iiceID*) containing the sample data for the VHDL model.

-showequiv

Includes the sample data for all equivalent signals.

fileName

Writes the VHDL model to a specified output file.

Command Example

```
write vhdlmodel D:/tmp/b.vhd
```


Index

A

activation command 30

B

breakpoints

- activating/deactivating 81
- searching 46

breakpoints command 31

buffer

- sample depth 55

C

cable option settings 37

cable types 36

cd command 33

chain command 34

clear command 36

clock

- sampling 50

clock option 50

com command 36

command history 83

command summary

- design debugging commands 26
- design hierarchy commands 24
- design instrumentation commands 25
- file system commands 24
- general commands 23

command-line options

- synthesis tool 19

commands

- recording 83

compile command 38

complex triggering 51

configuration

- IICE 50

- synthesis tool 16

console output

- logging 61

conventions

- design hierarchy 11
- file system 10
- symbol 9
- syntax 8
- text 8
- tool 10

counterwidth option 51

D

debugger

- process ID 64

depth option 55

design debugging

- command summary 26

design files

- listing 38
- writing 89

design hierarchy 43

- command summary 24

design hierarchy conventions 11

design instrumentation

- command summary 25

device command 39

device ID codes 48

directories

- changing 33
- displaying working 63

E

encryption command 41

Environment variables

- license type 19

event trigger 64

exit command 42

F

- file system
 - command summary 24
- file system conventions 10
- files
 - initialization 20
 - listing design 38
 - searching 68
 - synrc 20
 - Verilog Change Dump 92
 - writing design 89
- find option 45

G

- GUI
 - clearing 36
 - logging console output 61

H

- HDL files
 - searching 68
- help command 42
- hierarchy command 43
- hierarchy separator 12

I

- icode command 48
- IICE
 - arming 66
 - communicating with 36
 - selecting multiple 53
- iice command 50
- importing projects 62

J

- JTAG chains 34
- jtag_server command 58

L

- license types 18
- licenses
 - vendor-specific 18

- license-type environment variables 19
- log command 61

M

- models
 - VHDL 93
- multi-IICE selection 53
- multiple debuggers 64

O

- online help 42
- operators
 - state machine 78

P

- parallel port
 - defining 37
- passwords
 - encryption 41
- path names 12
- path separator 10
- process ID
 - debugger 64
- project command 62
- projects
 - creating new 62
 - importing 62
 - opening 62
- pwd command 63

R

- remote_trigger command 64
- run command 66

S

- sample data 90
- searching 45
- searchpath command 68
- separator
 - hierarchy 12
 - path 10

- server configuration 58
- set_synplify_configuration command 18
- setsys command 70
- show command 71
- signals command
 - debug logic 72
- software version
 - reporting 15
- source code
 - displaying 71
- source command 76
- startup 16
- startup modes 15
- state machines
 - configuring 77
 - operators 78
 - triggering 52
- statemachine command 77
- stop command 81
- symbol conventions 9
- synrc file 20
- syntax conventions 8
- synthesis tool
 - location 16
- system variables 70

T

- tables
 - idcode 26, 48
- target device 39
- Tcl scripts 76
- text conventions 8
- tool conventions 10
- transcript command 83
- trigger conditions 31
- trigger settings
 - reloading 30
 - saving 30
- triggering
 - complex 51
 - state machines 52
- triggermode option 56

- triggers 84
- triggerstates option 52
- triggertime option 56

V

- variables 70
- vendor-specific licenses 18
- Verilog
 - hierarchy 11
- version
 - reporting software 15
- VHDL
 - hierarchy 11
- VHDL models 93

W

- watch command 84
- watchpoints 84
 - searching 46
- waveform command 87
- wildcards
 - in hierarchies 12
 - in path names 10
- working directory
 - displaying 63
- write instrumentation command 89
- write samples command 90
- write vcd command 92
- write vhdlmodel command 93

