


Single Phase Bridges

Standard and Fast Recovery

697 & 698 Series



Dim.	Inches	Millimeter
A	.50±.01	12.70±.25
B	1.0 MIN.	25.4 MIN.
C	.250 MAX.	6.35 MAX.
D	.150 TYP.	3.81 TYP.

Leads-tinned copper .032" DIA.

MARKING:

Alternating Current Input: AC

Cathode Positive Output: +

Anode Negative: -

Part number is printed on the body.

Microsemi Catalog Number Standard Recovery	Microsemi Catalog Number Fast Recovery	Working Peak Reverse Voltage V _{RRM}
697-1	698-1	100V
697-2	698-2	200V
697-3	698-3	300V
697-4	698-4	400V
697-5	698-5	500V
697-6	698-6	600V

- Current ratings to 7.5A
- V_{RRM} 600 Volts
- Only fused-in-glass diodes used
- 150°C junction temperature
- Surge ratings to 80A
- Recovery times to 500nS
- Controlled avalanche characteristics
- MIL-PRF-19500 Similarity
- Sn/Pb terminations

Electrical Characteristics

	697	698
Maximum DC output current-T _C = 55°C	I _O	7.5A
Maximum DC output current-T _A = 25°C	I _O	2.5A
Maximum surge current-T _C = 100°C	I _{FSM}	70A
Max peak forward voltage per leg @ 25°C	V _{FM}	1.0V @ 2A*
Max peak reverse current @ 25°C, at V _{rrm}	I _{RM}	5uA
Max peak reverse current @ 100°C, at V _{rrm}	I _{RM}	200uA
Max. recovery time 1A, 1A, 0.5A	t _{rr}	---
		500nS

*Pulse test: Pulse width 300 μsec, Duty cycle 2%

Thermal and Mechanical Characteristics

Storage temp range	T _{STG}	-65°C to 150°C
Operating junction temp range	T _J	-65°C to 150°C
Max thermal resistance	R _{θJC}	10°C/W
Max thermal resistance junction to ambient	R _{θJA}	32°C/W
Weight-typical		4 grams

3-31-05 Rev. 2



800 Hoyt Street
Broomfield, CO 80020
PH: (303) 469-2161
FAX: (303) 466-3775
www.microsemi.com

697 & 698

Figure 1
Typical Forward Characteristics – Per Leg
697 Series




Figure 3
Typical Forward Characteristics – Per Leg
698 Series




Figure 2
Typical Reverse Leakage Current – Per Leg




Figure 4
Current Derating

