

7W LMT3210 62.5:1 Transformer
DESCRIPTION


This document describes and specifies the electrical and mechanical characteristics of the SGE2685-1G high voltage transformer for CCFL inverter power supplies. SGE2685-1G is the RoHS compliant and Lead free transformer. For Reliability and Safety Specification, refer to SGE2606-1.

ELECTRICAL CHARACTERISTICS

Items	Inductance (@ 10KHz, 0.1V)			Items	DC. Resistance		
	Min	Nom	Max		Min	Nom	Max
L1-2, L2-3 (μH)	112	130	152	R _{DC} 1-2, R _{DC} 2-3(mΩ)	225	239	253
L4-5 (mH)	1600	1825	2050	R _{DC} 4-5 (Ω)	563	580	620
L _{LKG1-2} , L _{LKG2-3} (μH)	Inductance (@ 100KHz, 1V), with Short pin4-5			R1-2/R2-3	0.96	1	1.04
	15	16	17	Quality Factor Q ₁₋₂ , Q ₂₋₃	15	18	-
L _{LKG4-5} (mH)	NA	NA	NA	Quality Factor Q ₄₋₅	20	24	-
Rating				Dielectric Voltage Withstand			
Note: Max output power varies depend on operating condition.				60Hz, Arc-detect enabled, 5 sec. min. 200μA max. leakage current			
Max Open Output Voltage	2000V _{RMS} , 3sec.			Secondary to Core	2500V _{RMS} min. (1min)		
Max Output Voltage	1600V _{RMS}			Primary to Core	1000V _{RMS} min.		
Max Output Power	7W			Primary to Secondary	2500V _{RMS} min.		

WINDING SPECIFICATIONS

	Primary		Secondary
	Pin 1-2	Pin 2-3	Pin 4 - 5
Winding Sequence	1S - 2F	2S-3F	4S - 5F
Wire Size & Type	AWG#33, Single Insulation, 180°C	AWG#33, Single Insulation, 180°C	AWG#46, Triple Insulation, 180°C
Number of Turns	16	16	2000
Winding Method	Bifilar		

PHYSICAL SPECIFICATIONS & WIRING DIAGRAM

PART MARKING

SGE□□□□-□G - SGE2685-1G: MSC PN
 ZZZ PYMDD A ZZZ: TMP(Maker code), P: Plant Code, Y: Year, M: Month, D: Date, A: Spec Rev.#

PACKAGING SPEC AND ORDER INFORMATION

Packaging Order Information - SGE2685-1GTR, TR - (Tape and Reel) . Blank - Tray
 TAPE & REEL : Refer to SGE2604-1



Specification Number
SGE2685-1G
Revision. A (101805)

7W LMT3210 62.5:1 Transformer

NOTES

PRODUCTION DATA – Information contained in this document is proprietary to Microsemi and is current as of publication date. This document may not be modified in any way without the express written consent of Microsemi. Product processing does not necessarily include testing of all parameters. Microsemi reserves the right to change the configuration and performance of the product and to discontinue product at any time.