Total Ionizing Dose Test Report

No. 12T-RTAX2000S-CQ352-D5A7T1

August 10, 2012

Table of Contents

I. Summary Table 3

II. Total Ionizing Dose (TID) Testing 3

A. Device-Under-Test (DUT) and Irradiation Parameters 3
B. Test Method 4
C. Design and Parametric Measurements 5

III. Test Results 6

A. Functionality 6
B. Power Supply Current (ICCA and ICCI) 6
C. Single-Ended Input Logic Threshold (VIL/VIH) 10
D. Differential Input (LVPECL) Threshold Voltage (VIL/VIH) 11
E. Output-Drive Voltage (VOL/VOH) 12
F. Propagation Delay 13
G. Transition Characteristics 15

Appendix A: DUT Bias 27

Appendix B: DUT Design Schematics and Verilog Files 29

TOTAL IONIZING DOSE TEST REPORT

No. 12T-RTAX2000S-CQ352-D5A7T1

August 10, 2012

CK Huang and J.J. Wang

(408) 643-6136, (408) 643-6302

chang-kai.huang@microsemi.com, jih-jong.wang@microsemi.com

I. Summary Table

Parameter	Tolerance
1. Gross Functionality	Passed 300 krad (SiO_2)
2. Power Supply Current (ICCA/ICCI)	Passed 200 krad (SiO_2)
3. Input Threshold (VTIL/VIH)	Passed 300 krad (SiO_2)
4. Output Drive (VOL/VOH)	Passed 300 krad (SiO_2)
5. Propagation Delay	Passed 300 krad (SiO_2) for 10% degradation criterion
6. Transition Characteristics	Passed 300 krad (SiO_2)

II. Total Ionizing Dose (TID) Testing

This testing is designed on the base of an extensive database (see TID data of antifuse-based FPGAs at http://www.klabs.org and http://www.microsemi.com/soc) accumulated from the TID testing of many generations of antifuse-based FPGAs.

A. Device-Under-Test (DUT) and Irradiation Parameters

Table 1 lists the DUT and irradiation parameters. During irradiation, each input and most of the output is grounded through a 1 MΩ resistor; during annealing, each input or output is tied to the ground or VCCI with a 2.7 kΩ resistor. Appendix A contains the schematics of the irradiation-bias circuit.

Table 1 DUT and Irradiation Parameters

Part Number	RTAX2000S
Package	CQFP352
Foundry	United Microelectronics Corp.
Technology	0.15 µm CMOS
DUT Design	TOP_AX2000S_TID
Die Lot Number	D5A7T1
Quantity Tested	6
Serial Number	300 krad(SiO_2): 597, 606, 607 200 krad(SiO_2): 617, 630, 651
Radiation Facility	Defense Microelectronics Activity
Radiation Source	Co-60
Dose Rate (±5%)	7.5 krad(SiO_2)/min
Irradiation Temperature	Room
Irradiation and Measurement Bias (VCCI/VCCA)	Static at 3.3 V/1.5 V

B. Test Method




Figure 1 Parametric Test Flow Chart

The test method generally follows the guidelines in the military standard TM1019.8. Figure 1 is the flow chart describing the steps for functional and parametric tests, irradiation, and post-irradiation annealing.

The accelerated aging, or rebound test mentioned in TM1019.8 is unnecessary because there is no adverse time-dependent effect (TDE) in Microsemi products manufactured by deep sub-micron CMOS technologies. Elevated temperature annealing basically reduces the effects originating from radiation-induced leakage currents. As indicated by test data in the following sections, the predominant radiation effects in RTAX2000S are due to radiation-induced leakage currents.

Room temperature annealing is performed in this test; the duration is approximately 1 week.

C. Design and Parametric Measurements

The DUT uses a high utilization, generic design (TOP_AX2000S_TID) to evaluate total dose effects for typical space applications. Appendix B contains the schematics and Verilog files of this design.

Table 2 lists measured electrical parameters and the corresponding logic design. The functionality is measured on the output pin (O_BS) of a combinational buffer-string with 14,000 buffers, output pins (O_ANDP_CLKF, O_ORP_CLKF, O_FF_CLKF, O_ANDC_CLKF, O_ORC_CLKF, O_ANDP_CLKG, O_ORP_CLKG, O_FF_CLKG, O_ANDC_CLKG, O_ORC_CLKG, O_ANDP_CLKH, O_ORP_CLKH, O_FF_CLKH, O_ANDC_CLKH, O_ORC_CLKH, O_ANDP_HCLKA, O_ORP_HCLKA, O_FF_HCLKA, O_ANDC_HCLKA, and O_ORC_HCLKA) of four (4) shift registers with 10,728 bits total, and half of the output pins (OUTX0, OUTX1, OUTX2, OUTX3, OUTX4, OUTX5, OUTX6 and OUTX7) of the embedded RAM configured as 16K×16.

ICC is measured on the power supply of the logic-array (ICCA) and I/O (ICCI) respectively. The input logic threshold (VIL/VIH) is measured on single-ended inputs EN8, DA, IO_I1, IO_I2, IO_I3, IO_I4, IO_I5 and IO_I6, and also on differential inputs DIO_I1P, DIO_I2P, DIO_I3P, DIO_I4P, DIO_I5P, DIO_I6P and DIO_I7P. The differential inputs are configured as LVPECL instead of LVDS because LVPECL, using 3.3 VDC, is worse than LVDS, which uses 2.5 VDC. During the measurement on the differential inputs, the N (negative) side of the differential pair is biased at 1.8 V. The output-drive voltage (VOL/VOH) is measured on QA0 and YQ0. The propagation delay is measured on the output (O_BS) of the buffer string; the definition is the time delay from the triggering edge at the CLOCK input to the switching edge at the output O_BS. Both the delays of low-to-high and high-to-low output transitions are measured; the reported delay is the average of these two measurements. The transition characteristics, measured on the output O_BS, are shown as oscilloscope captures.

Table 2 Logic Design for Parametric Measurements

Parameters	Logic Design
1. Functionality	All key logic functions (O_BS, O_ANDP_CLKF, O_ORP_CLKF, O_FF_CLKF, O_ANDC_CLKF, O_ORC_CLKF, O_ANDP_CLKG, O_ORP_CLKG, O_FF_CLKG, O_ANDC_CLKG, O_ORC_CLKG, O_ANDP_CLKH, O_ORP_CLKH, O_FF_CLKH, O_ANDC_CLKH, O_ORC_CLKH, O_ANDP_HCLKA, O_ORP_HCLKA, O_FF_HCLKA, O_ANDC_HCLKA, and O_ORC_HCLKA), and outputs of embedded RAM (OUTX0, OUTX1, OUTX2, OUTX3, OUTX4, OUTX5, OUTX6 and OUTX7)
2. ICC (ICCA/ICCI)	DUT power supply
3. Input Threshold (VIL/VIH)	Single ended inputs (EN8/YQ0, DA/QA0, IO_I1/IO_O1, IO_I2/IO_O2, IO_I3/IO_O3, IO_I4/IO_O4, IO_I5/IO_O5, IO_I6/IO_O6), and differential inputs (DIO_I1P/DIO_O1, DIO_I2P/DIO_O2, DIO_I3P/DIO_O3, DIO_I4P/DIO_O4, DIO_I5P/DIO_O5, DIO_I6P/DIO_O6, DIO_I7P/DIO_O7)
4. Output Drive (VOL/VOH)	Output buffer (EN8/YQ0, DA/QA0)
5. Propagation Delay	String of buffers (CLOCK to O_BS)
6. Transition Characteristic	String of buffers output (O_BS)

III. Test Results

A. Functionality

Every DUT passed the pre-irradiation and post-annealing functional tests. The as-irradiated DUT is functionally tested on the output (O_FF_HCLKA) of the largest shift register.

B. Power Supply Current (ICCA and ICCI)

Figure 2 through Figure 7 plot the influx standby ICCA and ICCI versus total dose for each DUT. The post-annealing ICC for four different bit patterns, all '0', all '1', checkerboard and inverted-checkerboard, in the RAM are basically the same.

In compliance with TM1019.8 subsection 3.11.2.c, the post-irradiation-parametric limit (PIPL) for the post-annealing ICCI in this test is defined as the addition of highest ICCI, ICCDA and ICCDIFFA values in Table 2-4 of *the RTAX-S/SL and RTAX-DSP Radiation-Tolerant FPGAs* datasheet:

http://www.microsemi.com/soc/documents/RTAXS_DS.pdf

For ICCA, the PIPL is 500 mA; the PIPL of ICCI equals to 35 + 10 + 3.13 × 7 = 66.91 (mA). Note that there are 7 pairs of differential LVPECL inputs in each DUT.

Table 3 summarizes the pre-irradiation, post-irradiation right after irradiation and before anneal, and post-annealing ICCA and ICCI data.

Table 3 Pre-irradiation, Post Irradiation and Post-Annealing ICC

DUT	Total Dose	ICCA (mA)			ICCI (mA)		
		Pre-irrad	Post-irrad	Post-ann	Pre-irrad	Post-irrad	Post-ann
597	300 krad	1	225	28	26	240	83
606	300 krad	2	349	25	27	238	107
607	300 krad	2	259	26	27	249	87
617	200 krad	2	16	2	27	88	50
630	200 krad	3	21	2	27	89	49
651	200 krad	2	24	5	26	88	58

Based on these PIPL, post-annealed DUT passes both the ICCA and ICCI spec for 200 krad (SiO2).




Figure 2 DUT 597 Influx ICCA and ICCI




Figure 3 DUT 606 Influx ICCA and ICCI




Figure 4 DUT 607 Influx ICCA and ICCI




Figure 5 DUT 617 Influx ICCA and ICCI




Figure 6 DUT 630 Influx ICCA and ICCI




Figure 7 DUT 651 Influx ICCA and ICCI

C. Single-Ended Input Logic Threshold (VIL/VIH)

Table 4a through Table 4c list the pre-irradiation and post-annealing single-ended input logic thresholds. All data are within the specification limits. The post-annealing shift in every case is very small.

Table 4a Pre-Irradiation and Post-Annealing Input Thresholds

DUT	597 (300 krad)				606 (300 krad)			
Input Pin	Pre-Irrad	Post-Ann	Pre-Irrad	Post-Ann	Pre-Irrad	Post-Ann	Pre-Irrad	Post-Ann
	VIL (mV)		VIH (mV)		VIL (mV)		VIH (mV)	
DA	1405	1410	1385	1380	1405	1415	1395	1390
EN8	1390	1395	1395	1385	1390	1380	1400	1390
IO_I_6	1395	1405	1390	1375	1395	1390	1405	1390
IO_I_5	1385	1395	1395	1390	1390	1380	1410	1400
IO_I_4	1400	1385	1395	1390	1390	1390	1415	1385
IO_I_3	1360	1345	1415	1410	1365	1350	1435	1415
IO_I_2	1380	1380	1405	1400	1400	1385	1430	1410
IO_I_1	1375	1370	1395	1390	1385	1380	1425	1395

Table 4b Pre-Irradiation and Post-Annealing Input Thresholds

DUT	607 (300 krad)				617 (200 krad)			
Input Pin	Pre-Irrad	Post-Ann	Pre-Irrad	Post-Ann	Pre-Irrad	Post-Ann	Pre-Irrad	Post-Ann
	VIL (mV)		VIH (mV)		VIL (mV)		VIH (mV)	
DA	1415	1400	1385	1380	1405	1405	1380	1380
EN8	1395	1370	1390	1385	1395	1395	1395	1385
IO_I_6	1405	1385	1390	1380	1400	1405	1385	1390
IO_I_5	1400	1375	1400	1395	1395	1400	1400	1395
IO_I_4	1385	1380	1385	1380	1395	1385	1395	1390
IO_I_3	1365	1345	1410	1410	1365	1350	1410	1410
IO_I_2	1385	1380	1405	1400	1400	1380	1405	1400
IO_I_1	1385	1375	1400	1395	1385	1375	1400	1395

Table 4c Pre-Irradiation and Post-Annealing Input Thresholds

DUT	630 (200 krad)				651 (200 krad)			
Input Pin	Pre-Irrad	Post-Ann	Pre-Irrad	Post-Ann	Pre-Irrad	Post-Ann	Pre-Irrad	Post-Ann
	VIL (mV)		VIH (mV)		VIL (mV)		VIH (mV)	
DA	1405	1410	1385	1380	1410	1410	1385	1380
EN8	1390	1395	1390	1385	1395	1390	1390	1380
IO_I_6	1395	1400	1390	1385	1410	1405	1395	1390
IO_I_5	1390	1390	1395	1390	1410	1395	1400	1395
IO_I_4	1385	1380	1390	1385	1390	1385	1390	1385
IO_I_3	1350	1345	1405	1405	1350	1345	1405	1410
IO_I_2	1380	1375	1405	1400	1385	1380	1405	1405
IO_I_1	1380	1370	1395	1390	1390	1375	1400	1400

D. Differential Input (LVPECL) Threshold Voltage (VIL/VIH)

Table 5a through Table 5c list the LVPECL differential input threshold voltage changes due to irradiations. All pins show negligible changes, and all the data are within the specification.

Table 5a Pre-Irradiation and Post-Annealing Differential Input Thresholds

DUT	597 (300 krad)				606 (300 krad)			
Input Pin	Pre-Irrad	Post-Ann	Pre-Irrad	Post-Ann	Pre-Irrad	Post-Ann	Pre-Irrad	Post-Ann
	VIL (mV)		VIH (mV)		VIL (mV)		VIH (mV)	
DIO_IP_7	1785	1780	1780	1780	1790	1790	1790	1780
DIO_IP_6	1780	1785	1790	1790	1790	1780	1790	1790
DIO_IP_5	1790	1790	1790	1785	1785	1785	1780	1780
DIO_IP_4	1780	1780	1785	1785	1785	1790	1790	1790
DIO_IP_3	1790	1790	1785	1785	1800	1795	1795	1790
DIO_IP_2	1785	1790	1790	1790	1785	1785	1790	1790
DIO_IP_1	1795	1795	1790	1790	1800	1800	1795	1795

Table 5b Pre-Irradiation and Post-Annealing Differential Input Thresholds

DUT	607 (300 krad)				617 (200 krad)			
Input Pin	Pre-Irrad	Post-Ann	Pre-Irrad	Post-Ann	Pre-Irrad	Post-Ann	Pre-Irrad	Post-Ann
	VIL (mV)		VIH (mV)		VIL (mV)		VIH (mV)	
DIO_IP_7	1785	1785	1775	1780	1790	1790	1790	1790
DIO_IP_6	1780	1775	1790	1790	1780	1780	1790	1790
DIO_IP_5	1790	1790	1785	1785	1795	1790	1790	1790
DIO_IP_4	1780	1780	1785	1785	1785	1785	1790	1790
DIO_IP_3	1795	1795	1790	1790	1795	1795	1790	1785
DIO_IP_2	1785	1785	1790	1790	1790	1790	1790	1790
DIO_IP_1	1790	1790	1785	1785	1795	1795	1790	1790

Table 5c Pre-Irradiation and Post-Annealing Differential Input Thresholds

DUT	630 (200 krad)				651 (200 krad)			
Input Pin	Pre-Irrad	Post-Ann	Pre-Irrad	Post-Ann	Pre-Irrad	Post-Ann	Pre-Irrad	Post-Ann
	VIL (mV)		VIH (mV)		VIL (mV)		VIH (mV)	
DIO_IP_7	1780	1780	1780	1780	1790	1790	1790	1790
DIO_IP_6	1780	1780	1790	1790	1780	1785	1790	1790
DIO_IP_5	1795	1795	1790	1790	1800	1795	1795	1795
DIO_IP_4	1780	1780	1785	1790	1785	1785	1790	1790
DIO_IP_3	1795	1790	1785	1785	1795	1790	1790	1785
DIO_IP_2	1785	1785	1790	1790	1780	1780	1780	1780
DIO_IP_1	1790	1790	1785	1785	1795	1795	1790	1790

E. Output-Drive Voltage (VOL/VOH)

The pre-irradiation and post-annealing VOL/VOH are listed in Tables 6 and 7. The post-annealing data are within the specification limits.

Table 6 Pre-Irradiation and Post-Annealing VOL (mV) at Various Sinking Current

Sourcing Current	Pin\DUT	597 (300 krad)		606 (300 krad)		607 (300 krad)		617 (200 krad)		630 (200 krad)		651 (200 krad)	
		Pre-rad	Post-an	Pre-rad	Post-an	Pre-rad	Post-an	Pre-rad	Post-an	Pre-rad	Post-an	Pre-rad	Post-an
1 mA	QA0	8	8	9	8	8	8	9	8	8	8	9	8
	YQ0	9	9	9	9	9	9	9	9	9	9	9	9
12 mA	QA0	97	91	97	91	98	92	98	93	96	91	99	94
	YQ0	108	103	106	100	107	101	106	101	107	102	107	102
20 mA	QA0	161	152	161	152	164	154	163	155	161	153	165	156
	YQ0	181	172	177	167	178	169	176	168	178	170	178	171
50 mA	QA0	410	386	411	386	417	391	416	394	409	388	420	397
	YQ0	459	436	448	423	452	428	447	426	452	431	453	432
100 mA	QA0	867	815	869	813	885	826	881	832	865	819	891	840
	YQ0	965	914	942	887	952	900	942	895	951	907	954	909

Table 7 Pre-Irradiation and Post-Annealing VOH (mV) at Various Sourcing Current

Sourcing Current	Pin\DUT	597 (300 krad)		606 (300 krad)		607 (300 krad)		617 (200 krad)		630 (200 krad)		651 (200 krad)	
		Pre-rad	Post-an	Pre-rad	Post-an	Pre-rad	Post-an	Pre-rad	Post-an	Pre-rad	Post-an	Pre-rad	Post-an
1 mA	QA0	3288	3284	3288	3285	3288	3284	3288	3285	3288	3286	3288	3286
	YQ0	3286	3282	3286	3283	3286	3282	3286	3284	3286	3284	3286	3284
8 mA	QA0	3218	3215	3220	3217	3217	3215	3218	3217	3219	3218	3218	3216
	YQ0	3210	3207	3213	3210	3211	3209	3212	3211	3211	3211	3211	3210
20 mA	QA0	3096	3096	3100	3100	3095	3095	3095	3097	3097	3099	3095	3096
	YQ0	3078	3076	3085	3084	3081	3081	3082	3083	3081	3082	3081	3082
50 mA	QA0	2777	2781	2788	2792	2774	2778	2774	2781	2779	2786	2773	2779
	YQ0	2733	2736	2752	2757	2744	2748	2747	2752	2743	2749	2742	2747
100 mA	QA0	2162	2173	2190	2201	2152	2162	2156	2172	2167	2184	2152	2166
	YQ0	2078	2086	2125	2135	2098	2108	2105	2118	2097	2111	2095	2105

F. Propagation Delay

The propagation delay was measured in-situ, post-irradiation, and post-annealing. The irradiation was temporarily stopped at each total-dose increment of 100 krad for the measurement. Each measurement has a 2-minute wait after a DUT is removed from the chamber. The results are plotted in Figure 8, and listed in Table 8. As shown in Figure 8, the propagation delay initially decreases with the total dose, but the change is small throughout the irradiation. Referring to influx static current plots (Figure 2 through Figure 7), a device probably heats up as the dose increases. The rising temperature could be the root cause of the increasing trend at high doses. The post-annealing data, on the other hand, show decreased delay in every case.

The radiation delta in every case is well within the 10% degradation criterion. User can take the worst case for the design-margin consideration.




Figure 8 In-Situ Propagation Delay versus Total Dose.
The measurement is performed outside the irradiation chamber.

Table 8 Radiation-Induced Propagation-Delay Degradations

	RTAX2000S D5A7T1 CQ352						
Delay (µs)							
	DUT	**Total Dose**	**Pre-rad**	**100 krad**	**200 krad**	**300 krad**	**Post-ann**
	597	300 krad	7.28	7.27	7.38	7.61	7.36
	606	300 krad	6.72	6.68	6.73	7.20	6.70
	607	300 krad	6.77	6.74	6.82	6.98	6.79
	617	200 krad	6.90	6.92	6.80	-	6.84
	630	200 krad	6.80	6.79	6.83	-	6.73
	651	200 krad	6.68	6.62	6.70	-	6.69
Radiation Δ (%)							
	DUT	**Total Dose**	**Pre-rad**	**100 krad**	**200 krad**	**300 krad**	**Post-ann**
	300 krad	-	-0.14%	1.37%	4.53%	1.10%	300 krad
	300 krad	-	-0.60%	0.15%	7.14%	-0.30%	300 krad
	300 krad	-	-0.44%	0.74%	3.10%	0.22%	300 krad
	200 krad	-	0.29%	-1.45%	-	-0.94%	200 krad
	200 krad	-	-0.15%	0.44%	-	-1.03%	200 krad
	200 krad	-	-0.90%	0.30%	-	0.07%	200 krad

G. Transition Characteristics

Figure 9a to Figure 20b show the pre-irradiation and post-annealing transition edges. In each case, the radiation-induced transition-time degradation is insignificant.




Figure 9a DUT 597 Pre-Irradiation Rising Edge



Figure 9b DUT 597 Post-Annealing Rising Edge




Figure 10a DUT 606 Pre-Irradiation Rising Edge




Figure 10b DUT 606 Post-Annealing Rising Edge




Figure 11a DUT 607 Pre-Radiation Rising Edge



Figure 11b DUT 607 Post-Annealing Rising edge




Figure 12a DUT 617 Pre-Irradiation Rising Edge




Figure 12b DUT 617 Post-Annealing Rising Edge




Figure 13a DUT 630 Pre-Irradiation Rising Edge




Figure 13b DUT 630 Post-Annealing Rising Edge



Figure 14a DUT 651 Pre-Irradiation Rising Edge



Figure 14b DUT 651 Post-Annealing Rising Edge



Figure 15a DUT 597 Pre-Radiation Falling Edge




Figure 15b DUT 597 Post-Annealing Falling Edge




Figure 16a DUT 606 Pre-Irradiation Falling Edge




Figure 16b DUT 606 Post-Annealing Falling Edge




Figure 17a DUT 607 Pre-Irradiation Falling Edge




Figure 17b DUT 607 Post-Annealing Falling Edge




Figure 18a DUT 617 Pre-Irradiation Falling Edge




Figure 18b DUT 617 Post-Annealing Falling Edge




Figure 19a DUT 630 Pre-Irradiation Falling Edge




Figure 19b DUT 630 Post-Annealing Falling Edge




Figure 20a DUT 651 Pre-Irradiation Falling Edge



Figure 20b DUT 651 Post-Annealing Falling Edge

Appendix A: DUT Bias




Figure A1 I/O Bias During Irradiation







Figure A2 Power Supply, Ground and Special Pins Bias During Irradiation


Appendix B: DUT Design Schematics and Verilog Files






O_ANDP_HCLK
O_ORP_HCLK
O_FF_HCLK
O_ANDC_HCL
O_ORC_HCLK
OUTBUF
PAD
AND4
OR4
FF32
FF128
HCLKBUF
HCLOCK_IN
CLEAR



QI
In
Out
BUFF2p3k
D
OUTBUF
PAD
O_BS



YQ7
YQ6
YQ5
YQ4
YQ3
YQ2
YQ1
YQ0
OUTBUF_PAD
D
Y
A
INBUF
PAD
ENB
QA2
QA0
QA1
DA


DIO_O1
DIO_O2
DIO_O3
DIO_O4
DIO_O5
DIO_O6
DIO_O7
OUTBUF
PAD
D
PADP
PADN
Y
LVPECL_INPUT
DIO_I1P
DIO_I1N
DIO_I2P
DIO_I2N
DIO_I3P
DIO_I3N
DIO_I4P
DIO_I4N
DIO_I5P
DIO_I5N
DIO_I6P
DIO_I6N
DIO_I7P
DIO_I7N


IO_O1
IO_O2
IO_O3
IO_O4
IO_O5
IO_O6
OUTBUF
PAD
D
INBUF
Y
IO_I1
IO_I2
IO_I3
IO_I4
IO_I5
IO_I6


O_ANDP_CLKF
O_ORP_CLKF
O_FF_CLKF
O_ANDC_CLKF
O_ORC_CLKF
CLOCKF_OUT
CLKBUF
CLOCKF_IN
CLEAR
FF128


O_ANDP_CLKG
O_ORP_CLKG
O_FF_CLKG
O_ANDC_CLKG
O_ORC_CLKG
OUTBUF
PAD
D
Y
AND4
OR4
A
B
C
D
Q
ANDP
ORP
ANDC
ORC
CLK
RST
FF128
CLOCKG_OUT
CLKBUF
CLOCKG_IN
CLEAR


O_ANDP_CLKH
O_ORP_CLKH
O_FF_CLKH
O_ANDC_CLKH
O_ORC_CLKH
OUTBUF
PAD
AND4
OR4
FF128
CLOCKH_OUT
CLKBUF
CLOCKH_IN
CLEAR

```
// BUFF2p3k.v
`timescale 1 ns/100 ps

module BUFF2p3k (In, Out);

input In;

output Out;

wire x1/*synthesis syn_keep=1 alspreserve=1*/;
wire x2/*synthesis syn_keep=1 alspreserve=1*/;
wire x3/*synthesis syn_keep=1 alspreserve=1*/;
wire x4/*synthesis syn_keep=1 alspreserve=1*/;
wire x5/*synthesis syn_keep=1 alspreserve=1*/;
wire x6/*synthesis syn_keep=1 alspreserve=1*/;
wire x7/*synthesis syn_keep=1 alspreserve=1*/;

BUFF1k buff1k_1 (.In(In), .Out(x1));
BUFF1k buff1k_2 (.In(x1), .Out(x2));
BUFF50 buff3 (.In(x2), .Out(x3));
BUFF50 buff4 (.In(x3), .Out(x4));
BUFF50 buff5 (.In(x4), .Out(x5));
BUFF50 buff6 (.In(x5), .Out(x6));
BUFF50 buff7 (.In(x6), .Out(x7));
BUFF50 buff8 (.In(x7), .Out(Out));

endmodule

// BUFF1k
`timescale 1 ns/100 ps

module BUFF1k (In, Out);

input In;

output Out;

wire x1/*synthesis syn_keep=1 alspreserve=1*/;
wire x2/*synthesis syn_keep=1 alspreserve=1*/;
wire x3/*synthesis syn_keep=1 alspreserve=1*/;
wire x4/*synthesis syn_keep=1 alspreserve=1*/;
wire x5/*synthesis syn_keep=1 alspreserve=1*/;
wire x6/*synthesis syn_keep=1 alspreserve=1*/;
wire x7/*synthesis syn_keep=1 alspreserve=1*/;
wire x8/*synthesis syn_keep=1 alspreserve=1*/;
wire x9/*synthesis syn_keep=1 alspreserve=1*/;
wire x10/*synthesis syn_keep=1 alspreserve=1*/;
wire x11/*synthesis syn_keep=1 alspreserve=1*/;
wire x12/*synthesis syn_keep=1 alspreserve=1*/;
wire x13/*synthesis syn_keep=1 alspreserve=1*/;
wire x14/*synthesis syn_keep=1 alspreserve=1*/;
wire x15/*synthesis syn_keep=1 alspreserve=1*/;
wire x16/*synthesis syn_keep=1 alspreserve=1*/;
wire x17/*synthesis syn_keep=1 alspreserve=1*/;
wire x18/*synthesis syn_keep=1 alspreserve=1*/;
wire x19/*synthesis syn_keep=1 alspreserve=1*/;
```

```
BUFF50 buff1 (.In(In), .Out(x1));
BUFF50 buff2 (.In(x1), .Out(x2));
BUFF50 buff3 (.In(x2), .Out(x3));
BUFF50 buff4 (.In(x3), .Out(x4));
BUFF50 buff5 (.In(x4), .Out(x5));
BUFF50 buff6 (.In(x5), .Out(x6));
BUFF50 buff7 (.In(x6), .Out(x7));
BUFF50 buff8 (.In(x7), .Out(x8));
BUFF50 buff9 (.In(x8), .Out(x9));
BUFF50 buff10 (.In(x9), .Out(x10));

BUFF50 buff11 (.In(x10), .Out(x11));
BUFF50 buff12 (.In(x11), .Out(x12));
BUFF50 buff13 (.In(x12), .Out(x13));
BUFF50 buff14 (.In(x13), .Out(x14));
BUFF50 buff15 (.In(x14), .Out(x15));
BUFF50 buff16 (.In(x15), .Out(x16));
BUFF50 buff17 (.In(x16), .Out(x17));
BUFF50 buff18 (.In(x17), .Out(x18));
BUFF50 buff19 (.In(x18), .Out(x19));
BUFF50 buff20 (.In(x19), .Out(Out));

endmodule

// BUFF50
`timescale 1 ns/100 ps

module BUFF50 (In, Out);

input In;

output Out;

wire x1 /*synthesis syn_keep=1 alspreserve=1*/;
wire x2 /*synthesis syn_keep=1 alspreserve=1*/;
wire x3 /*synthesis syn_keep=1 alspreserve=1*/;
wire x4 /*synthesis syn_keep=1 alspreserve=1*/;
wire x5 /*synthesis syn_keep=1 alspreserve=1*/;
wire x6/*synthesis syn_keep=1 alspreserve=1*/;
wire x7/*synthesis syn_keep=1 alspreserve=1*/;
wire x8/*synthesis syn_keep=1 alspreserve=1*/;
wire x9/*synthesis syn_keep=1 alspreserve=1*/;
wire x10/*synthesis syn_keep=1 alspreserve=1*/;
wire x11/*synthesis syn_keep=1 alspreserve=1*/;
wire x12/*synthesis syn_keep=1 alspreserve=1*/;
wire x13/*synthesis syn_keep=1 alspreserve=1*/;
wire x14/*synthesis syn_keep=1 alspreserve=1*/;
wire x15/*synthesis syn_keep=1 alspreserve=1*/;
wire x16/*synthesis syn_keep=1 alspreserve=1*/;
wire x17/*synthesis syn_keep=1 alspreserve=1*/;
wire x18/*synthesis syn_keep=1 alspreserve=1*/;
wire x19/*synthesis syn_keep=1 alspreserve=1*/;
wire x20/*synthesis syn_keep=1 alspreserve=1*/;
wire x21/*synthesis syn_keep=1 alspreserve=1*/;
wire x22/*synthesis syn_keep=1 alspreserve=1*/;
```

```
wire x23/*synthesis syn_keep=1 alspreserve=1*/;
wire x24/*synthesis syn_keep=1 alspreserve=1*/;
wire x25/*synthesis syn_keep=1 alspreserve=1*/;
wire x26/*synthesis syn_keep=1 alspreserve=1*/;
wire x27/*synthesis syn_keep=1 alspreserve=1*/;
wire x28/*synthesis syn_keep=1 alspreserve=1*/;
wire x29/*synthesis syn_keep=1 alspreserve=1*/;
wire x30/*synthesis syn_keep=1 alspreserve=1*/;
wire x31/*synthesis syn_keep=1 alspreserve=1*/;
wire x32/*synthesis syn_keep=1 alspreserve=1*/;
wire x33/*synthesis syn_keep=1 alspreserve=1*/;
wire x34/*synthesis syn_keep=1 alspreserve=1*/;
wire x35/*synthesis syn_keep=1 alspreserve=1*/;
wire x36/*synthesis syn_keep=1 alspreserve=1*/;
wire x37/*synthesis syn_keep=1 alspreserve=1*/;
wire x38/*synthesis syn_keep=1 alspreserve=1*/;
wire x39/*synthesis syn_keep=1 alspreserve=1*/;
wire x40/*synthesis syn_keep=1 alspreserve=1*/;
wire x41/*synthesis syn_keep=1 alspreserve=1*/;
wire x42/*synthesis syn_keep=1 alspreserve=1*/;
wire x43/*synthesis syn_keep=1 alspreserve=1*/;
wire x44/*synthesis syn_keep=1 alspreserve=1*/;
wire x45/*synthesis syn_keep=1 alspreserve=1*/;
wire x46/*synthesis syn_keep=1 alspreserve=1*/;
wire x47/*synthesis syn_keep=1 alspreserve=1*/;
wire x48/*synthesis syn_keep=1 alspreserve=1*/;
wire x49/*synthesis syn_keep=1 alspreserve=1*/;

BUFF buff1 (.A(In), .Y(x1));
BUFF buff2 (.A(x1), .Y(x2));
BUFF buff3 (.A(x2), .Y(x3));
BUFF buff4 (.A(x3), .Y(x4));
BUFF buff5 (.A(x4), .Y(x5));
BUFF buff6 (.A(x5), .Y(x6));
BUFF buff7 (.A(x6), .Y(x7));
BUFF buff8 (.A(x7), .Y(x8));
BUFF buff9 (.A(x8), .Y(x9));
BUFF buff10 (.A(x9), .Y(x10));

BUFF buff11 (.A(x10), .Y(x11));
BUFF buff12 (.A(x11), .Y(x12));
BUFF buff13 (.A(x12), .Y(x13));
BUFF buff14 (.A(x13), .Y(x14));
BUFF buff15 (.A(x14), .Y(x15));
BUFF buff16 (.A(x15), .Y(x16));
BUFF buff17 (.A(x16), .Y(x17));
BUFF buff18 (.A(x17), .Y(x18));
BUFF buff19 (.A(x18), .Y(x19));
BUFF buff20 (.A(x19), .Y(x20));

BUFF buff21 (.A(x20), .Y(x21));
BUFF buff22 (.A(x21), .Y(x22));
BUFF buff23 (.A(x22), .Y(x23));
BUFF buff24 (.A(x23), .Y(x24));
BUFF buff25 (.A(x24), .Y(x25));
BUFF buff26 (.A(x25), .Y(x26));
```

```
BUFF buff27 (.A(x26), .Y(x27));
BUFF buff28 (.A(x27), .Y(x28));
BUFF buff29 (.A(x28), .Y(x29));
BUFF buff30 (.A(x29), .Y(x30));

BUFF buff31 (.A(x30), .Y(x31));
BUFF buff32 (.A(x31), .Y(x32));
BUFF buff33 (.A(x32), .Y(x33));
BUFF buff34 (.A(x33), .Y(x34));
BUFF buff35 (.A(x34), .Y(x35));
BUFF buff36 (.A(x35), .Y(x36));
BUFF buff37 (.A(x36), .Y(x37));
BUFF buff38 (.A(x37), .Y(x38));
BUFF buff39 (.A(x38), .Y(x39));
BUFF buff40 (.A(x39), .Y(x40));

BUFF buff41 (.A(x40), .Y(x41));
BUFF buff42 (.A(x41), .Y(x42));
BUFF buff43 (.A(x42), .Y(x43));
BUFF buff44 (.A(x43), .Y(x44));
BUFF buff45 (.A(x44), .Y(x45));
BUFF buff46 (.A(x45), .Y(x46));
BUFF buff47 (.A(x46), .Y(x47));
BUFF buff48 (.A(x47), .Y(x48));
BUFF buff49 (.A(x48), .Y(x49));
BUFF buff50 (.A(x49), .Y(Out));

endmodule

// FF128
`timescale 1 ns/100 ps
module FF128 (D, Q, CLK, RST, ANDP, ORP, ANDC, ORC);

input D, CLK, RST;
output Q, ANDP, ORP, ANDC, ORC;

wire x1, x2, x3, Q;
wire andp_a, andp_b, andp_c, andp_d, orp_a, orp_b, orp_c, orp_d;
wire andc_a, andc_b, andc_c, andc_d, orc_a, orc_b, orc_c, orc_d;

FF32 dff_a (.D(D), .Q(x1), .CLK(CLK), .RST(RST), .ANDP(andp_a), .ORP(orp_a),
.ANDC(andc_a), .ORC(orc_a));

FF32 dff_b (.D(x1), .Q(x2), .CLK(CLK), .RST(RST), .ANDP(andp_b), .ORP(orp_b),
.ANDC(andc_b), .ORC(orc_b));

FF32 dff_c (.D(x2), .Q(x3), .CLK(CLK), .RST(RST), .ANDP(andp_c), .ORP(orp_c),
.ANDC(andc_c), .ORC(orc_c));

FF32 dff_d (.D(x3), .Q(Q), .CLK(CLK), .RST(RST), .ANDP(andp_d), .ORP(orp_d),
.ANDC(andc_d), .ORC(orc_d));

AND4 and4p (.A(andp_a), .B(andp_b), .C(andp_c), .D(andp_d), .Y(ANDP));
OR4 or4p (.A(orp_a), .B(orp_b), .C(orp_c), .D(orp_d), .Y(ORP));

AND4 and4c (.A(andc_a), .B(andc_b), .C(andc_c), .D(andc_d), .Y(ANDC));
```

```
OR4 or4c (.A(orc_a), .B(orc_b), .C(orc_c), .D(orc_d), .Y(ORC));

endmodule

// FF32
`timescale 1 ns/100 ps
module FF32 (D, Q, CLK, RST, ANDP, ORP, ANDC, ORC);

input D, CLK, RST;
output Q, ANDP, ORP, ANDC, ORC;

wire x1, x2, x3, Q;
wire andp_a, andp_b, andp_c, andp_d, orp_a, orp_b, orp_c, orp_d;
wire andc_a, andc_b, andc_c, andc_d, orc_a, orc_b, orc_c, orc_d;

FF8 dff_a (.D(D), .Q(x1), .CLK(CLK), .RST(RST), .ANDP(andp_a), .ORP(orp_a),
.ANDC(andc_a), .ORC(orc_a));

FF8 dff_b (.D(x1), .Q(x2), .CLK(CLK), .RST(RST), .ANDP(andp_b), .ORP(orp_b),
.ANDC(andc_b), .ORC(orc_b));

FF8 dff_c (.D(x2), .Q(x3), .CLK(CLK), .RST(RST), .ANDP(andp_c), .ORP(orp_c),
.ANDC(andc_c), .ORC(orc_c));

FF8 dff_d (.D(x3), .Q(Q), .CLK(CLK), .RST(RST), .ANDP(andp_d), .ORP(orp_d),
.ANDC(andc_d), .ORC(orc_d));

AND4 and4p (.A(andp_a), .B(andp_b), .C(andp_c), .D(andp_d), .Y(ANDP));
OR4 or4p (.A(orp_a), .B(orp_b), .C(orp_c), .D(orp_d), .Y(ORP));

AND4 and4c (.A(andc_a), .B(andc_b), .C(andc_c), .D(andc_d), .Y(ANDC));
OR4 or4c (.A(orc_a), .B(orc_b), .C(orc_c), .D(orc_d), .Y(ORC));

endmodule

// FF8
`timescale 1 ns/100 ps

module FF8 (D, Q, CLK, RST, ANDP, ORP, ANDC, ORC);

input D, CLK, RST;
output Q, ANDP, ORP, ANDC, ORC;

wire x1, x2, x3, x4, x5, x6, x7;

DFC1B dff1 (.D(D), .Q(x1), .CLK(CLK), .CLR(RST));
DFP1B dff2 (.D(x1), .Q(x2), .CLK(CLK), .PRE(RST));
DFC1B dff3 (.D(x2), .Q(x3), .CLK(CLK), .CLR(RST));
DFP1B dff4 (.D(x3), .Q(x4), .CLK(CLK), .PRE(RST));
DFC1B dff5 (.D(x4), .Q(x5), .CLK(CLK), .CLR(RST));
DFP1B dff6 (.D(x5), .Q(x6), .CLK(CLK), .PRE(RST));
DFC1B dff7 (.D(x6), .Q(x7), .CLK(CLK), .CLR(RST));
DFP1B dff8 (.D(x7), .Q(Q), .CLK(CLK), .PRE(RST));

AND4 and4p (.A(x2), .B(x4), .C(x6), .D(Q), .Y(ANDP));
OR4 or4p (.A(x2), .B(x4), .C(x6), .D(Q), .Y(ORP));
```

```
AND4 and4c (.A(x1), .B(x3), .C(x5), .D(x7), .Y(ANDC));
OR4 or4c (.A(x1), .B(x3), .C(x5), .D(x7), .Y(ORC));

endmodule

// Top_RAM_Module.v
`timescale 1 ns/100 ps

module Top_RAM_Module(Psel0, Psel1, RC_en, RC_clr, RC_clk, Write, Read, Wclk, Rclk,
                Q_RAM);
input Psel0, Psel1, RC_en, RC_clr, RC_clk, Write, Read, Wclk, Rclk;
output [5:0] Q_RAM;

wire Gnd, Vcc;
wire mx0, mx1;
wire [12:0] rc;
wire [3:0] dec;
wire y_0w, y_0r, y_1w, y_1r, y_2w, y_2r, y_3w, y_3r;
// y_4w, y_4r, y_5w, y_5r, y_6w, y_6r, y_7w, y_7r;
wire [5:0] DIN;
wire [5:0] Q_b0;
wire [5:0] Q_b1;
wire [5:0] Q_b2;
wire [5:0] Q_b3;
//wire [5:0] Q_b4;
//wire [5:0] Q_b5;
//wire [5:0] Q_b6;
//wire [5:0] Q_b7;

GND gnd_0(.Y(Gnd));
VCC vcc_0(.Y(Vcc));

mux_2x1 mux_0(.Data0_port(Gnd), .Data1_port(Vcc), .Sel0(Psel0), .Result(mx0));
mux_2x1 mux_1(.Data0_port(Gnd), .Data1_port(Vcc), .Sel0(Psel1), .Result(mx1));

counter_13 counter_0(.Enable(RC_en), .Aclr(RC_clr), .Clock(RC_clk), .Q(rc));

decoder_2to4 decoder_0(.Data0(rc[11]), .Data1(rc[12]), .Eq(dec));

NAND2 nand_0w(.A(dec[0]), .B(Write), .Y(y_0w));
NAND2 nand_0r(.A(dec[0]), .B(Read), .Y(y_0r));

ram_2048x6 ram_blk0(.Data(DIN), .Q(Q_b0), .WAddress(rc[10:0]), .RAddress(rc[10:0]),
                .WE(y_0w), .RE(y_0r), .WClock(Wclk), .RClock(Rclk));

assign DIN[0]=mx0, DIN[1]=mx1, DIN[2]=mx0, DIN[3]=mx1, DIN[4]=mx0, DIN[5]=mx1;

NAND2 nand_1w(.A(dec[1]), .B(Write), .Y(y_1w));
NAND2 nand_1r(.A(dec[1]), .B(Read), .Y(y_1r));

ram_2048x6 ram_blk1(.Data(DIN), .Q(Q_b1), .WAddress(rc[10:0]), .RAddress(rc[10:0]),
                .WE(y_1w), .RE(y_1r), .WClock(Wclk), .RClock(Rclk));

NAND2 nand_2w(.A(dec[2]), .B(Write), .Y(y_2w));
NAND2 nand_2r(.A(dec[2]), .B(Read), .Y(y_2r));
```

```
ram_2048x6 ram_blk2(.Data(DIN),
                .Q(Q_b2), .WAddress(rc[10:0]), .RAddress(rc[10:0]),
                .WE(y_2w), .RE(y_2r), .WClock(Wclk), .RClock(Rclk));

NAND2 nand_3w(.A(dec[3]), .B(Write), .Y(y_3w));
NAND2 nand_3r(.A(dec[3]), .B(Read), .Y(y_3r));

ram_2048x6 ram_blk3(.Data(DIN),
                .Q(Q_b3), .WAddress(rc[10:0]), .RAddress(rc[10:0]),
                .WE(y_3w), .RE(y_3r), .WClock(Wclk), .RClock(Rclk));

/* NAND2 nand_4w(.A(dec[4]), .B(Write), .Y(y_4w));
NAND2 nand_4r(.A(dec[4]), .B(Read), .Y(y_4r));

ram_2048x3 ram_blk4(.Data(DIN),
                .Q(Q_b4), .WAddress(rc[10:0]), .RAddress(rc[10:0]),
                .WE(y_4w), .RE(y_4r), .WClock(Wclk), .RClock(Rclk));

NAND2 nand_5w(.A(dec[5]), .B(Write), .Y(y_5w));
NAND2 nand_5r(.A(dec[5]), .B(Read), .Y(y_5r));

ram_2048x3 ram_blk5(.Data(DIN),
                .Q(Q_b5), .WAddress(rc[10:0]), .RAddress(rc[10:0]),
                .WE(y_5w), .RE(y_5r), .WClock(Wclk), .RClock(Rclk));

NAND2 nand_6w(.A(dec[6]), .B(Write), .Y(y_6w));
NAND2 nand_6r(.A(dec[6]), .B(Read), .Y(y_6r));

ram_2048x3 ram_blk6(.Data(DIN),
                .Q(Q_b6), .WAddress(rc[10:0]), .RAddress(rc[10:0]),
                .WE(y_6w), .RE(y_6r), .WClock(Wclk), .RClock(Rclk));

NAND2 nand_7w(.A(dec[7]), .B(Write), .Y(y_7w));
NAND2 nand_7r(.A(dec[7]), .B(Read), .Y(y_7r));

ram_2048x3 ram_blk7(.Data(DIN),
                .Q(Q_b7), .WAddress(rc[10:0]), .RAddress(rc[10:0]),
                .WE(y_7w), .RE(y_7r), .WClock(Wclk), .RClock(Rclk)); */

mux_6x4 mux_6x4_0(.Data0_port(Q_b0), .Data1_port(Q_b1), .Data2_port(Q_b2),
               .Data3_port(Q_b3), .Sel0(rc[11]),
               .Sel1(rc[12]), .Result(Q_RAM));

endmodule
```

```
`timescale 1 ns/100 ps
// Version: 6.0 SP3 6.0.30.3


module mux_2x1(Data0_port,Data1_port,Sel0,Result);
input Data0_port, Data1_port, Sel0;
output  Result;


    MX2 MX2_Result(.A(Data0_port), .B(Data1_port), .S(Sel0), .Y(
        Result));

endmodule

`timescale 1 ns/100 ps
// Version: 6.2 SP2 6.2.52.7


module counter_13(Enable,Aclr,Clock,Q);
input Enable, Aclr, Clock;
output [12:0] Q;

    wire ClrAux_0_net, ClrAux_7_net, MX2_1_Y, MX2_7_Y, MX2_4_Y,
        CM8_0_Y, MX2_10_Y, MX2_9_Y, MX2_3_Y, MX2_5_Y, MX2_6_Y,
        MX2_0_Y, MX2_8_Y, MX2_2_Y, MX2_11_Y, VCC, GND;

    VCC VCC_1_net(.Y(VCC));
    GND GND_1_net(.Y(GND));
    DFC1D DFC1D_Q_7_inst(.D(MX2_1_Y), .CLK(Q[6]), .CLR(
        ClrAux_7_net), .Q(Q[7]));
    DFC1D DFC1D_Q_1_inst(.D(MX2_7_Y), .CLK(Q[0]), .CLR(
        ClrAux_0_net), .Q(Q[1]));
    BUFF BUFF_ClrAux_0_inst(.A(Aclr), .Y(ClrAux_0_net));
    MX2 MX2_9(.A(VCC), .B(GND), .S(Q[5]), .Y(MX2_9_Y));
    DFC1D DFC1D_Q_2_inst(.D(MX2_6_Y), .CLK(Q[1]), .CLR(
        ClrAux_0_net), .Q(Q[2]));
    MX2 MX2_0(.A(VCC), .B(GND), .S(Q[8]), .Y(MX2_0_Y));
    DFC1D DFC1D_Q_12_inst(.D(MX2_4_Y), .CLK(Q[11]), .CLR(
        ClrAux_7_net), .Q(Q[12]));
    DFC1D DFC1D_Q_3_inst(.D(MX2_11_Y), .CLK(Q[2]), .CLR(
        ClrAux_0_net), .Q(Q[3]));
    DFC1D DFC1D_Q_4_inst(.D(MX2_5_Y), .CLK(Q[3]), .CLR(
        ClrAux_0_net), .Q(Q[4]));
    CM8 CM8_0(.D0(GND), .D1(VCC), .D2(VCC), .D3(GND), .S00(Q[0]),
        .S01(VCC), .S10(Enable), .S11(GND), .Y(CM8_0_Y));
    MX2 MX2_11(.A(VCC), .B(GND), .S(Q[3]), .Y(MX2_11_Y));
    DFC1B DFC1B_Q_0_inst(.D(CM8_0_Y), .CLK(Clock), .CLR(
        ClrAux_0_net), .Q(Q[0]));
    MX2 MX2_6(.A(VCC), .B(GND), .S(Q[2]), .Y(MX2_6_Y));
    MX2 MX2_3(.A(VCC), .B(GND), .S(Q[10]), .Y(MX2_3_Y));
    DFC1D DFC1D_Q_11_inst(.D(MX2_10_Y), .CLK(Q[10]), .CLR(
        ClrAux_7_net), .Q(Q[11]));
    MX2 MX2_10(.A(VCC), .B(GND), .S(Q[11]), .Y(MX2_10_Y));
    BUFF BUFF_ClrAux_7_inst(.A(Aclr), .Y(ClrAux_7_net));
    MX2 MX2_4(.A(VCC), .B(GND), .S(Q[12]), .Y(MX2_4_Y));
    DFC1D DFC1D_Q_5_inst(.D(MX2_9_Y), .CLK(Q[4]), .CLR(
```

```
    ClrAux_0_net), .Q(Q[5]));
  DFC1D DFC1D_Q_9_inst(.D(MX2_8_Y), .CLK(Q[8]), .CLR(
    ClrAux_7_net), .Q(Q[9]));
  MX2 MX2_5(.A(VCC), .B(GND), .S(Q[4]), .Y(MX2_5_Y));
  MX2 MX2_8(.A(VCC), .B(GND), .S(Q[9]), .Y(MX2_8_Y));
  DFC1D DFC1D_Q_8_inst(.D(MX2_0_Y), .CLK(Q[7]), .CLR(
    ClrAux_7_net), .Q(Q[8]));
  MX2 MX2_2(.A(VCC), .B(GND), .S(Q[6]), .Y(MX2_2_Y));
  MX2 MX2_7(.A(VCC), .B(GND), .S(Q[1]), .Y(MX2_7_Y));
  MX2 MX2_1(.A(VCC), .B(GND), .S(Q[7]), .Y(MX2_1_Y));
  DFC1D DFC1D_Q_6_inst(.D(MX2_2_Y), .CLK(Q[5]), .CLR(
    ClrAux_0_net), .Q(Q[6]));
  DFC1D DFC1D_Q_10_inst(.D(MX2_3_Y), .CLK(Q[9]), .CLR(
    ClrAux_7_net), .Q(Q[10]));

endmodule

`timescale 1 ns/100 ps
// Version: 6.2 SP2 6.2.52.7


module decoder_2to4(Data0,Data1,Eq);
input Data0, Data1;
output [3:0] Eq;


  AND2A AND2A_Eq_1_inst(.A(Data1), .B(Data0), .Y(Eq[1]));
  AND2 AND2_Eq_3_inst(.A(Data0), .B(Data1), .Y(Eq[3]));
  AND2A AND2A_Eq_2_inst(.A(Data0), .B(Data1), .Y(Eq[2]));
  AND2B AND2B_Eq_0_inst(.A(Data0), .B(Data1), .Y(Eq[0]));

endmodule

`timescale 1 ns/100 ps
// Version: 6.2 SP2 6.2.52.7


module ram_2048x6(Data,Q,WAddress,RAddress,WE,RE,WClock,RClock);
input [5:0] Data;
output [5:0] Q;
input [10:0] WAddress, RAddress;
input WE, RE, WClock, RClock;

  wire WEP, REP, VCC, GND;

  VCC VCC_1_net(.Y(VCC));
  GND GND_1_net(.Y(GND));
  RAM64K36P ram_2048x6_R0C2(.WCLK(WClock), .RCLK(RClock),
    .DEPTH0(GND), .DEPTH1(GND), .DEPTH2(GND), .DEPTH3(GND),
    .WEN(WEP), .WW0(VCC), .WW1(GND), .WW2(GND), .WRAD0(
    WAddress[0]), .WRAD1(WAddress[1]), .WRAD2(WAddress[2]),
    .WRAD3(WAddress[3]), .WRAD4(WAddress[4]), .WRAD5(
    WAddress[5]), .WRAD6(WAddress[6]), .WRAD7(WAddress[7]),
    .WRAD8(WAddress[8]), .WRAD9(WAddress[9]), .WRAD10(
    WAddress[10]), .WRAD11(GND), .WRAD12(GND), .WRAD13(GND),
    .WRAD14(GND), .WRAD15(GND), .WD0(Data[4]), .WD1(Data[5]),
```

```
    .WD2(GND), .WD3(GND), .WD4(GND), .WD5(GND), .WD6(GND),
    .WD7(GND), .WD8(GND), .WD9(GND), .WD10(GND), .WD11(GND),
    .WD12(GND), .WD13(GND), .WD14(GND), .WD15(GND), .WD16(GND)
    , .WD17(GND), .WD18(GND), .WD19(GND), .WD20(GND), .WD21(
    GND), .WD22(GND), .WD23(GND), .WD24(GND), .WD25(GND),
    .WD26(GND), .WD27(GND), .WD28(GND), .WD29(GND), .WD30(GND)
    , .WD31(GND), .WD32(GND), .WD33(GND), .WD34(GND), .WD35(
    GND), .REN(REP), .RW0(VCC), .RW1(GND), .RW2(GND), .RDAD0(
    RAddress[0]), .RDAD1(RAddress[1]), .RDAD2(RAddress[2]),
    .RDAD3(RAddress[3]), .RDAD4(RAddress[4]), .RDAD5(
    RAddress[5]), .RDAD6(RAddress[6]), .RDAD7(RAddress[7]),
    .RDAD8(RAddress[8]), .RDAD9(RAddress[9]), .RDAD10(
    RAddress[10]), .RDAD11(GND), .RDAD12(GND), .RDAD13(GND),
    .RDAD14(GND), .RDAD15(GND), .RD0(Q[4]), .RD1(Q[5]), .RD2()
    , .RD3(), .RD4(), .RD5(), .RD6(), .RD7(), .RD8(), .RD9(),
    .RD10(), .RD11(), .RD12(), .RD13(), .RD14(), .RD15(),
    .RD16(), .RD17(), .RD18(), .RD19(), .RD20(), .RD21(),
    .RD22(), .RD23(), .RD24(), .RD25(), .RD26(), .RD27(),
    .RD28(), .RD29(), .RD30(), .RD31(), .RD32(), .RD33(),
    .RD34(), .RD35());
  INV REBUBBLE(.A(RE), .Y(REP));
  INV WEBUBBLE(.A(WE), .Y(WEP));
  RAM64K36P ram_2048x6_R0C1(.WCLK(WClock), .RCLK(RClock),
    .DEPTH0(GND), .DEPTH1(GND), .DEPTH2(GND), .DEPTH3(GND),
    .WEN(WEP), .WW0(VCC), .WW1(GND), .WW2(GND), .WRAD0(
    WAddress[0]), .WRAD1(WAddress[1]), .WRAD2(WAddress[2]),
    .WRAD3(WAddress[3]), .WRAD4(WAddress[4]), .WRAD5(
    WAddress[5]), .WRAD6(WAddress[6]), .WRAD7(WAddress[7]),
    .WRAD8(WAddress[8]), .WRAD9(WAddress[9]), .WRAD10(
    WAddress[10]), .WRAD11(GND), .WRAD12(GND), .WRAD13(GND),
    .WRAD14(GND), .WRAD15(GND), .WD0(Data[2]), .WD1(Data[3]),
    .WD2(GND), .WD3(GND), .WD4(GND), .WD5(GND), .WD6(GND),
    .WD7(GND), .WD8(GND), .WD9(GND), .WD10(GND), .WD11(GND),
    .WD12(GND), .WD13(GND), .WD14(GND), .WD15(GND), .WD16(GND)
    , .WD17(GND), .WD18(GND), .WD19(GND), .WD20(GND), .WD21(
    GND), .WD22(GND), .WD23(GND), .WD24(GND), .WD25(GND),
    .WD26(GND), .WD27(GND), .WD28(GND), .WD29(GND), .WD30(GND)
    , .WD31(GND), .WD32(GND), .WD33(GND), .WD34(GND), .WD35(
    GND), .REN(REP), .RW0(VCC), .RW1(GND), .RW2(GND), .RDAD0(
    RAddress[0]), .RDAD1(RAddress[1]), .RDAD2(RAddress[2]),
    .RDAD3(RAddress[3]), .RDAD4(RAddress[4]), .RDAD5(
    RAddress[5]), .RDAD6(RAddress[6]), .RDAD7(RAddress[7]),
    .RDAD8(RAddress[8]), .RDAD9(RAddress[9]), .RDAD10(
    RAddress[10]), .RDAD11(GND), .RDAD12(GND), .RDAD13(GND),
    .RDAD14(GND), .RDAD15(GND), .RD0(Q[2]), .RD1(Q[3]), .RD2()
    , .RD3(), .RD4(), .RD5(), .RD6(), .RD7(), .RD8(), .RD9(),
    .RD10(), .RD11(), .RD12(), .RD13(), .RD14(), .RD15(),
    .RD16(), .RD17(), .RD18(), .RD19(), .RD20(), .RD21(),
    .RD22(), .RD23(), .RD24(), .RD25(), .RD26(), .RD27(),
    .RD28(), .RD29(), .RD30(), .RD31(), .RD32(), .RD33(),
    .RD34(), .RD35());
  RAM64K36P ram_2048x6_R0C0(.WCLK(WClock), .RCLK(RClock),
    .DEPTH0(GND), .DEPTH1(GND), .DEPTH2(GND), .DEPTH3(GND),
    .WEN(WEP), .WW0(VCC), .WW1(GND), .WW2(GND), .WRAD0(
    WAddress[0]), .WRAD1(WAddress[1]), .WRAD2(WAddress[2]),
    .WRAD3(WAddress[3]), .WRAD4(WAddress[4]), .WRAD5(
```

```
        WAddress[5]), .WRAD6(WAddress[6]), .WRAD7(WAddress[7]),
        .WRAD8(WAddress[8]), .WRAD9(WAddress[9]), .WRAD10(
        WAddress[10]), .WRAD11(GND), .WRAD12(GND), .WRAD13(GND),
        .WRAD14(GND), .WRAD15(GND), .WD0(Data[0]), .WD1(Data[1]),
        .WD2(GND), .WD3(GND), .WD4(GND), .WD5(GND), .WD6(GND),
        .WD7(GND), .WD8(GND), .WD9(GND), .WD10(GND), .WD11(GND),
        .WD12(GND), .WD13(GND), .WD14(GND), .WD15(GND), .WD16(GND)
        , .WD17(GND), .WD18(GND), .WD19(GND), .WD20(GND), .WD21(
        GND), .WD22(GND), .WD23(GND), .WD24(GND), .WD25(GND),
        .WD26(GND), .WD27(GND), .WD28(GND), .WD29(GND), .WD30(GND)
        , .WD31(GND), .WD32(GND), .WD33(GND), .WD34(GND), .WD35(
        GND), .REN(REP), .RW0(VCC), .RW1(GND), .RW2(GND), .RDAD0(
        RAddress[0]), .RDAD1(RAddress[1]), .RDAD2(RAddress[2]),
        .RDAD3(RAddress[3]), .RDAD4(RAddress[4]), .RDAD5(
        RAddress[5]), .RDAD6(RAddress[6]), .RDAD7(RAddress[7]),
        .RDAD8(RAddress[8]), .RDAD9(RAddress[9]), .RDAD10(
        RAddress[10]), .RDAD11(GND), .RDAD12(GND), .RDAD13(GND),
        .RDAD14(GND), .RDAD15(GND), .RD0(Q[0]), .RD1(Q[1]), .RD2()
        , .RD3(), .RD4(), .RD5(), .RD6(), .RD7(), .RD8(), .RD9(),
        .RD10(), .RD11(), .RD12(), .RD13(), .RD14(), .RD15(),
        .RD16(), .RD17(), .RD18(), .RD19(), .RD20(), .RD21(),
        .RD22(), .RD23(), .RD24(), .RD25(), .RD26(), .RD27(),
        .RD28(), .RD29(), .RD30(), .RD31(), .RD32(), .RD33(),
        .RD34(), .RD35());

endmodule

`timescale 1 ns/100 ps
// Version: 6.2 SP2 6.2.52.7

module mux_6x4(Data0_port,Data1_port,Data2_port,Data3_port,Sel0,
        Sel1,Result);
input [5:0] Data0_port, Data1_port, Data2_port, Data3_port;
input Sel0, Sel1;
output [5:0] Result;

    MX4 MX4_Result_0_inst(.D0(Data0_port[0]), .D1(Data1_port[0]),
        .D2(Data2_port[0]), .D3(Data3_port[0]), .S0(Sel0), .S1(
        Sel1), .Y(Result[0]));
    MX4 MX4_Result_2_inst(.D0(Data0_port[2]), .D1(Data1_port[2]),
        .D2(Data2_port[2]), .D3(Data3_port[2]), .S0(Sel0), .S1(
        Sel1), .Y(Result[2]));
    MX4 MX4_Result_5_inst(.D0(Data0_port[5]), .D1(Data1_port[5]),
        .D2(Data2_port[5]), .D3(Data3_port[5]), .S0(Sel0), .S1(
        Sel1), .Y(Result[5]));
    MX4 MX4_Result_1_inst(.D0(Data0_port[1]), .D1(Data1_port[1]),
        .D2(Data2_port[1]), .D3(Data3_port[1]), .S0(Sel0), .S1(
        Sel1), .Y(Result[1]));
    MX4 MX4_Result_4_inst(.D0(Data0_port[4]), .D1(Data1_port[4]),
        .D2(Data2_port[4]), .D3(Data3_port[4]), .S0(Sel0), .S1(
        Sel1), .Y(Result[4]));
    MX4 MX4_Result_3_inst(.D0(Data0_port[3]), .D1(Data1_port[3]),
        .D2(Data2_port[3]), .D3(Data3_port[3]), .S0(Sel0), .S1(
        Sel1), .Y(Result[3]));

endmodule
```



Microsemi Corporate Headquarters
One Enterprise, Aliso Viejo CA 92656 USA
Within the USA: +1 (949) 380-6100
Sales: +1 (949) 380-6136
Fax: +1 (949) 215-4996

Microsemi Corporation (NASDAQ: MSCC) offers a comprehensive portfolio of semiconductor solutions for: aerospace, defense and security; enterprise and communications; and industrial and alternative energy markets. Products include high-performance, high-reliability analog and RF devices, mixed signal and RF integrated circuits, customizable SoCs, FPGAs, and complete subsystems. Microsemi is headquartered in Aliso Viejo, Calif. Learn more at **www.microsemi.com**.

© 2012 Microsemi Corporation. All rights reserved. Microsemi and the Microsemi logo are trademarks of Microsemi Corporation. All other trademarks and service marks are the property of their respective owners.