


Microsemi Adaptec® 7805 in 1U Chassis

A 7805 RAID adapter with right angle mini SAS HD cable connector in a generic 1U chassis with 8 storage bays for 2.5" drives with backplanes with right angle SATA connectors and sideband



Requirements

1U chassis are one of the most challenging rack-mount configurations because of the very low profile footprint. This presents some challenges for RAID adapter cards with respect to:

- Height of the boards
- Limited performance of a PCIe Gen3 RAID card with expanders
- Cables with straight connectors

Series 7 RAID Solution

- The 8-port RAID adapter, an MD2- Low Profile card, easily plugs into a PCI Gen3 slot, with 200 LFM airflow, in a 1U chassis.
- Microsemi's new right-angle connectors at the adapter end and also at the drive end, are an ideal solution for this super low profile chassis configuration. For more information on SAS HD cables visit: <http://www.microsemi.com/products/storage/cables-accessories/cables-accessories>.

The illustration above is specific to a RAID card with 8 internal ports. If a specific 1U chassis configuration contains a full height slot, the 24-port 71685 with 2 external connectors allows connectivity to an external JBOD without compromising performance and with no need for an internal expander.

8-Port RAID Card with 1 Internal Cable

Configuration

- 7805: 8 internal native SAS/SATA ports, MD2-low profile. Single Part Number: 2274100-R
- The ACK-I-rA-HDmSAS-4rASATA-SB-.8M is an internal "right angle" Mini Serial Attached SCSI HD x4 (SFF-8643) to "right angle" (4) x1 Serial ATA fan-out cable with sideband signals (SFF-8448). It measures 0.8 meters and is used for connecting a SAS/SATA adapter to SATA disks, or a SAS/SATA backplane. Part Number: 2279900-R
- HDDs and SSDs – check the compatibility guide at: <http://www.microsemi.com/products/storage/compatibility>
- Flash Module AFM-700 Optional: add-on super capacitor module for maintenance-free cache protection with real-time monitoring

Microsemi makes no warranty, representation, or guarantee regarding the information contained herein or the suitability of its products and services for any particular purpose, nor does Microsemi assume any liability whatsoever arising out of the application or use of any product or circuit. The products sold hereunder and any other products sold by Microsemi have been subject to limited testing and should not be used in conjunction with mission-critical equipment or applications. Any performance specifications are believed to be reliable but are not verified, and Buyer must conduct and complete all performance and other testing of the products, alone and together with, or installed in, any end-products. Buyer shall not rely on any data and performance specifications or parameters provided by Microsemi. It is the Buyer's responsibility to independently determine suitability of any products and to test and verify the same. The information provided by Microsemi hereunder is provided "as is, where is" and with all faults, and the entire risk associated with such information is entirely with the Buyer. Microsemi does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other IP rights, whether with regard to such information itself or anything described by such information. Information provided in this document is proprietary to Microsemi, and Microsemi reserves the right to make any changes to the information in this document or to any products and services at any time without notice.



Microsemi Corporate Headquarters
 One Enterprise, Aliso Viejo, CA 92656 USA
 Within the USA: +1 (800) 713-4113
 Outside the USA: +1 (949) 380-6100
 Sales: +1 (949) 380-6136
 Fax: +1 (949) 215-4996
 email: sales.support@microsemi.com
www.microsemi.com

Microsemi Corporation (Nasdaq: MSCC) offers a comprehensive portfolio of semiconductor and system solutions for aerospace & defense, communications, data center and industrial markets. Products include high-performance and radiation-hardened analog mixed-signal integrated circuits, FPGAs, SoCs and ASICs; power management products; timing and synchronization devices and precise time solutions, setting the world's standard for time; voice processing devices; RF solutions; discrete components; enterprise storage and communication solutions, security technologies and scalable anti-tamper products; Ethernet solutions; Power-over-Ethernet ICs and midspans; as well as custom design capabilities and services. Microsemi is headquartered in Aliso Viejo, Calif., and has approximately 4,800 employees globally. Learn more at www.microsemi.com.

©2016 Microsemi Corporation. All rights reserved. Microsemi and the Microsemi logo are registered trademarks of Microsemi Corporation. All other trademarks and service marks are the property of their respective owners.