

Customer Notification No: CN1674

Customer Advisory Notice (CAN)

Subject: Resetting SmartFusion Device After In-Application Programming (IAP) Under Certain Conditions

Description

During IAP programming, if an external clock source is used to drive the phase-locked loop (PLL) that is used to clock the microcontroller subsystem (MSS), a SmartFusion[®] device may hang at the end of the IAP operation. Any SmartFusion device could potentially have this problem. The list of SmartFusion part numbers is provided in Appendix A.

When switching between programming and operational modes, in-rush current causes the PLL to lose the lock signal as well as the clock. In some instances the clock never recovers. Since the ARM Cortex-M3 in the SmartFusion device depends on the clock source for proper operation, it no longer can function in this scenario. This behavior does not occur in standard programming or when the internal oscillator is used to drive the MSS clock.

Workaround

To mitigate this issue, a software workaround has been identified which involves performing a system reset at the end of the IAP operation, instead of the normal ISC_DISABLE instruction. This resets the device and the Cortex-M3. This workaround will be available with the MSS IAP driver v2.3 by 11th November, 2016. This IAP software version will be available through the [Firmware Catalog](#).

This IAP software release has a variable called `enable_system_reset_on_exit` defined in the `dp_user.c` file. The default value of this variable is TRUE to perform the reset operation at the end of the IAP operation. You may choose to set it to FALSE if you want the device to go through the normal process of exiting programming mode, avoiding the system reset. Manual setting may be desired if the internal oscillator is used to drive the MSS clock as the device hang behavior is not observed in this use model.

Till the time updated IAP software is available, you can change the code manually by calling `NVIC_SystemReset ()` function in the `dp_exit ()` function as shown in the following code snippet:

```
void dp_exit(void)
{
#ifdef NVM_SUPPORT
if (
((device_family & SFS_BIT) == SFS_BIT) &&
(dat_support_status | (NVM0_DAT_SUPPORT_BIT | NVM1_DAT_SUPPORT_BIT |
NVM2_DAT_SUPPORT_BIT | NVM3_DAT_SUPPORT_BIT)) &&
(
(Action_code == DP_PROGRAM_ACTION_CODE) ||
(Action_code == DP_VERIFY_ACTION_CODE) ||
(Action_code == DP_PROGRAM_NVM_ACTION_CODE) ||
```

```

(Action_code == DP_VERIFY_NVM_ACTION_CODE) ||
(Action_code == DP_PROGRAM_PRIVATE_CLIENTS_ACTION_CODE) ||
(Action_code == DP_VERIFY_PRIVATE_CLIENTS_ACTION_CODE) ||
(
((device_family & SFS_BIT) == SFS_BIT) &&
((Action_code == DP_PROGRAM_ARRAY_ACTION_CODE) || (Action_code ==
DP_VERIFY_ARRAY_ACTION_CODE))
)
)
)
{
    dp_exit_access_nvm();
}
#endif
    NVIC_SystemReset();
    while( 1 )
    {
        ;
    }
    return;
}

```

Note: Before compiling the code, add the below header file in the `dpalg.c` file:
`#include "a2fxxm3.h"`

Microsemi Corporation

One Enterprise, Aliso Viejo, CA 92656 USA
 Within the USA: +1 (800) 713-4113 Outside the USA: +1 (949) 380-6100 Fax: +1 (949) 215-4996 Email: sales.support@microsemi.com, www.microsemi.com
 MSC-F-0003 Rev 3

Appendix A: SmartFusion Device List

A2F060	A2F200	A2F500
A2F060M3E-1CS288	A2F200M3F-1CS288	A2F500M3G-1CS288
A2F060M3E-1CS288I	A2F200M3F-1CS288I	A2F500M3G-1CS288I
A2F060M3E-1CSG288	A2F200M3F-1CSG288	A2F500M3G-1CSG288
A2F060M3E-1CSG288I	A2F200M3F-1CSG288I	A2F500M3G-1CSG288I
A2F060M3E-1FG256	A2F200M3F-1FG256	A2F500M3G-1FG256
A2F060M3E-1FG256I	A2F200M3F-1FG256I	A2F500M3G-1FG256I
A2F060M3E-1FG256M	A2F200M3F-1FG484	A2F500M3G-1FG256M
A2F060M3E-1FGG256	A2F200M3F-1FG484I	A2F500M3G-1FG484
A2F060M3E-1FGG256I	A2F200M3F-1FGG256	A2F500M3G-1FG484I
A2F060M3E-1FGG256M	A2F200M3F-1FGG256I	A2F500M3G-1FG484M
A2F060M3E-1TQ144	A2F200M3F-1FGG484	A2F500M3G-1FGG256
A2F060M3E-1TQ144I	A2F200M3F-1FGG484I	A2F500M3G-1FGG256I
A2F060M3E-1TQG144	A2F200M3F-1PQ208	A2F500M3G-1FGG256M
A2F060M3E-1TQG144I	A2F200M3F-1PQ208I	A2F500M3G-1FGG484
A2F060M3E-CS288	A2F200M3F-1PQG208	A2F500M3G-1FGG484I
A2F060M3E-CS288I	A2F200M3F-1PQG208I	A2F500M3G-1FGG484M
A2F060M3E-CSG288	A2F200M3F-CS288	A2F500M3G-1PQ208
A2F060M3E-CSG288I	A2F200M3F-CS288I	A2F500M3G-1PQ208I
A2F060M3E-FG256	A2F200M3F-CSG288	A2F500M3G-1PQG208
A2F060M3E-FG256I	A2F200M3F-CSG288I	A2F500M3G-1PQG208I
A2F060M3E-FG256M	A2F200M3F-FG256	A2F500M3G-CS288
A2F060M3E-FGG256	A2F200M3F-FG256I	A2F500M3G-CS288I
A2F060M3E-FGG256I	A2F200M3F-FG484	A2F500M3G-CSG288
A2F060M3E-FGG256M	A2F200M3F-FG484I	A2F500M3G-CSG288I
A2F060M3E-TQ144	A2F200M3F-FGG256	A2F500M3G-FG256
A2F060M3E-TQ144I	A2F200M3F-FGG256I	A2F500M3G-FG256I
A2F060M3E-TQG144	A2F200M3F-FGG484	A2F500M3G-FG256M
A2F060M3E-TQG144I	A2F200M3F-FGG484I	A2F500M3G-FG484
-	A2F200M3F-PQ208	A2F500M3G-FG484I
-	A2F200M3F-PQ208I	A2F500M3G-FG484M
-	A2F200M3F-PQG208	A2F500M3G-FGG256
-	A2F200M3F-PQG208I	A2F500M3G-FGG256I
-	-	A2F500M3G-FGG256M
-	-	A2F500M3G-FGG484
-	-	A2F500M3G-FGG484I
-	-	A2F500M3G-FGG484M
-	-	A2F500M3G-PQ208
-	-	A2F500M3G-PQ208I
-	-	A2F500M3G-PQG208
-	-	A2F500M3G-PQG208I

Microsemi Corporation

One Enterprise, Aliso Viejo, CA 92656 USA

Within the USA: +1 (800) 713-4113 Outside the USA: +1 (949) 380-6100 Fax: +1 (949) 215-4996 Email: sales.support@microsemi.com, www.microsemi.com

MSC-F-0003 Rev 3

Contact Information

If you have any questions, please contact Microsemi's SoC technical support at soc_tech@microsemi.com.

Regards,

Microsemi Corporation

Customer Notice (CN) or Customer Advisory Notice (CAN) are confidential and proprietary information of Microsemi and is intended only for distribution by Microsemi to its customers, for customers' use only. It must not be copied or provided to any third party without Microsemi's prior written consent.



Microsemi Corporate Headquarters
One Enterprise, Aliso Viejo, CA 92656 USA
Within the USA: +1 (800) 713-4113
Outside the USA: +1 (949) 380-6100
Sales: +1 (949) 380-6136
Fax: +1 (949) 215-4996
E-mail: sales.support@microsemi.com
www.microsemi.com

©2016 Microsemi Corporation. All rights reserved.
Microsemi and the Microsemi logo are registered trademarks of Microsemi Corporation. All other trademarks and service marks are the property of their respective owners.

Microsemi makes no warranty, representation, or guarantee regarding the information contained herein or the suitability of its products and services for any particular purpose, nor does Microsemi assume any liability whatsoever arising out of the application or use of any product or circuit. The products sold hereunder and any other products sold by Microsemi have been subject to limited testing and should not be used in conjunction with mission-critical equipment or applications. Any performance specifications are believed to be reliable but are not verified, and Buyer must conduct and complete all performance and other testing of the products, alone and together with, or installed in, any end-products. Buyer shall not rely on any data and performance specifications or parameters provided by Microsemi. It is the Buyer's responsibility to independently determine suitability of any products and to test and verify the same. The information provided by Microsemi hereunder is provided "as is, where is" and with all faults, and the entire risk associated with such information is entirely with the Buyer. Microsemi does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other IP rights, whether with regard to such information itself or anything described by such information. Information provided in this document is proprietary to Microsemi, and Microsemi reserves the right to make any changes to the information in this document or to any products and services at any time without notice.

About Microsemi

Microsemi Corporation (Nasdaq: MSCC) offers a comprehensive portfolio of semiconductor and system solutions for aerospace & defense, communications, data center and industrial markets. Products include high-performance and radiation-hardened analog mixed-signal integrated circuits, FPGAs, SoCs and ASICs; power management products; timing and synchronization devices and precise time solutions, setting the world's standard for time; voice processing devices; RF solutions; discrete components; enterprise storage and communication solutions; security technologies and scalable anti-tamper products; Ethernet solutions; Power-over-Ethernet ICs and midspans; as well as custom design capabilities and services. Microsemi is headquartered in Aliso Viejo, Calif., and has approximately 4,800 employees globally. Learn more at www.microsemi.com.

MSC-F-0003 Rev 3

Do Not Distribute Outside Microsemi Without Written Permission

Page 4 of 4