



# **Power over Ethernet**

## **Power View Pro**

### **User Guide**

**Revision 1.6**  
**Catalog Number PD\_NMS\_IPV6\_UG**

## Power Over Ethernet Power View Pro User Guide

---

### Acknowledgements

All other products or trademarks are property of their respective owners.

The product described by this manual is a licensed product of Microsemi.

### Abbreviations and Terminology

Abbreviations are spelled out in full when first used or are listed in Table 1-1. Only industry-standard terms are used throughout this manual.

**Note:** Covered under U.S patent S/N 6,473,608. Other patents are pending.

## Table of Contents

1	About this Guide .....	7
1.1	Objectives .....	7
1.2	Audience .....	7
1.3	Organization .....	9
1.4	Conventions .....	9
1.5	Related Documentation .....	9
1.6	Abbreviations .....	10
2	Introducing the Power View Pro (IPv4, IPv6) .....	11
2.1	Features .....	11
2.2	System Capabilities .....	12
2.3	POE Capabilities .....	12
2.4	Configuration Options .....	12
2.5	Security and User Authentication .....	13
2.5.1	Web Security .....	13
2.5.2	SNMP Security .....	13
2.5.3	Telnet/SSH Security .....	14
3	Installation .....	15
3.1	System Requirements .....	15
3.2	Hardware Setup .....	15
3.3	Configuration Procedure .....	16
3.3.1	Connecting to Unit Using a Web Browser .....	16
3.3.2	Connecting to Unit Using Window's Telnet .....	16
3.3.3	Connecting to Unit Using serial port and a Hyper Terminal Application .....	16
3.3.4	Connecting via USB Serial Communication Virtual Port .....	18
3.3.5	Configuring the System via the serial port .....	19
3.4	Configuring the TFTP Server .....	22
4	Web Interface Description .....	23
4.1	Overview .....	23
4.2	Opening Screen .....	23
4.3	View Menu .....	24
4.3.1	View - Status Screen 65xx, 65xxG Midspan Series .....	24
4.3.2	View - Status Screen 90xxG, 95xxG, 96xxG four-pair High Power Midspan Series .....	25
4.3.3	View - Status Screen 55xxG energy efficient High Power Midspan Series .....	29
4.3.4	View - Status Screen Elements .....	31
4.3.5	View - Configuration Summary .....	35
4.3.6	View - Product Information .....	41
4.3.7	System Configuration Screen .....	42
4.3.8	System Configuration SNMP .....	55
4.3.9	System Configuration SNMPv3 .....	58
4.3.10	System Configuration Security .....	60
4.3.11	System Configuration - RADIUS .....	63
4.3.12	System Configuration - Dynamic UPS Power Management .....	64
4.3.13	System Configuration - Access List Filter .....	67
4.3.14	System Configuration - Product Parameters - 65xx, 65xxG Family .....	72
4.3.15	System Configuration - Product Parameters - 90xxG Family .....	73
4.3.16	System Configuration - Product Parameters - 95xxG Family .....	75
4.3.17	System Configuration - Product Parameters - 96xxG Family .....	77
4.3.18	System Configuration - Product Parameters - 55xxG Family .....	79
4.3.19	System Configuration Maintenance .....	81
4.4	Port Configuration Screen .....	83
4.4.1	Port Configuration - Enable/Disable .....	84
4.4.2	Port Configuration - Detailed .....	85
4.4.3	Port Configuration - Weekly Schedule .....	91
5	Midspan 90xxG, 95xxG, 55xxG, 96xxG – Power Backup and Power Management .....	93

# Power Over Ethernet Power View Pro User Guide

5.1	Viewing the Power Source Status .....	94
5.2	RPS Power Backup .....	95
5.3	Dual 90xxG, 95xxG, 96xxG, 55xxG Midspan Power Backup .....	97
5.3.1	Midspan 90xxG/95xxG/96xxG/55xxG to Midspan 90xxG/95xxG/96xxG/55xxG Power Shift .....	97
5.3.2	Changing Power Limit (%) by SNMP .....	98
5.3.3	Activating Dynamic UPS Power Management .....	99
5.3.4	Power Failure and Invalid Midspan to Midspan Power Backup Connection Report .....	99
6	SNMP Monitoring and Configuration .....	100
6.1	Enabling Midspan SNMP .....	100
6.2	SNMP MIBs .....	101
6.3	RFC3621 PoE MIB .....	101
6.4	Private MIB .....	103
7	Software Upgrade .....	105
7.1	Software upgrade types .....	105
7.2	Midspan Manager Module Software Upgrade .....	105
7.2.1	Upgrading from IPv4 to IPv6 (software version 3.xx to 4.xx) .....	106
7.2.2	Upgrading to Latest IPv6 Software Version (version 4.xx) .....	106
7.2.3	Checklist Prior to Performing Software Update .....	106
7.2.4	Performing software update .....	107
8	Troubleshooting .....	109

## List of Figures

Figure 2-1:	Management Deployment .....	12
Figure 3-1:	Connecting the PoE Unit .....	16
Figure 3-2:	Windows XP Hyper Terminal Specifications .....	17
Figure 3-3:	Putty Configuration Window .....	18
Figure 3-4:	PuTTY Serial Configuration Window Specifications .....	18
Figure 3-5:	Main Menu Screen .....	19
Figure 3-6:	View Menu Screen .....	20
Figure 3-7:	Configuration & Maintenance Menu .....	20
Figure 3-8:	NBTFTP Server Window .....	22
Figure 4-1:	Power View Pro Main Window .....	23
Figure 4-2:	View Menu .....	24
Figure 4-3:	View - Status Screen (65xx, 65xxG Midspan Series) .....	25
Figure 4-4:	View - Status Screen (90xxG High Power Midspan Series) .....	26
Figure 4-5:	View - Status Screen (95xxG four-pair High Power Midspan Series) .....	27
Figure 4-6:	View - Status Screen (96xxG PoH four-pair High Power Midspan Series) .....	28
Figure 4-7:	View - Status Screen (55xxG energy efficient High Power Midspan Series) .....	29
Figure 4-8:	Ports Status Panel .....	31
Figure 4-9:	Detailed Port Information .....	33
Figure 4-10:	Manual Override Deactivation key .....	34
Figure 4-11:	Weekly Activated/Deactivated Ports .....	35
Figure 4-12:	View - Configuration Summary Screen .....	36
Figure 4-13:	IP in-Use Window .....	37
Figure 4-14:	Remote Servers Window .....	37
Figure 4-15:	Date and Time Window .....	38
Figure 4-16:	Remote Trap SNMP Managers List .....	39
Figure 4-17:	Remote Access & Security Window .....	39
Figure 4-18:	Advanced Features Window .....	40
Figure 4-19:	View - Product Information Screen .....	41
Figure 4-20:	System Configuration Screen .....	42
Figure 4-21:	System Configuration - Network Screen .....	43
Figure 4-22:	Auto Services Configuration by DHCP .....	46
Figure 4-23:	Defining Vendor Class .....	46
Figure 4-24:	Set Vendor Class String .....	47
Figure 4-25:	Set Predefined Options .....	47

## Power Over Ethernet Power View Pro User Guide

Figure 4-26: Adding Predefined Sub Types .....	48
Figure 4-27: SNMP Manager Option Type .....	48
Figure 4-28: Midspan Option Code .....	48
Figure 4-29: SysLog Option Type .....	49
Figure 4-30: RADIUS Option Type .....	49
Figure 4-31: Scope Options Configurations .....	50
Figure 4-32: Midspan Scope Options .....	50
Figure 4-33: Configuring Scope Options .....	51
Figure 4-34: Advertised Scope Options .....	51
Figure 4-35: SNMP Scope Options .....	52
Figure 4-36: Setting SNMP Manager IP List .....	52
Figure 4-37: Midspan Automatic Service Configuration .....	53
Figure 4-38: Syslog Server Log Events .....	54
Figure 4-39: System Configuration SNMP Screen .....	56
Figure 4-40: SNMPv2 Window .....	56
Figure 4-41: Remote Trap SNMP Managers List .....	58
Figure 4-42: System Configuration SNMPv3 Screen .....	59
Figure 4-43: System Configuration Security Screen .....	60
Figure 4-44: Web Secure Access & Configuration Window .....	61
Figure 4-45: Telnet/SSH View & Configuration Window .....	61
Figure 4-46: Remote Access Window .....	62
Figure 4-47: RADIUS Configuration Screen .....	63
Figure 4-48: Dynamic UPS Power Management .....	65
Figure 4-49: Dynamic UPS Power Management Screen .....	66
Figure 4-50: Midspan Enforced Maximum Power Levels .....	67
Figure 4-51: UPS-Midspan Communication Failure .....	67
Figure 4-52: Access List Filtering .....	68
Figure 4-53: Access List Filtering .....	69
Figure 4-54: View ACL Filter Parameters from View Menu .....	69
Figure 4-55: View ACL Filter Parameters .....	70
Figure 4-56: View ACL Filter Statistics Counters .....	70
Figure 4-57: ACL Filter Configuration Example .....	71
Figure 4-58: System Configuration Product Parameters Screen .....	72
Figure 4-59: System Configuration Product Parameters Screen .....	73
Figure 4-60: System Configuration Product Parameters Screen .....	75
Figure 4-61: System Configuration Product Parameters Screen .....	77
Figure 4-62: System Configuration Product Parameters Screen .....	79
Figure 4-63: System Configuration Maintenance Screen .....	81
Figure 4-64: Port Configuration Screen .....	83
Figure 4-65: Port Configuration Enable/Disable Screen .....	84
Figure 4-66: Port Configuration Detailed Screen (65xx, 65xxG, 90xxG Family) .....	85
Figure 4-67: Port Configuration Detailed Screen (95xxG Family) .....	86
Figure 4-68: Port Configuration Detailed Screen (96xxG Family) .....	86
Figure 4-69: Port Configuration Detailed Screen (55xxG Family) .....	87
Figure 4-70: Port Configuration Detailed Screen (55xxG Family) .....	88
Figure 4-72: Port Configuration – Weekly Schedule .....	91
Figure 5-1: External Power Backup .....	93
Figure 5-2: Secondary Midspan Power Backup .....	93
Figure 5-3: Power Source Status .....	95
Figure 5-4: Power Backup Mode .....	96
Figure 5-5: View - Status Window (Power Shift Display) .....	97
Figure 5-6: Midspan Power Limit by SNMP .....	98
Figure 6-1: SNMPc Network Management Tool .....	100
Figure 6-2: MIB Tree Structure .....	102
Figure 6-3: MIBs Management Functionalities .....	103
Figure 7-1: System Software Architecture .....	105
Figure 7-2: Identifying Flash Memory Size .....	105

Figure 7-3: TFTP Server Root Folder Setting .....	107
---	-----

## List of Tables

Table 1-1: List of Abbreviations .....	10
Table 4-1: Main Status Indications .....	31
Table 4-2: 65xx, 65xxG, 90xxG, 95xxG and 55xxG Gigabit High Power Midspan Port Status Indications .....	32
Table 4-3: Midspan Status Table Details .....	33
Table 4-4: Detailed Port Description Information .....	34
Table 4-5: IP in User Parameters .....	37
Table 4-6: System Configuration Network Screen Details .....	44
Table 4-7: SNMPv2 Field Details .....	57
Table 4-8: System Information Window .....	57
Table 4-9: RFC3621 PoE MIB Parameters .....	57
Table 4-10: Weekly Schedule Icons Reported by View-Status Web Page .....	92
Table 5-1: Power Backup Connectivity Options .....	94
Table 5-2: SNMP Object IDs Affected by Midspan Power Backup Mode Connection .....	94
Table 5-3: <i>mainPowerUsageBudget</i> SNMP OiD Vs Midspan Maximum Power .....	99
Table 8-1: Troubleshooting Guide .....	109

## 1 About this Guide

The following sections define the manual objectives, concepts used, conventions used and associated documentation

### 1.1 Objectives

This User Guide introduces PowerDsine's **IPv6** capable Power View Pro Remote Web Managers used for managing PowerDsine's Power over Ethernet (PoE) product line of IPv6 capable Midspan devices including:

- 10/100Mbit Midspans
  - PD – 6506/AC/M: 6 port 10/100Mbit Midspan
  - PD – 6512/AC/M: 12 port 10/100Mbit Midspan
  - PD – 6524/AC/M: 24 port 10/100Mbit Midspan
  - PD – 6524/AC/M/F: 24 port 10/100Mbit full power Midspan

#### NOTE:



**Only Network Management Modules with internal FLASH memory of 4MB can be upgraded to latest IPv6 compliant software version. For further information see Midspan Manager Module Software Upgrade on page no. 105.**

- 1 Gigabit Midspans
  - PD – 6506G/AC/M: 6 port 1 Gigabit Midspan
  - PD – 6512G/AC/M: 12 port 1 Gigabit Midspan
  - PD – 6524G/AC/M: 24 port 1 Gigabit Midspan
  - PD – 6524G/AC/M/F: 24 port 1Gigabit full power Midspan
- 1 Gigabit High Power 802.3at compliant Midspans
  - PD – 9006G/ACDC/M: 6-port High Power 1 Gigabit 802.3at compliant Midspan
  - PD – 9012G/ACDC/M: 12-port High Power 1 Gigabit 802.3at compliant Midspan
  - PD – 9024G/ACDC/M: 24-port High Power 1 Gigabit 802.3at compliant Midspan
  - PD – 9024G/ACDC/M/F: 24-port Full High Power 1Gigabit 802.3at compliant Midspan
- 1 Gigabit High Power 802.3at compliant four-pair Midspans
  - PD – 9506G/ACDC/M: 6-port High Power 1 Gigabit 802.3at compliant four-pair Midspan
  - PD – 9512G/ACDC/M: 12-port High Power 1 Gigabit 802.3at compliant four-pair Midspan
  - PD – 9524G/ACDC/M: 24-port High Power 1 Gigabit 802.3at compliant four-pair Midspan
- 1 Gigabit High Power 802.3at compliant energy efficient Midspans
  - PD – 5524G/ACDC/M: 24-port High Power 1 Gigabit 802.3at compliant energy efficient Midspan
- 1 Gigabit High Power PoH compliant four-pair Midspans
  - PD – 9606G/ACDC/M: 6-port High Power 1 Gigabit PoH compliant four-pair Midspan
  - PD – 9612G/ACDC/M: 12-port High Power 1 Gigabit PoH compliant four-pair Midspan

### 1.2 Audience

This guide is intended for network administrators, supervisors and installation technicians who have a background in:

- Basic concepts and terminology of networking
- Network topology
- Protocols

## Power Over Ethernet Power View Pro User Guide

---

- Microsoft Windows environment



## 1.3 Organization

This guide is divided into the following sections:

- **Section 1:** Defines the concepts used, conventions used and associated documentation
- **Section 2:** Power View Pro features and capabilities
- **Section 3:** Complete system installation procedure
- **Section 4:** PowerView Pro Web interface detailed description
- **Section 5:** Midspan 90xxG/95xxG/55xxG/96xxG - Power Backup and Management
- **Section 6:** SNMP Monitoring and Configuration
- **Section 7:** Upgrading Midspan software
- **Section 8:** Troubleshooting

## 1.4 Conventions

The various conventions used in defining commands and examples are given in the following table.

CONVENTION	DEFINITION
<b>bold</b>	Keywords and commands
<i>italics</i>	<i>Represents a Web interface item</i>
<code>screen</code>	Displayed Information
<code>Courier text</code>	Information to be entered
Notes	Helpful information

## 1.5 Related Documentation

For additional information, refer to the following documentation:

- Product user guide (included inside the CD)
- Technical Note 132: Using RFC3621 PoE MIB with PowerDsine Midspans (included inside the CD).
- Creating SSL Certificate for Midspan Secured Web Server User Guide (included inside the CD)
- RFC3621 SNMP MIB, and private MIB (included inside the CD)
- IEEE Standard 802.3af, DTE Power via MDI

## 1.6 Abbreviations

**Table 1-1: List of Abbreviations**

IPv4	32 bit long IP address
IPv6	128 bit long IP address
DHCPv4	Dynamic IPv4 Host Configuration Protocol
DHCPv6	Dynamic IPv6 Host Configuration Protocol
PoE	Power over Ethernet
NTP	Network Time Protocol
DES	Data Encryption Standard
MD5	Message Digest algorithm 5
MDI	Media Dependent Interface
MIB	Management Information Base
PD	Powered Device
SNMP	Simple Network Management Protocol
SSL	Secure Sockets Layer
TFTP	Trivial File Transfer Protocol
SysLog	System Log
SSH	Secure Shell
RADIUS	Remote Authentication Dial In User Service
RPS	Redundant Power Source
EEPoE	Energy Efficient Power over Ethernet
PoH	Power Over HDBaseT

## 2 Introducing the Power View Pro (IPv4, IPv6)

PowerDsine's Power View Pro is a management system used to monitor and control PowerDsine's Power over Ethernet (PoE) and Power over HDBaseT (PoH) Midspans, via a remote network management station. Management can be done over IPv4, IPv6 or both Network protocols. The system provides direct online power supervision, configuration, monitoring and diagnostics of PowerDsine products via WEB / SNMPv2c / SNMPv3 / Telnet/SSH.

### NOTE:



The principle of operation is similar for all IPv6 capable Midspan models described in this manual.

### 2.1 Features

The manager provides a number of unique features along with multiple access options:

- **Supported network IP protocols:**
  - IPv4 – IP address is made out of 32 bits (static / DHCPv4).
  - IPv6 – IP address is made out of 128 bits (static / DHCPv6)
- **Access Options:**
  - **HTTP:** Web based friendly configuration interface for managing remote Power over Ethernet device
  - **SSL:** Secured WEB based configuration
  - **SNMP:** SNMPv2c and secured plus encrypted SNMPv3 (legacy SNMPv1 is also supported)
    - RFC3621 Power over Ethernet (PoE) SNMP MIBs
    - Private MIB extension for RFC3621 PoE MIB
  - **Telnet:** Remote terminal over Ethernet Network
  - **SSH:** Remote encrypted terminal over Ethernet Network
- **RADIUS:** Authentication and accounting for WEB / Telnet / SSH remote WEB users
- **SysLog Server:** Sends log events to remote SysLog Server
- **Automatic Service Configuration by DHCP:** Enables DHCP Server to configure automatically Midspan SNMP Manager's IP address, SysLog Servers IP address, Radius Servers IP address
- **Access List Filtering:** Controls which remote Host or Network can manage the Midspan device, and via which management interface. Interfaces such as SNMP, Telnet, Web, etc.
- Easy software update during run time without affecting active PoE ports
- Configuration and real time monitoring using graphical representations of remote device
- System status display
- Automatic activation / deactivation of PoE ports based on weekly schedule configuration
- Automatic deactivation of low priority ports when UPS battery is low
- Power backup by 2nd Midspan or external Power Source (90xxG, 95xxG series only)

## 2.2 System Capabilities

The manager can be accessed from any computer using any WEB browser, SNMPv2c/SNMPv3 management station, Telnet/SSH, RS232 Terminal or USB virtual COM (Midspan 90xxG, 95xxG, 55xxG series). The Power View Pro enables monitoring and controlling of Power over Ethernet IP networks as shown in Figure 2-1.




Figure 2-1: Management Deployment

## 2.3 POE Capabilities

The Midspan injects power over data-carrying Ethernet cabling which reduces the need for AC outlets, local UPS and AC/DC adapters near PDs. The following Power over Ethernet (PoE) options are available:

- **Legacy PoE** – delivers power to pre IEEE 802.3af PoE devices
- **IEEE 802.3af** – delivers up to 15.4 Watts using two out of four pairs on RJ45 Ethernet connector. Applicable mostly to 65xx/65xxG Midspan family although all Midspans support IEEE-802.3af.
- **IEEE 802.3at** – delivers up to 30/36 Watts (PowerDsine Midspan may be configured to deliver up to 36 Watts). Applicable to 55xxG/90xxG/95xxG Midspan family.
- **4-pairs IEEE 802.3at** – PowerDsine Midspan solution to deliver up to 72 Watts by delivering up to 36 Watts on each pair of wires on the RJ45 Ethernet connector. Applicable to 95xxG Midspan family.
- **EEPoE** – Energy Efficient Power over Ethernet deliver up to 30/36 Watts by powering IEEE-802.3at PD devices over four pairs. By powering PD devices over four pairs, the power loss on the Ethernet cable is reduced by 50%. For example a PD device which consumes 30 Watts may cause power loss of up to 5W on the Ethernet cable, forcing the Midspan to deliver 35 Watts. By using 55xxG EEPoE Midspan the power loss on the Ethernet cable will be reduced by 50% to 2.5 Watts, forcing the Midspan to deliver only 32.5 Watts.
- **PoH** – Power Over HDBaseT delivers up to 95 Watts over four pairs. Applicable to 96xxG Midspan family.

## 2.4 Configuration Options

Serial communication configuration should be used to set unit's initial IPv4 or IPv6 address (also set by web browser), upload / download unit configuration, restore unit configuration to factory default (also set by web browser), or update software. Any other configuration should be carried out via the WEB browser.

- **Web based:** Via a WEB browser
- **SNMPv1/2c/3:** Via an SNMP management application on a remote computer

## Power Over Ethernet Power View Pro User Guide

- **Telnet:** Via a Telnet application on a remote computer
- **SSH:** Via an SSH client application on a remote computer
- **Serial communication port:** Via a DB9 port using Terminal emulation software such as Microsoft Windows Hyper Terminal, PuTTY, or any similar software (excluding Midspan 90xxG, 95xxG, 55xxG series).
- **Serial communication port via USB Virtual Communication Port driver** (Midspan 90xxG, 95xxG, 55xxG series only): Simplifies serial communication whenever laptop is in use (laptops are missing physical serial communication ports).

### NOTE:



Serial communication rate must be set to 38400, no hardware flow control. When using RS232 serial port cable, a cross cable must be used (pin 2 crossed with pin 3).

### NOTE:



The Midspan default IPv4 address is 192.168.0.50. Make sure that a computer network card is configured to the same IPv4 network (for example 192.168.0.40).

### NOTE:



For security reasons, when unit is shipped the SNMP is disabled. Prior to enabling SNMP, modify SNMP community strings and only then enable it.

The Telnet/SSH and WEB configuration options are password protected.

## 2.5 Security and User Authentication

Different security profiles are available, depending on the used type of configuration.

### 2.5.1 Web Security

Web interface has two user access levels, Viewer and Administrator.

- **Viewer:** The user has access only to Web pages which report Midspan status of configuration summary and cannot change the Midspan configuration.
- **Administrator:** The user has full access to all Web pages and can modify Midspan configuration.

### NOTE:



SSL (https) offers encryption and authentication protection in addition to Viewer & Administrator access levels.

### 2.5.2 SNMP Security

- **SNMP v1/v2:** Community string is utilized for Get/Set/Trap authentication. SNMPv1/v2 is considered an unsecured protocol since the community string password can be easily intercepted by any Network sniffer device.
- **SNMP v3:** Resolves SNMPv1/v2 security issues by adding authenticating and encryption to SNMP packets.

### 2.5.3 Telnet/SSH Security

Since Telnet/SSH provides access to various configuration parameters, software update and data base upload/download, it is always password protected.

#### NOTE:



The Web interface has a dedicated password, while Telnet and SSH share the same passwords

#### NOTE:



The Power View Pro is provided with the following factory defaults passwords:

#### WEB/Telnet/SSH:

*View (usually user) :*

*user name ="user"*

*password ="password"*

*Configure (usually administrator):*

*user name ="admin"*

*password ="password".*

#### SNMP v3:

*Guest (usually remote SNMP manager) :*

*user name ="public"*

*View User (usually user) :*

*user name ="view"*

*authentication password (MD5) = "password"*

*privacy password (DES)= "password"*

*Admin User (usually administrator) :*

*user name ="admin"*

*authentication password (MD5) = "password"*

*privacy password (DES)= "password",*

### 3 Installation

The following sections detail the installation process.

#### 3.1 System Requirements

The following hardware/software items are required to configure and operate the Power over Ethernet (PoE) Midspan:

- Computer with Ethernet Network card configured to the following parameters:
  - IPv4: 192.168.0.40
  - IPv4 Mask: 255.255.255.0
- Ethernet cable.
- Ethernet switch connected to the computer and Midspan management RJ-45 port (user can use cross cable connected directly between the computer and the Midspan without needing to use an Ethernet Switch).
- Telnet application (already provided by Windows/Linux).
- A free serial communication port on the computer.
  - Null-modem RS232 crossed cable
  - USB cable (90xxG, 95xxG, 96xxG, 55xxG Midspan series). For virtual com driver installation, refer to section 3.4.6.


**Important:** The Midspan is shipped with the default IP set to 192.168.0.50. Before connecting the Midspan to your network, verify that no other device has the same IP address.

#### 3.2 Hardware Setup

Before configuring the units, set up your hardware as follows:

1. Connect an AC power cable to the PoE unit.
2. Verify that all LEDs are lit (self test).
3. Configure the units (refer to Figure 3-1):
  - **Serial port:** Connect the crossed null-modem cable between the management station serial port and the Midspan RS 232 port.
  - **Midspan 90xxG, 95xxG, 96xxG, 55xxG:** Use USB cable (verify virtual com port driver installation was already done).
  - **Ethernet network:** Connect a network cable to Midspan RJ45 management port (use cross cable whenever connecting it directly to Laptop Ethernet port).

Make sure the green LED on the right side of Midspan RJ45 Management port turns on. In case a problem arises, refer to Troubleshooting, Section 8.



**Figure 3-1: Connecting the PoE Unit**

## 3.3 Configuration Procedure

The following sections describe how to install the unit via the configuration options.

The following connection options are available:

- Connecting to Unit Using a Web Browser
- Connecting to Unit Using Window's Telnet
- Connecting to Unit Using serial port and a Hyper Terminal Application (65xx, 65xxG Midspan series)
- Connecting via USB Serial Communication Virtual Port, page 18 (90xxG, 95xxG, 96xxG, 55xxG Midspan series)

### 3.3.1 Connecting to Unit Using a Web Browser

1. Open the web browser.
2. In the address field type:

*192.168.0.50*

### 3.3.2 Connecting to Unit Using Window's Telnet

For Windows XP / Windows Vista / Windows 7:

- In the Start Menu, select Run.
- Type: *cmd*. (Black DOS window will appear).
- Type: *telnet 192.168.0.50*.
- Type the username and password.



**NOTE:**

Use the web browser to view the System Configuration->Security web page and make sure that the Telnet is enabled.

### 3.3.3 Connecting to Unit Using serial port and a Hyper Terminal Application

Windows XP includes Hyper Terminal communication application which can be used to configure the Midspan over the serial port. For Windows Vista and Windows 7 we recommend using PuTTY application which can be downloaded for free from the Internet.

#### 3.3.3.1 Windows 2000 and Windows XP

1. In the Start Menu, select:

*Start >Programs >Accessories >Communications > HyperTerminal.*




## Power Over Ethernet Power View Pro User Guide

The Hyper Terminal window appears (Figure 3-2).

2. Select the following parameters:

- **Bits per second:** 38400
- **Data bits:** 8
- **Parity:** None
- **Stop bits:** 1
- **Flow control:** None



**Figure 3-2: Windows XP Hyper Terminal Specifications**


### 3.3.3.2 Windows Vista / Windows 7

Windows XP HyperTerminal serial communication is not included in Windows Vista / Windows 7. It is recommended to use PuTTY, HyperTerminal freeware serial communication software or any other commercial serial communication software tool.

1. Download PuTTY freeware at: <http://www.putty.org/>.
2. Run **PuTTY**.

The Putty Configuration window appears (Figure 3-3).


## Power Over Ethernet Power View Pro User Guide



**Figure 3-3: PuTTY Configuration Window**

3. Under Connection type, select **Serial**.

The PuTTY Serial Configuration Window appears (Figure 3-4).



**Figure 3-4: PuTTY Serial Configuration Window Specifications**

4. Select:
  - **Serial line to connect to:** Required COM port
  - **Speed (baud):** 38400
  - **Flow control:** None
5. Click **Open**.

### 3.3.4 Connecting via USB Serial Communication Virtual Port

The 90xxG/95xxG/96xxG/55xxG Midspan offers USB serial communication rather than the traditional RS232 DB-9 interface. This eases the serial communication whenever a laptop is used (laptops lack serial interface ports).

**To install the 90xxG/95xxG/96xxG/55xxG driver:**

## Power Over Ethernet Power View Pro User Guide

1. Verify that the host's USB port is disconnected from the 90xxG/95xx/96xxG/55xxG Midspan's USB port.
2. Install the Virtual Serial Communication driver from the included CD
3. Connect the host USB to the 90xxG, 95xxG, 96xxG, 55xxG Midspan USB port.
4. In the host, configure the connection setting.
  - Windows 2000 and Windows XP OS: Run the HyperTerminal application.
  - Windows Vista / Windows 7 OS: Run PuTTY.
  - Select the following settings:
    - **Baud rate:** 38400
    - **Number of bits:** 8
    - **Stop bit:** 1
    - **Flow-control:** None

### 3.3.5 Configuring the System via the serial port



#### NOTE:

There is no password protection while using the serial communication port. Password protection is only applicable for Telnet, SSH or WEB access.

To configure the system via the HyperTerminal:

- Click the ESC or space key (in case you are already in the main menu). The Main Menu appears:

```

Main Menu - [Midspan Device]
-----
1. View menu
2. Configuration & maintenance menu
3. Ping remote host

E. Exit to debug information screen
  
```


Figure 3-5: Main Menu Screen

The Main Menu contains the following functions:

- **View Menu:** View PoE ports status, Network configuration, ACL Filter, software version and release date.
- **Configuration & maintenance menu:** Enable/disable PoE ports, Network configuration, upload/download configuration, update SSL certificate, software update, restore username & password or unit configuration to factory default and reset unit.
- **Ping remote host:** Determine whether a particular IP system on a network is functional. Use this function to diagnose IPv4 and IPv6 network connectivity.
- **Exit to debug information screen:** Enables on-going debug information to be reported by the terminal.

#### 3.3.5.1 Using the View Menu

- In the Main Menu, select the View Menu option.  
The View Menu screen appears.



**Figure 3-6: View Menu Screen**

The View Menu contains the following functions:

- **View PoE ports status:** Shows whether a PoE port is enabled/disabled, if the port provides power to a PD device, and PD power consumption.
- **View network parameters:** Displays the Midspan IPv4 address, subnet mask, default gateway. For IPv6, same data is displayed plus DNS, SysLog servers, NTP server and unit MAC address.




**NOTE:**

While DHCP is in use, DHCP server IP appears as well.

- **View ACL (Access List) filter parameters:** Shows Access List Filter configuration mode and statistics detailing how many network packets were accepted or rejected by HTTP, HTTPS, SNMP, Telnet, and SSH filters.
- **View time & system up time:** Displays how many days, hours, minutes and seconds the unit has been operational.
- **View application & Boot software version:** Displays the application and boot version number and creation date.

## 3.3.5.2 Using the Configuration & Maintenance Menu

- In the Main Menu, select the Configuration & Maintenance Menu.



**Figure 3-7: Configuration & Maintenance Menu**

The Configuration & Maintenance Menu contains the following options:

- **Enable/Disable PoE Port:** Allows users to enable/disable a PoE port (same as from WEB/SNMP/Telnet/SSH).

## Power Over Ethernet Power View Pro User Guide

- **Network configuration:**
- Set IPv4 address (static / DHCPv4), and DNSv4
- Set IPv6 address (static / DHCPv6), and DNSv6
- Set Host name (used by DHCP4 / DHCPv6)
- **Download configuration File from TFTP Server:** Download a configuration file from a remote host using a TFTP application (host must run TFTP server application prior to using this option; see Section 3.4).



### NOTE:

Upon successful downloading, only the manager module will reset itself without effecting active powered PD devices.

- **Upload Configuration File to TFTP Server:** The unit uploads its internal configuration file to the host, utilizing a TFTP application (host must run TFTP server application prior to using this option - see Section 3.4).
- **Download WEB SSL Certificate from the TFTP Server:** Download a valid private key and certificate files for Web SSL by TFTP. The private key eliminates web browser security warnings whenever SSL is used.



### NOTE:

For detailed procedure description and applicable utility files, refer to Web SSL documentation on the CD.

- **Software update menu:** Enables the user to update management module software or PoE firmware.



### NOTE:

It is recommended that you use the TFTP server application on the CD.

- **Turn RADIUS, ACL Filter off. Restore all user & password to factory default:** Turns RADIUS and Access List Filter (ACL Filter) off, and restores Manager Module view/configure user name and password to default values (only the manager module resets itself without effecting active powered PD devices).
- **Restore the unit to factory default. Keep IP configuration unchanged:** Restores most of the unit configuration parameters to factory default values. Note that to enable the remote user to access the Midspan after it was restored to factory default; various IP parameters (for example unit IP address) remain the same (only the manager module will reset itself without effecting active powered PD devices).
- **Reset Manager Module:** Manager Module resets only itself, without effecting active powered PD devices.
- **Reset unit:** Reset the entire unit, which causes all powered PD devices to be turned off for several seconds, and then re-powered.
- **Enable/Disable auto ping to Default Gateway to ensure Network connectivity:** When enabled, it allows the Midspan Network Management Module to verify proper Network connectivity by pinging default gateway every six seconds (IPv4 DGW or IPv6 DGW). After 10 consecutive ping failures, Network Management Module will reset itself without effecting PoE ports.



### NOTE:

Manager Module will not reset itself in case there are no DGWs

- **ESC:** Return to Previous Menu

### 3.3.5.3 Using the Ping Remote Host Menu

The Ping Remote Host Menu can be used to test Midspan Network configuration, and also verify access to remote services such as SysLog server, SNMP Network management station, etc.

To ping a remote device:

## Power Over Ethernet Power View Pro User Guide

1. In the Main Menu, select Ping Remote Host Menu.
2. Type the remote IPv4, IPv6 or remote Host name (for using hostname, DNS must be configured).

### 3.4 Configuring the TFTP Server

The following section describes how to configure the IPv4 TFTP server which is utilized for optional software updates and transferring unit configuration to and from the host.




#### NOTE:

1. Make sure Firewall is turned off on the computer which runs the TFTP Server (or enable UDP port 69 to pass through the Firewall).
2. For Upload Configuration: Make sure Enable Writes checkbox is checked (see Figure 3-8).

To configure the TFTP server:

1. From the provided CD, copy the **NBTFTP.exe** application to your server's desktop.
2. Run NBTFTP.exe application; the following window appears (Figure 3-8)



**Figure 3-8: NBTFTP Server Window**

3. Click ADD, to add the root folder of the TFTP server.

## 4 Web Interface Description

The Web Interface provides a friendly graphical interface for monitoring and configuring the Midspan unit..

### 4.1 Overview

The system provides the following features:

- View of PoE ports status, Power consumption and Midspan configuration.
- Modification of Midspan configurations which are applicable for the entire Midspan unit.
- Modification of PoE ports configurations, such as maximum power, priority, port description, etc.

The Web Interface has two authorization levels (see System Configuration Security, page 60):

- **User:** Allows remote users to access only web pages which are located under the View menu.
- **Administrator:** Allows remote users full access to all web pages.

### 4.2 Opening Screen

Browse to the Midspan IPv4 or IPv6 address. The Main Window (Opening screen) appears (Figure 4-1). The Opening screen is composed of three main submenus:

- **View menu:** Used to view unit status, network configuration and product information.
- **System Configuration menu:** Used for configuring anything that isn't PoE port specific (network, SNMP, security, RADIUS, UPS power management, access list filter, product parameters and maintenance).
- **Port Configuration menu:** Used for enabling/disabling of ports, allocation of power, setting of priorities, and weekly based schedule automatic PoE ports activation/deactivation.




Figure 4-1: Power View Pro Main Window

## Power Over Ethernet Power View Pro User Guide

### 4.3 View Menu

The View menu is used to view the following categories (see Figure 4-2):

- System status
- Configuration summary
- Product information

The View menu differs according to the model being used:

- View - Status Screen 65xx, 65xxG Midspan Series
- View - Status Screen 90xxG, 95xxG, 96xxG four-pair High Power Midspan Series.
- View - Status Screen 55xxG energy efficient High Power Midspan Series.






Figure 4-2: View Menu

#### 4.3.1 View - Status Screen 65xx, 65xxG Midspan Series

The View - Status screen is used for monitoring which PoE ports are active and power consumption (for the entire unit or per port). It is made up of several elements (see Figure 4-3):

- Port status panel – view which PoE ports are enabled, which are provide with power, and amount of power.
- Port power status table – pressing the  or  images will open a detailed port report table.
- General power status table – reports internal power supply voltage, total power consumption, etc.
- UPS power management information – reports remote UPS battery level, and AC or Battery power source.



#### NOTE:

UPS Power Management window for 65xx, 65xxG, 90xxG appears at the bottom right section of the screen only if the UPS Power Management option is enabled (for more details, refer to Section 4.3.12).






Figure 4-3: View - Status Screen (65xx, 65xxG Midspan Series)

## 4.3.2 View - Status Screen 90xxG, 95xxG, 96xxG four-pair High Power Midspan Series

In addition to the information provided by the View - Status Screen (65xx, 65xxG Midspan Series), the 90xxG, 95xxG High Power Midspan series View - Status Screen (see Figure 4-4) provides the following addition information:

- **PoE PD detection method:** Includes IEEE802.3at PoE PD in addition to the 802.3af and legacy PoE PD devices (not supported by 96xxG Midspan).
- **Power sources:** Internal and external power sources status (redundancy power backup capability was added to 90xxG, 95xxG, 96xxG Midspan series).
- **External redundancy power source status:** The 90xxG, 95xxG, 96xxG Midspan support redundant power supplies.
- **PD power consumption (90xxG):** PoE PD Power consumption reports up to 30 watts for IEEE802.3at devices or up to 36W if Extended Power Mode is enabled.
- **PD power consumption (95xxG):** PoE PD Power consumption reports up to 60 watts or up to 72 watts if the Extended Power Mode is enabled.
- **Temperature (95xxG/96xxG/55xxG):** Internal temperature sensor is included in 95xxG Midspan series which reports the Midspan internal temperature. The 95xxG/96xxG/55xxG Midspan temperature can be obtained from View System Status WEB page, or from Midspan SNMP Private MIB (Version 1.7 and above).

## Power Over Ethernet Power View Pro User Guide




Figure 4-4: View - Status Screen (90xxG High Power Midspan Series)

## Power Over Ethernet Power View Pro User Guide




Figure 4-5: View - Status Screen (95xxG four-pair High Power Midspan Series)

## Power Over Ethernet Power View Pro User Guide

**Microsemi** Home View System Configuration Port Configuration

### View - Status

Midspan Nickname: Midspan PoE Device

Diagram showing 12 ports (1-12) with Data & Power Out and Data In indicators. PowerDsine 9612G Console Main.

#	1	2	3	4	5	6	7	8	9	10	11	12
Power (W)	0	0	0	0	0	0	0	0	0	0	0	0
Description												

**Midspan Status**

Total Power Consumption (Watt)	0
Maximum available Power (Watt)	950
System Voltage (Volt)	55.4
Temperature (F)	75.7
Midspan Status	Active

**Power Source Status**

Internal (950W) Power Source	Ok
No External Power Source	---

Figure 4-6: View - Status Screen (96xxG PoH four-pair High Power Midspan Series)

## Power Over Ethernet Power View Pro User Guide

### 4.3.3 View - Status Screen 55xxG energy efficient High Power Midspan Series

In addition to the information provided by the View - Status Screen 90xxG, 95xxG, 96xxG four-pair High Power Midspan Series, the 55xxG High Power Midspan series View - Status Screen (see Figure 4-7) provides the following addition information:

- Energy saving information – reports annual Energy saving, annual Co2 Saving and number of EEPoE active ports out of the number of EEPoE enabled ports.
- **PD power consumption:** PoE PD Power consumption reports up to 30 watts for IEEE802.3af devices or up to 36W if Extended Power Mode is enabled.




Figure 4-7: View - Status Screen (55xxG energy efficient High Power Midspan Series)

**NOTE:**

The external power source type **MUST** match the Midspan type.

**PD-RPS-450 backups:**

- \* PD-9006/ACDC/M
- \* PD-9012G/ACDC/M
- \* PD-9024G/ACDC/M
- \* PD-9506G/ACDC/M
- \* PD-5524G/ACDC/M

**PD-RPS-1000 backup:**

- \* PD-9024G/ACDC/M/F
- \* PD-9512G/ACDC/M
- \* PD-9524G/ACDC/M
- \* PD-9606G/ACDC/M
- \* PD-9612G/ACDC/M

## Power Over Ethernet Power View Pro User Guide

### 4.3.4 View - Status Screen Elements

The following sections describe in detail the View - Status Screen elements.

#### 4.3.4.1 Ports Status Panel

The display panel includes a number of visual indicators (see Figure 4-8).

- A green colored RJ45 port indicates that the PoE port is enabled, and may provide power whenever a PD device is connected to this port.
- A green LED on top of the green colored RJ45 port indicates that the PoE port provides power to a PD.
- A red colored RJ45 port with an "X" symbol indicates a disabled PoE port (a port that can't provide power).




Figure 4-8: Ports Status Panel

#### 4.3.4.2 Midspan LED Indications

Two LEDs are located on the front panel, marked "Main" (220/110VAC) and "Link" (Ethernet connection plus activity status) as described in Table 4-1.

Table 4-1: Main Status Indications

Indicator	Color	Main Power Status	Remarks
AC LED	Off	Internal power supply unit is unplugged or faulty	Internal power supply voltage is too low. All ports are disconnected
	Green	Indicates AC power input active	Internal power supply voltage is within limits
	Green blinking	Internal power supply voltage is out of range 90xxG, 95xxG, 96xxG – Internal power supply is unplugged	All ports are disconnected 90xxG, 95xxG – unit powered by external power source
LINK LED	Green blinking	Indicates valid Ethernet link, and some data communication flow over the Ethernet network	
LINK LED	Green	Indicates valid Ethernet link (no communication data)	

**Table 4-2: 65xx, 65xxG, 90xxG, 95xxG and 55xxG Gigabit High Power Midspan Port Status Indications**

Port LED Color	Port Load Conditions	Port Voltage
Off	Non-active load, unplugged port or disabled port	Power to the port is disconnected. No DC voltage present on spare pairs
Green	<p>Active load is plugged in and complies with normal load conditions</p> <p><b>95xxG:</b> PoE port is configured as two-pair, and power PD device, or as four-pair and power PD device on all four pairs.</p> <p><b>55xxG:</b> PoE port is configured as EEPoE and power PD device, or as four-pair and power PD device, on all four pairs</p>	Continuous nominal DC voltage is present on the spare pairs
Orange	<p><b>95xxG/96xxG:</b> PoE port is configured as four-pair, and power PoE device on two pairs only.</p> <p><b>55xxG:</b> PoE port is configured as EEPoE, and power PoE device on two pairs only.</p>	
Green blinking	Overload conditions; or short; or forced external voltage feed (constant DC) into the port	Power to the port is disconnected. No DC voltage is present on the spare pairs
Slow Green blinking	Port can't be activated since total aggregated power exceeds maximum power budget	Power to the port is disconnected. No DC voltage is present on the spare pairs



## Power Over Ethernet Power View Pro User Guide

### 4.3.4.3 Midspan Status Table


The Midspan Status Table displays the following parameters:


Total Power Consumption (Watt)	14.1
Maximum available Power (Watt)	1000
System Voltage (Volt)	55.2
PD Detection Method	IEEE802.3af + IEEE802.3at + Legacy
Midspan Status	Active

**Table 4-3: Midspan Status Table Details**

Parameter	Description
Total Power Consumption	Total power consumed by all PDs
Maximum available Power	Maximum available power for all PDs
System Voltage	Voltage level supplied to PDs
PD Detection Method	Detection method selected by the user from the System Configuration - Product Parameters menu (see Sections 4.3.14, 4.3.15, and 4.3.16)
Midspan Status	Midspan status display with the following options: <ul style="list-style-type: none"> <li>Active: Normal operation</li> <li>Midspan has no firmware</li> <li>Internal communication failure</li> <li>Midspan firmware update</li> </ul>

### 4.3.4.4 Detailed Port Information Report

Clicking the  image, or the RJ45 jack image, causes a new popup web page to appear with detailed port description information (see Figure 4-9):



**Figure 4-9: Detailed Port Information**

**Table 4-4: Detailed Port Description Information**

Parameter	Description
Port	<ul style="list-style-type: none"> <li><b>Disabled:</b> Port is disabled</li> <li><b>Enabled:</b> Port is enabled</li> <li><b>Enabled:</b> Delivering Power; Port is enabled and a valid PoE PD device is connected and consuming power</li> <li><b>Enabled:</b> Failure to power a PoE Device; Port is enabled, PoE PD device is connected, but no power is provided. Possible causes include: PoE device consumes too much power (overload) or the PoE PD device is invalid, etc.</li> </ul>
Power (W)	Actual consumed power by individual PD
Max Power(W)	Maximal allocated power per port as configured in the Port Configuration Midspan 95xxG reports also if PoE port is configured as two pair or four pair. Midspan 55xxG reports also if PoE port is configured as energy efficient PoE.
Priority	Current priority level set by the user
Terminal Type / Description	Textual terminal description as configured in the Port Configuration
Class	PD device class

## 4.3.4.5 Manual Override Key



Whenever the Weekly Schedule feature is activated, the IT manager can configure one of the Midspan PoE ports to act as a Manual Override Deactivation key. This enables easy temporary deactivation of the Weekly Schedule feature, whenever an authorized user arrives at work during unexpected hours. The IT manager selects the override port manually via the Web interface and then enables the override feature; an icon then appears on the selected port.



### NOTE:

The Deactivation key is an optional item which may be purchased separately from Microsemi.

Upon unexpected user arrival to work, the user inserts the deactivation key into the previously assigned override port (Figure 4-10) (usually routed through the patch panel near the doorway entrance).




**Figure 4-10: Manual Override Deactivation key**

As long as the override key is inserted, all Weekly Schedule deactivated PoE ports remain active. Upon leaving work, the user removes the override key, which in-turn will causes all Weekly Schedule assigned ports to turn Off (Weekly Schedule time configuration dependent).




### NOTE:

In cases where the  icon appears but the corresponding port LED does not illuminate, it means that the port had been assigned as a 'bypass' port, but the override key has not been inserted.

## Power Over Ethernet Power View Pro User Guide

### 4.3.4.6 Weekly Scheduled Activated Port/s

The weekly schedule feature enables (when checked) scheduling of automatic PoE ports activation/deactivation as set in the weekly schedule activation scheme.

When the  icon appears on a port, it means that a specific port was temporary deactivated by the Weekly Schedule algorithm.



#### NOTE:

Note that PoE port activation/deactivation hours depend on user Weekly Schedule configuration (see Section 4.4.3.1).





Figure 4-11: Weekly Activated/Deactivated Ports

### 4.3.5 View - Configuration Summary

The View - Configuration Summary screen (see Figure 4-12) displays the following parameters:

- **IPv4 in-use:** Currently in use IPv4 address/Mask/Gateway (may be acquired by DHCP or static configuration) and IPv4 Domain name servers.
- **IPv6 in-use:** Currently in use IPv6 address/Prefix/Gateway (may be acquired by DHCPv6 or static configuration), and IPv6 Domain name servers.
- **Network Host Name:** Midspan hostname used by IPv4 / IPv6 to register Midspan hostname in DHCPv4/DHCPv6 Server.  
NOTE: Only A-Z, a-z, 0-9, minus, and dots are allowed. Hostname must start with a letter.
- **Ethernet MAC Address:** Six byte (48 bit) unique Ethernet address.
- **Remote Servers:** IP address of remote NTP (Network Time Protocol) Server, remote SysLog Servers, and remote Radius Servers.
- **Remote Trap SNMP Managers List:** List of assigned SNMP managers to receive Midspan SNMP Trap reports.
- **Date & Time:** Unit local time, as acquired from the NTP Server (GMT time zone should be configured by the user)
- **Remote Access & Security:** A list of Midspan remote access and security options; SNMP v1/v2 and SNMPv3, Telnet/SSH, RADIUS, and SSL Web encryption
- **Advanced Features:** Indication of Automatic Weekly Schedule PoE ports activation and UPS Power Management features activation.



[Home](#)
[View](#)
[System Configuration](#)
[Port Configuration](#)

## View - Configuration Summary

### IPv4 in-use

DHCPv4	No
IPv4 Address	172.16.5.247
IPv4 Mask	255.255.248.000
IPv4 Default Gateway	172.16.0.2
Domain Name Server #1	172.16.1.46
Domain Name Server #2	172.16.1.47

### Network Host Name

Host Name	abc
-----------	-----

### Ethernet MAC Address

MAC Address	00:05:5A:02:88:AD
-------------	-------------------

### IPv6 in-use

DHCPv6 - No	
IPv6 Address	fe80::205:5aff:fe02:88ad%1/128
IPv6 Default Gateway	
IPv6 Domain Name Servers	

### Remote Access & Security

Telnet/SSH	Telnet
SNMP v2	<input checked="" type="checkbox"/>
SNMP v3	<input checked="" type="checkbox"/>
Web SSL Encryption	<input type="checkbox"/>
RADIUS Authentication	<input type="checkbox"/>
RADIUS Accounting	<input type="checkbox"/>

### Remote Servers

NTP Server	HODDTC8400.microsemi.net
SysLog #1	HODDTC8400.microsemi.net
SysLog #2	
Radius #1	000.000.000.000
Radius #2	000.000.000.000

### Advanced Features

Weekly Schedule	<input type="checkbox"/>
UPS Power Management	<input checked="" type="checkbox"/>

### Remote Trap SNMP Managers List

Manager #1	HODDTC8400.microsemi.net
Manager #2	
Manager #3	
Manager #4	
Manager #5	
Manager #6	
Manager #7	
Manager #8	
Manager #9	
Manager #10	

### Date and Time

Local Time (OK)	12:32:56
Date (DD/MM/YYYY)	09/06/2011

Figure 4-12: View - Configuration Summary Screen

## 4.3.5.1 IPv4 in-Use

IPv4 in-use window displays the current IP address being used with the following parameters (Figure 4-13):

IPv4 in-use	
DHCPv4	No
IPv4 Address	172.16.5.247
IPv4 Mask	255.255.248.000
IPv4 Default Gateway	172.16.0.2
Domain Name Server #1	172.16.1.46
Domain Name Server #2	172.16.1.47

Figure 4-13: IP in-Use Window

Table 4-5: IP in User Parameters

Parameter	Description
DHCPv4	Indicates if DHCPv4 or static IPv4 is in use
IPv4 Address	IPv4 address of the Midspan in use.
IPv4 Mask	Determines the size of the IPv4 Network
IPv4 Default Gateway	IPv4 address of the local Gateway which enables communication with other IPv4 networks
Domain Name Server 1&2	IPv4 address of DNS used for resolving remote host names.

## 4.3.5.2 Remote Servers

The Remote Servers window (see Figure 4-14) displays IPv4, IPv6 or remote hostname address of a remote SysLog Servers, Radius Servers and NTP Server.

Remote Servers	
NTP Server	HODDTC8400.microsemi.net
SysLog #1	HODDTC8400.microsemi.net
SysLog #2	
Radius #1	172.016.005.254
Radius #2	172.016.005.253

Figure 4-14: Remote Servers Window

Parameter	Description
NTP Server	IPv4/IPv6 address of a remote Network Time Protocol (NTP) Server.
SysLog Server#1 SysLog Server#2	Send SysLog events to Main and Backup IPv4/IPv6 SysLog Server via SysLog protocol. Note that empty fields prohibit the unit from sending Log Events.
Radius Server #1 Radius Server #2	Used for authenticating remote user by sending remote user username and password to Radius Server for

## Power Over Ethernet Power View Pro User Guide

	authentication and obtaining remote user access level (viewer or administrator).
--	--

### 4.3.5.3 Date and Time

The Date and Time (GMT time zone) window (see Figure 4-15) displays the unit's local time as acquired from the NTP Time Protocol Server by the user. Set the offset local time zone as well.




Figure 4-15: Date and Time Window

Parameter	Description
Local Time	Time (HH:MM:SS) as acquired from the NTP Server, plus time zone offset
Date (D/M/Y)	Date (DD/MM/YYYY) as acquired from the NTP Server



#### NOTES:

1. When the appropriate time and date are acquired from the NTP server, an OK indication appears. Alongside the Time Zone Offset from GMT window in the System Configuration - Weekly Schedule Ports Activation menu (refer to Section 4.4.3.1) If the system fails to acquire the appropriate time and date 'FAIL' indication appears instead!
2. If the unit fails to acquire time from NTP Server, it displays the elapsed time starting from 1/1/2005
3. If time and date are not acquired, Weekly Schedule functionality will not function!
4. If local time zone offset has been improperly set by the user (Weekly Schedule configuration Web page), an incorrect time will be shown!

### 4.3.5.4 Remote Trap SNMP Managers List

This list displays all of the user pre-configured SNMP managers (see Figure 4-16). All listed managers will receive traps reported by the Midspan (to receive PoE traps, make sure that PoE RFC3621 Notification feature is enabled). Verify RFC3621 and Midspan private MIB are installed on the SNMP management station used to monitor the Midspan device.

IPv4/IPv6 Remote Trap SNMP Managers List (v2c/v3)

Trap Manager #1	snmp.trap.manager
Trap Manager #2	172.16.5.254
Trap Manager #3	
Trap Manager #4	
Trap Manager #5	
Trap Manager #6	
Trap Manager #7	
Trap Manager #8	
Trap Manager #9	
Trap Manager #10	

**Figure 4-16: Remote Trap SNMP Managers List**

## 4.3.5.5 Remote Access & Security

Remote Access & Security list (see Figure 4-17) summarizes whether Midspan can be managed by SNMPv2, SNMPv3 Telnet or SSH, HTTP or HTTPS, and whether RADIUS authentication and accounting is enabled.

Remote Access & Security

Telnet/SSH	Telnet
SNMP v2	<input checked="" type="checkbox"/>
SNMP v3	<input checked="" type="checkbox"/>
Web SSL Encryption	<input type="checkbox"/>
RADIUS Authentication	<input type="checkbox"/>
RADIUS Accounting	<input type="checkbox"/>

**Figure 4-17: Remote Access & Security Window**

Parameter	Description
Telnet/SSH	Indicates whether Midspan can be managed by Telnet, SSHv2 (secure and encrypted terminal) or by none of them.
SNMPv2	Indicates whether Midspan can be managed by SNMPv1/v2.
SNMPv3	Indicates whether Midspan can be managed by SNMPv3. It is not recommended to enable SNMPv2 while SNMPv3 is in use.
Web SSL	Indicates whether Midspan WEB pages will be encrypted by SSL.
RADIUS Authentication	When checked, indicates that remote Telnet/SSH/WEB users are authenticated by the RADIUS Server rather than by the Midspan itself.
RADIUS Accounting	When checked, indicates that the Midspan sends an accounting report to the RADIUS Server whenever remote users access Midspan by Telnet/SSH/WEB..




## Power Over Ethernet Power View Pro User Guide

### 4.3.5.6 Advanced Features

The Advanced Features window (see Figure 4-18) displays which of the Weekly Schedule / UPS Power Management advanced features is activated.

The weekly schedule feature enables scheduling of automatic PoE ports activation/deactivation as set in the weekly schedule activation scheme.

The UPS Power Management feature enables to extend the period of time the Midspan may provide power to high priority PoE devices during a power failure. This is accomplished by monitoring the UPS battery level, and automatically shutting down low priority PoE ports, whenever the UPS battery level drops to a low level.



**Figure 4-18: Advanced Features Window**

Parameter	Description
Weekly Schedule	Indicates that the weekly schedule feature had been activated via the System Configuration - Weekly Schedule Ports Activation menu.
UPS Power Management	Indicates that the Midspan was configured to communicate with UPS SNMP agent to monitor its UPS battery level and automatically deactivate low priority PoE ports whenever UPS battery becomes low.



## 4.3.6 View - Product Information

The View - Product Information web page summarises production related parameters such as product type, serial number, PoE firmware software version, and Network management module software version (see Figure 4-19):



**Figure 4-19: View - Product Information Screen**

Parameter	Description
Product Nickname	Unit nickname as configured by network administrator to be displayed in the View-Status web page and in serial/Telnet/SSH menus
Part Number	Midspan part number
Serial Number	Midspan serial number
Production Number	Unique manufacturing product number per each Midspan type (all Midspans of the same type have the same production number)
Software Version	Power View Pro Network Manager Module software version
Firmware Version	PoE Firmware version
Boot Version	Network Manager Module boot version
Flash Size	Network Management Module flash memory size.

## Power Over Ethernet Power View Pro User Guide

### 4.3.7 System Configuration Screen

The System Configuration menu is used for configuring the following options (Figure 4-20):

- Network Configuration
- SNMP Configuration
- SNMPv3 Configuration
- Security Configuration
- RADIUS Configuration
- UPS Power Management Configuration
- Access List Filter Configuration
- Product Parameters - Configuration
- System Configuration - Maintenance



Figure 4-20: System Configuration Screen

#### 4.3.7.1 System Configuration - Network

The System Configuration - Network menu (see Figure 4-21) enables configuration of

- static/dynamic IPv4 address
- static/dynamic IPv6 address
- NTP server (IPv4/IPv6)
- SysLog log (IPv4/IPv6) servers
- automatic SNMP Trap list

## Power Over Ethernet Power View Pro User Guide


- SysLog and Radius IP to be obtained by DHCP Server which simplifies management whenever many Midspan devices need to be managed.

For a detailed description see section 4.3.7.2.



### NOTE:

When enabling Automatic IP configuration for SNMP traps, SysLog, and DARIUS by DHCPv4 server, only IPv4 address type can be obtained automatically for SysLog, SNMP and RADIUS.



**Microsemi** Home View **System Configuration** Port Configuration

### System Configuration - Network

#### IPv4 Address Configuration

Enable DHCPv4 ☐

Use the following Static IP address:

IPv4 Address: 192.168.0.50

IPv4 Subnet Mask: 255.255.255.0

IPv4 Default Gateway: 192.168.0.1

IPv4 DNS #1: 192.168.0.250

IPv4 DNS #2: 192.168.0.251

#### IPv6 Address Configuration

Enable DHCPv6 ☐

Use the following Static IP address:

IPv6 Address:

IPv6 Prefix: 64

IPv6 Default Gateway:

IPv6 DNS #1: 1234::12

IPv6 DNS#2:

#### Auto services configuration by DHCPv4

DHCP-Request Vendor ClassID (option 60): midspan\_ip\_list

Automatic Services Configuration by DHCP-Reply (option 43)

SNMP Managers IP (code 180) ☒

SysLog Servers IP (code 181) ☒

Radius Servers IP (code 182) ☒

**Note - Auto services configuration by DHCP**  
When creating new Vendor Option class, use code numbers 180-182, and data type as IP Address array (see user manual for detailed configuration description).

#### Network Host Name

Host name: second.floor.midspan

#### IPv4/IPv6 Remote Servers

NTP Server: 128.249.10

SysLog Server #1: 192.168.0.249



SysLog Server #2:

Save Options

Update & Save Cancel

Figure 4-21: System Configuration - Network Screen

**Table 4-6: System Configuration Network Screen Details**

Parameter	Description
<b>IPv4 Address Configuration</b> Enable DHCPv4 <input type="checkbox"/> Use the following Static IP address: IPv4 Address <input type="text" value="172.16.5.247"/> IPv4 Subnet Mask <input type="text" value="255.255.248.000"/> IPv4 Default Gateway <input type="text" value="172.16.0.2"/> IPv4 DNS #1 <input type="text" value="172.16.1.46"/> IPv4 DNS #2 <input type="text" value="172.16.1.47"/>	DHCPv4 En/Dis – When checked enables Midspan to obtain IPv4 address from DHCPv4 Server. IPv4 Address – Static IPv4 address to be used in case DHCPv4 is disabled. IPv4 Subnet Mask – Static IPv4 subnet mask to be used in case DHCPv4 is disabled. IPv4 Default Gateway – Static IPv4 default gateway to be used in case DHCPv4 is disabled. IPv4 DNS #1 – Static IPv4. 1 <sup>st</sup> DNS IPv4 address to be used in case DHCPv4 is disabled. IPv4 DNS #2 – Static IPv4. 2 <sup>nd</sup> DNS IPv4 address to be used in case DHCPv4 is disabled.
<b>Auto services configuration by DHCPv4</b> DHCP-Request Vendor ClassID (option 60): <input type="text" value="midspan_ip_list"/> Automatic Services Configuration by DHCP-Reply (option 43) SNMP Managers IP (code 180) <input type="checkbox"/> SysLog Servers IP (code 181) <input type="checkbox"/> Radius Servers IP (code 182) <input type="checkbox"/>	Set Vendor Class ID string (DHCPv4 option #60) within DHCPv4 request message sent by Midspan to DHCP Server. Whenever DHCPv4 is active, Enable/Disable DHCPv4 Server to automatically configure SNMP Managers IP, SysLog Server IP, and RADIUS Server IP (for detailed configuration example see manual).
<b>Network Host Name</b> Host name <input type="text" value="midspan.2nd.floor"/>	Midspan Hostname to be send within DHCPv4 and DHCPv6 messages.
<b>IPv6 Address Configuration</b> Enable DHCPv6 <input type="checkbox"/> Use the following Static IP address: IPv6 Address <input type="text" value="1234::AB:3A2"/> IPv6 Prefix <input type="text" value="64"/> IPv6 Default Gateway <input type="text" value="1234::1"/> IPv6 DNS #1 <input type="text" value="1234::98"/> IPv6 DNS#2 <input type="text" value="1234::99"/>	DHCPv6 En/Dis – When checked enables Midspan to obtain IPv6 address from DHCPv6 Server. <div>  <b>NOTES:</b> <ul style="list-style-type: none"> <li>DHCPv6 functionality varies by M&amp;O bits which are advertised by IPv6 Router over the Network.</li> <li>M=1, O=1: Obtain IPv6 address &amp; DNS from DHCPv6 Server</li> <li>M=0, O=1: Obtain only DNS from DHCPv6 Server. Use Automatic link-local IPv6 address</li> </ul> </div> IPv6 Address – Static IPv6 address to be used in case DHCPv6 is disabled. IPv6 Prefix – Static IPv6 prefix (subnet mask) to be used in case DHCPv6 is disabled. IPv6 Default Gateway – Static IPv6 default gateway to be used in case DHCPv6 is disabled. IPv6 DNS #1 – Static IPv6. 1 <sup>st</sup> DNS IPv6 address to be used in case DHCPv6 is disabled. IPv6 DNS #2 – Static IPv6 2 <sup>nd</sup> . DNS IPv6 address to be used in case DHCPv6 is disabled.
<b>IPv4/IPv6 Remote Servers</b> NTP Server <input type="text" value="128.249.1.10"/> SysLog Server #1 <input type="text" value="192.168.0.10"/> SysLog Server #2 <input type="text" value="syslog.server1"/>	NTP Server – IPv4/IPv6/Hostname address of a remote NTP Server. <div>  <b>NOTES:</b> <p>Local time GMT offset can be configured via the Weekly Schedule Port Activation WEB page.</p> </div>


## Power Over Ethernet Power View Pro User Guide

	SysLog Server #1 – IPv4/IPv6/Hostname address of remote SysLog Server #1.
	SysLog Server #2 – IPv4/IPv6/Hostname address of remote SysLog Server #2.
Update & Save	Updates new network parameters. All properties and Remote Server parameters become effective only after this button has been clicked.
Cancel	Cancels current operation and restores previous values in case Update & Save buttons were not clicked.

#### 4.3.7.2 Auto Services Configuration by DHCPv4


DHCPv4 Server can be configured (see Figure 4-22) to automatically set the Midspan SNMP Manager List, SysLog servers, and Radius Servers. Such a configuration simplifies multiple Midspans management. The configuration example shown below is based on a Windows 2008 Server. The same configuration guidelines should be used when another DHCP Server type is in use.

- **Configure Midspan DHCP Vendor Class ID (DHCP option 60) on Midspan:** Set Vendor Class ID string which will be sent from the Midspan to DHCP Server in each DHCP-Discover and DHCP-Request message.




**Figure 4-22: Auto Services Configuration by DHCP**

- **Configure DHCP Vendor Class ID on DHCP Server:** Configure same Vendor Class ID on DHCP Server. Whenever DHCP Server detects a known Vendor Class ID string, it may be configured to provide various IP addresses which are unique for each pre configured Vendor Class ID string.
  1. Right click on DHCP root and then choose Define Vendor Class (see Figure 4-23).
  2. Click **Add**.
  3. Fill in the Display name and Description fields.
  4. Click on the **ASCII** section and type midpsan\_IP\_list (Figure 4-24).
  5. Click **OK** to close the window.



**Figure 4-23: Defining Vendor Class**


## Power Over Ethernet Power View Pro User Guide



**Figure 4-24: Set Vendor Class String**


▪ **Adding Pre Defined Sub types:**

1. Right click on **DHCP** root.
2. Select the Set Predefined Options (Figure 4-25).
3. Select the new Option Class - Midspan automatic IP configuration (see Figure 4-26).
4. Click **OK**
5. Click **Add**.




**Figure 4-25: Set Predefined Options**

## Power Over Ethernet Power View Pro User Guide




**Figure 4-26: Adding Predefined Sub Types**

- In the Option Type window (Figure 4-27):
  1. Fill in the Name and Description fields.
  2. Set **Data Type** to IP Address.
  3. Check the array checkbox. The Code field must be the same as in the Midspan (Figure 4-28).
  4. Click **OK**.



**Figure 4-27: SNMP Manager Option Type**



**Figure 4-28: Midspan Option Code**

- Code 180: SNMP Manager IP list
- Code 181: SysLog IP list
- Code 182: Radius IP list




## Power Over Ethernet Power View Pro User Guide

- Repeat the same procedure to create the SysLog Manager List and Radius Manager List Option Type (Figure 4-29 and Figure 4-30).


**Figure 4-29: SysLog Option Type**

**Figure 4-30: RADIUS Option Type**

- Setting Scope Options:**
  - Select the appropriate DHCP,
  - Right Click Scope Options.
  - Select Configure Options (Figure 4-31).
  - Select the Advanced tab (Figure 4-32).
  - In the Vendor Class select the new defined vendor class (Midspan Automatic IP Configuration).




**Figure 4-31: Scope Options Configurations**




**Figure 4-32: Midspan Scope Options**

- Check the sub vendor options that the DHCP Server should advertise so as to automatically configure the various IP addresses used by the Midspan. The new configured scope options are added to the Scope Options advertised by the DHCP Server (Figure 4-34).



**Figure 4-33: Configuring Scope Options**



**Figure 4-34: Advertised Scope Options**

▪ **Setting SNMP Manager IP Address List:**

1. Select **SNMP Manager List**.
2. Right click and select **Properties** (Figure 4-35).
3. Type SNMP Manager IP Address (up to 10 SNMP Managers).
4. Click **Add**.
5. Repeat same process for SysLog IP list (up to two addresses) and Radius Servers IP list (Figure 4-36).

## Power Over Ethernet Power View Pro User Guide




Figure 4-35: SNMP Scope Options





Figure 4-36: Setting SNMP Manager IP List

- **Setting Midspan Automatic Service Configuration:** After configuring the DHCP Server to advertise the SNMP Manager List, SysLog Servers List and Radius Server List, configure which Midspan Network services should be configured dynamically, and which one should use Midspan static configuration.

As shown in Figure 4-37, SNMP Manager IP List and SysLog IP are updated dynamically by the DHCP Server. The Radius Servers IP list is not updated even if advertised by the DHCP Server. Check **Obtain IP by DHCP** checkbox and click **Update & Save**.



**System Configuration - Network**

**IPv4 Address Configuration**

Enable DHCPv4 ☐

Use the following Static IP address:

IPv4 Address: 192.168.0.50

IPv4 Subnet Mask: 255.255.255.0

IPv4 Default Gateway: 192.168.0.1

IPv4 DNS #1: 192.168.0.249

IPv4 DNS #2: 192.168.0.250

**IPv6 Address Configuration**

Enable DHCPv6 ☐

Use the following Static IP address:

IPv6 Address: 1234::AB:3A2

IPv6 Prefix: 64

IPv6 Default Gateway: 1234::1

IPv6 DNS #1: 1234::98

IPv6 DNS #2: 1234::99

**Auto services configuration by DHCPv4**

DHCP-Request Vendor ClassID (option 60): midspan\_ip\_list

Automatic Services Configuration by DHCP-Reply (option 43)

SNMP Managers IP (code 180) ☒

SysLog Servers IP (code 181) ☒

Radius Servers IP (code 182) ☐

**Note - Auto services configuration by DHCP**  
When creating new Vendor Option class, use code numbers 180-182, and data type as IP Address array (see user manual for detailed configuration description).

**Network Host Name**

Host name: second.floor.midspan

**IPv4/IPv6 Remote Servers**

NTP Server: 128.249.1.10

SysLog Server #1: 192.168.0.248

SysLog Server #2:

Save Options

Update & Save Cancel

**Figure 4-37: Midspan Automatic Service Configuration**



## NOTES:

- All IP address obtained by the Auto Service Configuration by DHCP will be saved even after Midspan DHCPv4 option was disabled

- Checking the SNMP, effect if DHCPv4 is

SNMP Managers IP (180) ☒


SysLog Servers IP (181) ☒

Radius Servers IP (182) ☐

SysLog or Radius has no disabled

### 4.3.7.3 Log Server

The Midspan can send various internal event reports to an external IPv4/IPv6 host running SysLog daemon application (see Figure 4-38) which logs those events for future use. An example of such IPv4 SysLog server application can be found at <http://www.kiwisyslog.com/>.



Date	Time	Priority	Hostname	Message
08-13-2006	11:21:37	Local0.Info	172.16.17.16	Aug 13 8:23:07 172.016.017.016 (GMT): MsgID#001 - Port #12 status changed to [Deliver Pwr]

**Figure 4-38: Syslog Server Log Events**

SysLog messages are sent whenever the SysLog Server's IP field is other than 0.0.0, or none empty string. The following events may be sent by the Midspan:

- System UP
- Port status has changed (PoE port was changed to another RFC3621 SNMP MIB port state)
- Midspan delivers power above xy% threshold
- Midspan delivers power less then xy% threshold (after exceeded power message was sent)
- Remote user tried to access web view pages using an incorrect username or password
- Remote user tried to access web configuration pages using incorrect username or password
- Remote user tried to post web form using incorrect username or password
- Unit was restored to factory default values
- Unit configuration was changed
- PoE controller reset was detected
- Remote Telnet/SSH user failed to login (incorrect username or password)
- Remote Telnet/SSH/Web user was rejected by RADIUS Server (incorrect username or password)
- Remote Telnet/SSH/Web user was rejected since no reply from primary and secondary RADIUS Server
- Remote Telnet/SSH/web user got viewing access privilege from remote RADIUS Server, while trying to access configuration section
- Weekly Schedule override key was inserted
- Weekly Schedule override key was removed
- Remote UPS operates on battery
- Remote UPS switched back to AC
- Maximum delivered power by Midspan was changed by remote SNMP manager or UPS dynamic power management algorithm

#### **Additional Midspan 90xxG/95xxG/96xxG55xxG SysLog Messages:**

- Internal Power Source failure. External Power Source is in use
- Internal Power Source was restored
- External Power Source failure
- External Power Source was restored
- Midspan is connected to incompatible Power-Backup source type. Turn unit off and disconnect it.

**NOTE:**

Each SysLog message contains a message date and time (GMT). The Midspan acquires date & time from the Network NTP Server.

### 4.3.7.4 NTP Server

Whenever a valid NTP Server IPv4/IPv6/NTP-Server-hostname is configured, the Midspan acquires date & time (GMT) from the Network NTP Server. In cases where no valid IP is set, or in cases where the Midspan fails to acquire time from the NTP Server, initial Midspan time will be set to 1/1/2005 as default.

### 4.3.8 System Configuration SNMP

The Unit's SNMP agent (v1/v2/v3) can be accessed either by IPv4 or IPv6. It enables a remote SNMP management station to monitor and configure the unit as per RFC3621 (enable/disable PoE ports, view total power consumption, etc) and view MIB-II Network statistics. The Private MIB extends PoE functionality beyond the RFC3621 PoE MIB. For example:

- Set each individual PoE port maximum power
- Read each individual port current power
- Limit entire Midspan maximum power

The SNMPv3 offers a secured method for accessing the Midspan, both for configuration and monitoring. SNMP Network packets may be authenticated by MD5 and encrypted by DES.

The System Configuration SNMP screen enables configuration of SNMP parameters common to both SNMPv1/v2 and SNMPv3 (SNMPv1/2 community string is the only exception). The following parameters can be configured (see Figure 4-39):

- SNMPv1/v2c Community Strings
- MIB-II System Information
- Remote Trap SNMPv2c/v3 Managers List
- RFC3621 PoE MIB partial configuration parameters

Figure 4-39: System Configuration SNMP Screen

#### 4.3.8.1 SNMPv2c

The SNMPv2c feature (Figure 4-40) enables/disables an SNMP agent to respond to SNMPv1/v2c get/set commands, generated by remote SNMP Management station as HP OpenView, IBM Tivoli, etc.

Community strings – Get/Set/Trap community strings are actually SNMP passwords. To enable remote SNMP manager communication with the device, you must configure his community strings to match those of the Midspan. Community Strings window enables configuration of the following parameters:

Figure 4-40: SNMPv2 Window



**Table 4-7: SNMPv2 Field Details**

Field	Description
Enable SNMPv2c	Enable/Disable SNMPv1/v2c agent.
Get community	Password to be used by remote SNMP NMS station for SNMP GET commands.
Set community	Password to be used by remote SNMP NMS station for SNMP SET commands.
Trap community	Each TRAP sent by the Midspan to remote NMS managers contains a Trap community string password. It must match remote SNMP NMS managers password or otherwise be discarded by SNMP manager.

## 4.3.8.2 System Information (MIB-II, v2c/v3)

The System Information window enables configuring the following:

**Table 4-8: System Information Window**

Button/Checkbox	Description
SysContact	SNMP MIB-II 1.3.6.1.2.1.1.4: Textual identification of the contact person for this managed node, joined by information on how to contact this person.
SysName	SNMP MIB-II 1.3.6.1.2.1.1.5: Textual identification of an administratively-assigned name for current managed node.
SysLocation	SNMP MIB-II 1.3.6.1.2.1.1.6: Textual identification of the physical location of current node.

## 4.3.8.3 PoE MIB (RFC3621, v2c/v3)

This window simplifies the configuration of two major RFC3621 PoE MIB parameters:

**Table 4-9: RFC3621 PoE MIB Parameters**

Button/Checkbox	Description
Enable Notification	Allows/prohibits unit from sending RFC3621 PoE traps (both SNMPv2c and SNMPv3)
Notify Exceeded Power Usage (1-99%)	If Enable Notification is checked, Midspan will send a trap whenever total power consumption exceeds xy%.

## 4.3.8.4 Remote Trap SNMP Managers List

This window enables configuration of up to 10 remote IPv4/IPv6 SNMP managers (see Figure 4-41). Whenever Midspan needs to send a trap message, the trap will be duplicated and sent by the Midspan to all the remote SNMP managers (in cases where both SNMPv2c and SNMPv3 are set, each trap will be sent twice, once by SNMPv2c and once by SNMPv3).

**IPv4/IPv6 Remote Trap SNMP Managers List (v2c/v3)**


Trap Manager #1	<input type="text" value="snmp.trap.manager"/>
Trap Manager #2	<input type="text" value="172.16.5.229"/>
Trap Manager #3	<input type="text"/>
Trap Manager #4	<input type="text"/>
Trap Manager #5	<input type="text"/>
Trap Manager #6	<input type="text"/>
Trap Manager #7	<input type="text"/>
Trap Manager #8	<input type="text"/>
Trap Manager #9	<input type="text"/>
Trap Manager #10	<input type="text"/>

**Figure 4-41: Remote Trap SNMP Managers List**

Button	Description
Update & Save	Updates Midspan functionality per the new configuration. All SNMP parameters become effective only after this button has been clicked!
Cancel	Cancels current operation and restores previous values

## 4.3.9 System Configuration SNMPv3

The System Configuration SNMPv3 menu (see Figure 4-42) enables configuration of three different SNMPv3 user types and notification (trap) which requires similar parameters as any other SNMPv3 user.



**Figure 4-42: System Configuration SNMPv3 Screen**

- **Enable/Disable SNMPv3:** Enables/disables SNMPv3 agent to respond to SNMPv3 GET/SET messages sent by remote SNMP management station (note that SNMPv3 works independently from SNMPv2c).
- **Guest User:** Enables read only access to the MIB-II System Oid tree. It should be used by SNMP managers who prefer not to expose their real username and password to pool the device for "keep alive" reports. A guest user has no authentication or privacy (encryption) ability.
- **View User:** Has read only (GET) access to all SNMP branches but cannot perform any modifications (SET).
  - User Name: SNMPv3 user (mandatory field).
  - Authentication Password (MD5): Applicable when MD5 or MD5+DES are being used.
  - Privacy Password (DES): Applicable only when MD5+DES are being used.
  - Authentication + Encryption: Enables selection of one of three security levels:
    - None: SNMPv3 packets are neither authenticated nor encrypted.
    - MD5: SNMPv3 packets are authenticated but not encrypted.
    - MD5+DES: SNMPv3 packets are authenticated and encrypted.
- **Admin User:** Has full reading (GET) and writing (SET) access to all SNMP branches.
  - User Name: SNMPv3 user (mandatory field).
  - Authentication Password (MD5): Applicable when MD5 or MD5+DES are being used.
  - Privacy Password (DES): applicable only when MD5+DES are being used.
  - Authentication + Encryption: Enables selection of one of three security levels:
    - None: SNMPv3 packets are not authenticated or encrypted.

- MD5: SNMPv3 packets are authenticated but not encrypted.
- MD5+DES: SNMPv3 packets are authenticated and encrypted.
- **Notification Trap:** SNMPv3 trap configuration parameters are identical to SNMPv3 user
  - User Name: SNMPv3 user (mandatory field).
  - Authentication Password (MD5): applicable when MD5 or MD5+DES is being used.
  - Privacy Password (DES): Applicable only when MD5+DES is being used.
  - Authentication + Encryption: Enables selection of one of three security levels:
    - None: SNMPv3 packets are not authenticated and neither encrypted
    - MD5: SNMPv3 packets are authenticated but not encrypted
    - MD5+DES: SNMPv3 packets is authenticated and encrypted

## 4.3.10 System Configuration Security

The System Configuration Security menu enables configuration of the following parameters (see Figure 4-43):

- WEB Secure Access & Configuration
- Telnet/SSH View & Configuration
- Remote Access





Figure 4-43: System Configuration Security Screen

### 4.3.10.1 Web Secure Access & Configuration

Web pages are divided into two sections, View and Configuration. View web pages provide status reports and configuration summaries, without being able to change configuration. Configuration web pages (under System Configuration and Port Configuration) enable the user to view and modify the Midspan configuration.

View web pages and Configuration web pages use different passwords. View user name and password provides access only to View web pages, while configuration user name and password provides access both to View and Configuration Web pages (see Figure 4-44).



The screenshot shows a web interface titled "Web Secure Access & Configuration". It contains two sections. The first section, "Protect View by Password", has an unchecked checkbox and three input fields: "User Name" with the value "user", "Password" with masked characters, and "Confirm Password" with masked characters. The second section, "Protect Configuration by Password", has a checked checkbox and three input fields: "User Name" with the value "admin", "Password" with masked characters, and "Confirm Password" with masked characters.

Figure 4-44: Web Secure Access & Configuration Window



**NOTE:**


Disabling Web View/Configuration password protection is applicable only when RADIUS Authentication is disabled!

## 4.3.10.2 Telnet/SSH View & Configuration

The Telnet/SSH remote terminal are always password protected.

The Telnet/SSH menu is divided into View privilege and Configuration privilege sub menus (see Figure 4-45).

- **View privilege:** Can view Telnet/SSH text menus but will be rejected when trying to access the Configuration text menus.
- **Configuration privilege:** can access both to View and Configuration text menus.



The screenshot shows a web interface titled "Telnet / SSH View & Configuration". It contains two sections. The first section, "Viewer privilege", has two input fields: "User Name" with the value "user" and "Password" with masked characters. The second section, "Configuration privilege", has two input fields: "User Name" with the value "admin" and "Password" with masked characters.

Figure 4-45: Telnet/SSH View & Configuration Window



**NOTE:**

Web, Telnet/SSH username and password are applicable only in cases where RADIUS Authentication is disabled.

## Power Over Ethernet Power View Pro User Guide

### Remote Terminal view menu example

```

View Menu
-----
1. View PoE ports status
2. View network parameters
3. View ACL (Access List) filter parameters
4. View time & system up time
5. View application & Boot software version

ESC - Return to previous menu
  
```

### Remote Terminal configuration menu example

```

Configuration & Maintenance Menu
-----
1. Enable/Disable PoE Port
2. Network configuration

3. Download configuration file from TFTP Server (reset only Manager module)
4. Upload configuration file to TFTP Server
5. Download WEB SSL Certificate from TFTP Server (reset only Manager module)
6. Software update menu

7. Turn RADIUS,ACL Filter off. Restore all user & password to factory default
8. Restore unit to factory default (excluding IP configuration)

9. Reset Manager module
A. Reset unit

B. Enable/Disable auto ping to Default Gateway to ensure Network connectivity

ESC - Return to previous menu
  
```

### 4.3.10.3 Remote Access

See Figure 4-46.

**Figure 4-46: Remote Access Window**

- **Enable Telnet / SSH / None:** Enables/disables remote IPv4/IPv6 terminal access by Telnet, SSH or none of them.
- **Enable Web SSL Encryption:** When checked, enables encryption of WEB pages between remote WEB client and an on-board WEB Server.



**NOTE:**

Due to Web browser Web pages caching, whenever changing the Web SSL encryption method (encrypted/non encrypted) close the Web browser and re-open it.

Button	Description
Update & Save	Updates Midspan parameters and saves configuration. All Remote Access parameters become effective only after this button has been clicked.

Cancel	Cancels current operation and restores previous values (in cases where Update & Save was not clicked).
--------	--

## 4.3.11 System Configuration - RADIUS

Whenever the IPv4 RADIUS client is enabled (see Figure 4-47), the remote Web/Telnet/SSH username and password are sent to the RADIUS Server for authentication purposes. This in turn can provide the user with a viewer access level, administrator access level, or reject the remote user.




### NOTE:

Any invalid activity (e.g. user was rejected, user tried to access the configuration section), is reported to the SysLog Server



### NOTE:

Please view attached CD under Documentation > Technical Notes, on how to configure Midspan RADIUS to work against Cisco ACS Radius Server



**System Configuration - RADIUS**

RADIUS Authentication (View & Configuration)

Enable RADIUS Authentication	<input type="checkbox"/>
Enable RADIUS Accounting Report	<input type="checkbox"/>
Authentication Method	CHAP
Primary RADIUS Server IP Address	172 . 016 . 005 . 254
Secondary RADIUS Server IP Address	172 . 016 . 005 . 253
Shared Secret	testing123
Authentication UDP port	1812
Accounting UDP port	1813
Timeout (Sec)	2

**Note #1**  
To get Administrator privileges, RADIUS Server Authentication-Reply has to contain 'callback-Number' attribute with 'admin' value.

**Note #2**  
Each Midspan authentication-Request message includes 'Calling-Station-ID' attribute with one of the following values: 'telnet', 'ssh' or 'web'. RADIUS Server may use it to provide different privilege access level.

Save Options

Update & Save Cancel

Figure 4-47: RADIUS Configuration Screen

- **Enable RADIUS Authentication:** When checked, all remote Telnet/SSH/Web users will be authenticated by the RADIUS Server.



### NOTE:

To deactivate RADIUS in case it was enabled while configured incorrectly, connect to Midspan serial port (38400), and select from configuration menu:  
Turn RADIUS, ACL Filter off. Restore all user & password to factory default

- **Enable RADIUS Accounting Report:** When enabled, (checked), the Midspan will send an accounting report whenever login or logout of remote Web/Telnet/SSH users occurs. Note that the Accounting report can be enabled only if RADIUS Authentication is enabled.
- **Authentication Method:** Determines whether the remote user, username and password are sent to the RADIUS Server via PAP or CHAP (more secure).
- **Primary and Secondary RADIUS Server IP Address:** IP address of the RADIUS Server. In cases where there is no reply from the primary RADIUS server after 3 retries, the same authentication request will be sent to the backup RADIUS Server.
- **Shared Secret:** The same string must be configured both in the RADIUS server and the Midspan RADIUS client.
- **Authentication UDP Port:** Should not be changed, unless you use a RADIUS Server which utilizes UDP port 1645.
- **Accounting UDP Port:** Should not be changed, unless you use a RADIUS Server which utilizes UDP port 1646.
- **Timeout:** A period of time (in seconds) during which the Midspan RADIUS client waits for a reply from the RADIUS Server before resending a request. Note that the Midspan RADIUS client retries up to 3 times before accessing the backup RADIUS server. For example, if timeout equals two seconds, the backup server will be accessed only after 6 seconds.

### 4.3.11.1 Configuring RADIUS Server to Provide Viewer/Administrator a Privileged Access

To get administrator privileges, RADIUS Server Authentication-Reply must contain a 'callback-Number' attribute with an 'admin' value. Failing to do so results in providing viewing access privilege only!

### 4.3.11.2 How to Differentiate Between Telnet/SSH/Web RADIUS Users

Each Midspan authentication-request message includes a 'Calling-Station-ID' attribute with one of the following values: 'telnet', 'ssh' or 'web'. The RADIUS server may use this attribute to differentiate between Telnet/SSH/Web remote RADIUS users by providing different privilege access levels.



#### NOTE:


Whenever RADIUS authentication is enabled, Web users will be authenticated regardless of whether or not the Web username and password validation was unchecked (disabled).

### 4.3.12 System Configuration - Dynamic UPS Power Management

Dynamic UPS power management (Figure 4-48) enables extending UPS operation time whenever power failure occurs by monitoring the UPS battery level. Whenever the battery level starts to decline, the Midspan automatically starts shutting down low priority ports to save overall power consumption, which in turn extends the operation of critical PD devices by extending UPS operation time.



## Power Over Ethernet Power View Pro User Guide



**Figure 4-48: Dynamic UPS Power Management**

Parameters to be set by the user are (see Figure 4-49):


- UPS SNMP Agent Network Parameters
- Vendor Specific SNMP Parameters
- Maximum Provided Power Versus UPS Battery Level

Whenever Dynamic UPS Power Management is enabled, the View - Status screen provides information related to the UPS status (battery level, UPS operates on AC/Battery, UPS Battery remaining time).



**NOTE:**

User should not use SNMP private MIB *mainPowerUsageBudget* Oid to make changes while *Dynamic UPS Power Management* is enabled.



**System Configuration - Dynamic UPS Power Management**

**UPS SNMP Agent**

Enable Midspan Dynamic UPS Power Management	<input checked="" type="checkbox"/>
IPv4/IPv6 Address	172.16.5.225
SNMP v1/v2c	SNMPv1
GET Community String	public
UPS Vendor	MGE
Timeout (Sec)	2

**Midspan Max Power Versus UPS Battery Charge Level**

Battery Level 80%-100%	Midspan Max Power (%)	100
Battery Level 60%-80%	Midspan Max Power (%)	80
Battery Level 40%-60%	Midspan Max Power (%)	70
Battery Level 20%-40%	Midspan Max Power (%)	50
Battery Level 0%-20%	Midspan Max Power (%)	30

**Custom UPS Vendor SNMP OIDs**

Battery Charge Level (0-100%) OID	1.3.6.1.4.1.705.1.5.2.0
UPS on Battery/AC Power OID	1.3.6.1.4.1.705.1.7.3.0
UPS on Battery - OID Value	1
Battery time left OID	1.3.6.1.4.1.705.1.5.1.0
Time unit type (Minute/Second)	Sec

Save Options

Update & Save Cancel

**Figure 4-49: Dynamic UPS Power Management Screen**

In a typical Dynamic Power Management configuration, PoE ports priority and power limit **must** be set. Whenever battery level drops below 80%, 60%, 40%, etc. (main power failure), the Midspan automatically starts to shut down pre-defined low priority PoE ports. This is done to reduce UPS power consumption. The ports which are deactivated are marked by blinking green LEDs which are located on top of each port. The same report can be seen from remote by browsing to the Midspan unit and accessing View System Status Web page.



**NOTE:**

SysLog reports and SNMP Traps are sent, per each deactivated PoE port.

## 4.3.12.1 UPS SNMP Agent

- **Enable Midspan Dynamic UPS Power Management:** Enables/ disables Midspan from monitoring remote UPS over the Network by sending IPv4/IPv6 SNMP GET messages.
- **IPv4/IPv6 Address:** IPv4/IPv6 address of the UPS SNMP agent.
- **SNMP Type:** Midspan uses either SNMPv1 or SNMPv2c to communicate with the UPS SNMP agent.
- **GET Community String:** Should be identical to the community string set for the UPS SNMP agent.
- **UPS Vendor:** For APC and MGE UPS vendors, there is no need to define a dedicated SNMP Object's ID to be used to communicate with the UPS. In cases where another vendor is used, select the 'custom' option and manually type in the SNMP Object ID's to be used.



**NOTE:**

Whenever APC or MGE UPS vendors are selected, the Custom UPS Vendor SNMP OIDs section is dimmed. It is active only whenever the 'custom' option is selected!

- **Timeout:** The period of time in which the Midspan waits for reply from the UPS SNMP agent before retrying again.

## 4.3.12.2 Custom UPS Vendor SNMP OIDs

- **Battery charge level (0-100%) Oid:** An SNMP object ID which provides battery charge percentage level (100% = battery fully charged).
- **UPS on Battery/AC Oid:** SNMP object ID which reports if the UPS operates on an AC/Battery.
- **UPS on Battery Oid value:** Used by the Midspan to properly interpret UPS on AC/Battery returned value.

Note that any other returned value will be considered as if the UPS works on AC.

- **Battery time left Oid:** An SNMP object ID which provides the amount of UPS battery time remaining.
- **Time Unit Type (Minute/Second):** Selected time units (seconds, minutes or time ticks) for the Timeout parameter.

## 4.3.12.3 Midspan Max Power versus UPS Battery Charge Level

- For each 20% drop in battery level, users may limit the maximum power allocated by the Midspan (Figure 4-50). 100% power applies to Midspan maximum power when operated on AC.

Midspan Max Power Versus UPS Battery Charge Level		
Battery Level 80%-100%	Midspan Max Power (%)	100
Battery Level 60%-80%	Midspan Max Power (%)	80
Battery Level 40%-60%	Midspan Max Power (%)	70
Battery Level 20%-40%	Midspan Max Power (%)	50
Battery Level 0%-20%	Midspan Max Power (%)	30

Figure 4-50: Midspan Enforced Maximum Power Levels



### NOTES:

1. The user should make sure that the Midspan and the Ethernet Switch are connected to an AC power source through a UPS!
2. After configuring, the user should verify that the Midspan communicates with the UPS over the Network. This is performed via the View - Status page; UPS Power Management window appears on the screen with the relevant UPS information.
- 3 If UPS-Midspan communication fails, the screen below with '???' marks appears (see Figure 4-51):


UPS Power Management		
Midspan UPS Powered by		???
Midspan UPS Battery Level(%)		???
Midspan UPS Battery Time Left (min)		???

Figure 4-51: UPS-Midspan Communication Failure


## 4.3.13 System Configuration - Access List Filter

ACL (Access List) Filter enables configuring which remote networks or even remote users can manage the Midspan over the network.



## NOTES:

The Access List Filter filters (block/forward) only HTTP/HTTPS/Telnet/SSH/SNMP traffic. All other network traffic as DHCP, Ping, ARP, etc., is handled the same regardless if the Access List Filter is enabled or disabled.



**System Configuration - Access List Filtering**

[Enable Remote Users Access Filtering](#)

Enable Access List Filter ☒

[Access List Filter Mode - Accept/Block remote users](#)

Access List Filter Mode: Accept remote users according to the filter list (block all others)

**Remote users Filter list**

Filter #	Enable Filter	Source IP IPv4/IPv6-Address	IP-Prefix(mask)	Network Services				
				HTTP	HTTPS	Telnet	SSH	SNMP
1	<input checked="" type="checkbox"/>	1234::1	/ 24	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
2	<input type="checkbox"/>	172.16.5.1	/ 24	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
3	<input type="checkbox"/>		/ 24	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
4	<input type="checkbox"/>		/ 24	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
5	<input type="checkbox"/>		/ 24	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
6	<input type="checkbox"/>		/ 24	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
7	<input type="checkbox"/>		/ 24	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
8	<input type="checkbox"/>		/ 24	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
9	<input type="checkbox"/>		/ 24	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
10	<input type="checkbox"/>		/ 24	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Save Options

Update & Save Cancel

**Figure 4-52: Access List Filtering**

- **Enable Access Filter:** Enable/Disable Access List Filter functionality
- **Access List Filter Mode:**
  - Accept remote users according to the filter list (block all others): Accept only remote users which comply with one or more ACL filters. All other remote users are blocked.
  - Block remote users according to the filter list (allow all others): Accept all remote users excluding remote users which comply with one or more ACL filters.
- **Remote Users Filter List:**

Remote users Filter list								
Filter #	Enable Filter	Source IP		Network Services				
		IPv4/IPv6-Address	IP-Prefix(mask)	HTTP	HTTPS	Telnet	SSH	SNMP
1	<input checked="" type="checkbox"/>	1234::1	/ 24	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

**Figure 4-53: Access List Filtering**

A user can configure up to ten ACL filters. The IPv4/IPv6 -Address, plus IP-Prefix (mask), controls the size of the IP network which is affected by these filter settings. IP-Prefix is equivalent to IP-Mask. For example, IP-Prefix 24 = 255.255.255.0, IP-Prefix 16 = 255.255.0.0.

Each filter can be configured to affect one or more of the following network protocols:

- HTTP
- HTTPS
- Telnet
- SSH
- SNMP

The filter configuration does not affect any other network traffic.

Field	Description
Enable Filter	Enable/Disable one out of ten ACL filters
Source IP: IP-Address	IPv4/IPv6-Address or IPv4/IPv6-Net to be affected by this ACL filter
Source IP: IP-Prefix	IPv4-Prefix (1 - 32) or IPv6-Prefix (1-128) controls the range of IPs which are affected by this filter setting. <b>Example:</b> 32 (255.255.255.255) = Single IP address 24 (255.255.255.0) = 256 IP address
Network Services: HTTP	En/Dis ACL filter from filtering remote user HTTP (Web) access
Network Services: HTTPS	En/Dis ACL filter from filtering remote user HTTPS (Web) access
Network Services: Telnet	En/Dis ACL filter from filtering remote user Telnet access
Network Services: SSH	En/Dis ACL filter from filtering remote user SSH (secure Telnet) access
Network Services: SNMP	En/Dis ACL filter from filtering remote user SNMPv1-v3 access

## 4.3.13.1 ACL Filter Statistics

Via the View Menu, you can access the ACL statistics. View Menu is accessible by serial/Telnet/SSH interface (see the following figure).

View Menu	
1. View PoE ports status	
2. View network parameters	
3. View ACL (Access List) filter parameters	←
4. View time & system up time	
5. View application & Boot software version	

**Figure 4-54: View ACL Filter Parameters from View Menu**

**ACL Filter Menu options:**

- **View ACL filter configuration & statistic counters:** Displays ACL filter statistics counters
- **Clear ACL filter statistic counters:** Clears ACL filter statistics counters

ACL Filter Menu	
1.	View ACL filter configuration & statistic counters
2.	Clear ACL filter statistic counters

**Figure 4-55: View ACL Filter Parameters**

ACL statistics offers easy ACL configuration verification by reporting how many packets are accepted (or blocked in Block mode) by each ACL filter, and by which network protocol (HTTP, HTTPS, Telnet, SSH, SNMP).

Access List Filter Statistics Counters: Accept mode					ACL Mode (Accept/Block)
# 1:HTTP:44	,HTTPS:0	,Telnet:0	,SSH:0	,SNMP:6	
# 2:HTTP:0	,HTTPS:0	,Telnet:0	,SSH:0	,SNMP:0	
# 3:HTTP:0	,HTTPS:0	,Telnet:0	,SSH:0	,SNMP:0	
# 4:HTTP:0	,HTTPS:0	,Telnet:0	,SSH:0	,SNMP:0	
# 5:HTTP:0	,HTTPS:0	,Telnet:0	,SSH:0	,SNMP:0	
# 6:HTTP:0	,HTTPS:0	,Telnet:0	,SSH:0	,SNMP:0	
# 7:HTTP:0	,HTTPS:0	,Telnet:0	,SSH:0	,SNMP:0	
# 8:HTTP:0	,HTTPS:0	,Telnet:0	,SSH:0	,SNMP:0	
# 9:HTTP:0	,HTTPS:0	,Telnet:0	,SSH:0	,SNMP:0	
#10:HTTP:0	,HTTPS:0	,Telnet:0	,SSH:0	,SNMP:0	
Number of HTTP packets that were accepted (or blocked in Block mode) by ACL filter#1					
Total accepted packets (HTTP/HTTPS/Telnet/SSH/SNMP): 50					Total accepted packets by all ACL filters
Total blocked packets (HTTP/HTTPS/Telnet/SSH/SNMP): 8					Total blocked packets by all ACL filters


**Figure 4-56: View ACL Filter Statistics Counters**

## 4.3.13.2 ACL Filter Configuration Example

ACL (Access List Filter) example filtering requirements:

- Enable the Midspan to be fully managed only from IP-Network 172.16.5.0-172.16.5.255.
- Limit remote user with IP 174.16.124.35 to manage the Midspan only by HTTP ( Web) Solution:

Figure 4-57 illustrates the required settings for complying with the above ACL filter requirements.



The screenshot shows the 'Enable Remote Users Access Filtering' configuration page. It includes a checkbox for 'Enable Access List Filter' which is checked. Below it is a dropdown for 'Access List Filter Mode' set to 'Accept remote users according to the filter list (block all others)'. At the bottom is a table titled 'Remote users Filter list' with columns for Filter #, Enable Filter, Source IP (IPv4/IPv6-Address and IP-Prefix(mask)), and Network Services (HTTP, HTTPS, Telnet, SSH, SNMP).

Filter #	Enable Filter	Source IP		Network Services				
		IPv4/IPv6-Address	IP-Prefix(mask)	HTTP	HTTPS	Telnet	SSH	SNMP
1	<input checked="" type="checkbox"/>	172.16.5.0	/ 24	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
2	<input type="checkbox"/>	174.16.124.35	/ 32	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Figure 4-57: ACL Filter Configuration Example




### NOTES:

If Midspan network connectivity is lost due to incorrect ACL filter configuration, connect to Midspan via serial port (38400), and from the configuration menu select one of the following options:

1. **Turn RADIUS, ACL Filter off. Restore all users & passwords to factory default–** turn off ACL without changing unit configuration
2. **Restore the unit to factory default. Keep IP configuration unchanged –** turn off ACL filter as part of restoring the unit to factory default configuration (without modifying IP configuration).

## 4.3.14 System Configuration - Product Parameters - 65xx, 65xxG Family



**Microsemi** Home View **System Configuration** Port Configuration

### System Configuration - Product Parameters

**Midspan Nickname**

Midspan Nickname: Midspan PoE Device

**System Detection Method**

PD Detection Method: IEEE802.3af + Legacy

**Status View Refresh Rate**

Refresh Rate (in seconds): 10

Save Options

Update & Save Cancel

**Figure 4-58: System Configuration Product Parameters Screen**

Use the System Configuration Product Parameters Screen to configure the following parameters:


- Midspan Nickname
- System Detection Method
- Status View Refresh Rate

Button	Description
<b>Midspan Nickname</b> Midspan Nickname: Midspan PoE Device	Assists network managers to identify a Midspan by assigning a unique name for each Midspan device. Midspan nickname is displayed when browsing to view->status web page, or accessing the Midspan through Serial / Telnet / SSH
<b>System Detection Method</b> PD Detection Method: IEEE802.3af + Legacy	<ul style="list-style-type: none"> <li>• IEEE 802.3af</li> <li>• IEEE 802.3af + Legacy (default)</li> </ul>



<b>Status View Refresh Rate</b> Refresh Rate (in seconds) <input type="text" value="10"/>	Set refresh rate for View System Status web page.
<input type="button" value="Update &amp; Save"/>	Updates Midspan product based parameters. All the product parameters become effective only after this button has been clicked!
<input type="button" value="Cancel"/>	Cancels current operation and restores previous values

## 4.3.15 System Configuration - Product Parameters - 90xxG Family



**System Configuration - Product Parameters**

**System Detection Method**

PD Detection Method

Enable pre 802.3at ☒

**Extended Power Mode (36W per port)**

Enable Extended Power Mode ☒

**Power Backup Mode**

Power Backup Mode

**Midspan Nickname**

Midspan Nickname

**Status View Refresh Rate**

Refresh Rate (in seconds)

**Save Options**

**Figure 4-59: System Configuration Product Parameters Screen**

Product parameters set by the user include (see Figure 4-59):


- System Detection Method
- Other vendors pre 802.3at PD (as Cisco 125x access points)
- Extended Power Mode
- Power Backup Mode

## Power Over Ethernet Power View Pro User Guide

- Midspan Nickname
- Status View Refresh Rate

Button	Description
PD Detection Method <input type="text" value="IEEE802.3af + IEEE802.3at + Legacy"/>	PD Detection Method for 90xxG Midspan series: <ul style="list-style-type: none"> <li>• IEEE 802.3af + IEEE 802.3at</li> <li>• IEEE 802.3af + IEEE 802.3at + Legacy</li> </ul>
Enable pre 802.3at <input checked="" type="checkbox"/>	Powers pre 802.3at PD devices including Cisco 125X access points.
<b>Extended Power Mode (36W per port)</b> Enable Extended Power Mode <input checked="" type="checkbox"/>	Extend PD maximum power beyond 802.3at 30W to 36W
<b>Power Backup Mode</b> Power Backup Mode <input type="text" value="Redundancy"/>	External Power Backup mode <ul style="list-style-type: none"> <li>• <b>Redundancy:</b> In this mode the external power source backs up the internal power supply of the Midspan. In case the internal power supply fails to operate, the external source will pick up the full load and all the ports will continue to function normally.</li> <li>• <b>Maximum Power:</b> In this mode the external power source offers additional power on top of the power delivered by the internal power supply. For example the PD-9024G/ACDC/M Midspan is using internal power supply of 430W, when external power source is connected in Max Power mode(PD-RPS-450) the user available power will be 860W (430W internal + 430W external)</li> </ul>
<b>Midspan Nickname</b> Midspan Nickname <input type="text" value="Midspan PoE Device"/>	Assists network managers to identify a Midspan by assigning a unique name for each Midspan device. Midspan nickname is displayed when browsing to view->status web page, or accessing the Midspan by Serial / Telnet / SSH.
<b>Status View Refresh Rate</b> Refresh Rate (in seconds) <input type="text" value="10"/>	Enables Setting of System Status WEB page refresh rate.
<input type="button" value="Update &amp; Save"/>	Updates Midspan product based parameters. All the product parameters become effective only after this button has been clicked!
<input type="button" value="Cancel"/>	Cancels current operation and restores previous values

## 4.3.16 System Configuration - Product Parameters - 95xxG Family



**Microsemi** Home View **System Configuration** Port Configuration

### System Configuration - Product Parameters

**System Detection Method**  
 PD Detection Method: IEEE802.3af + IEEE802.3at + Legacy

**Midspan Nickname**  
 Midspan Nickname: Midspan PoE Device

**Extended Power Mode (72W per port)**  
 Enable Extended Power Mode: ☒

**Status View Refresh Rate**  
 Refresh Rate (seconds): 10

**Power Backup Mode**  
 Power Backup Mode: Redundancy

**Temperature Format (Fahrenheit / Celcius)**  
 Temperature format: Fahrenheit

**Unit maximum power Vs Unit Temperature**  
 Enable automatic unit maximum power reduction: ☐

Save Options  
 Update & Save Cancel

**Figure 4-60: System Configuration Product Parameters Screen**

Product parameters set by the user include (see Figure 4-60):

- System Detection Method
- Extended Power Mode
- Power Backup Mode
- Unit maximum power Vs Unit Temperature (see note below)
- Midspan Nickname
- Status View Refresh Rate
- Temperature Format (Fahrenheit/Celsius)




**NOTE:**

Please uncheck 'Unit maximum power Vs Unit Temperature' checkbox whenever connecting 95xxG Midspan to a redundant power source such as another Midspan or RPS unit.

## Power Over Ethernet Power View Pro User Guide

Button	Description
<p><b>System Detection Method</b></p> <p>PD Detection Method <span>IEEE802.3af + IEEE802.3at + Legacy</span></p>	<p>PD Detection Method for 95xxG Midspan series:</p> <ul style="list-style-type: none"> <li>IEEE 802.3af + IEEE 802.3at</li> <li>IEEE 802.3af + IEEE 802.3at + Legacy</li> </ul>
<p><b>Extended Power Mode (72W per port)</b></p> <p>Enable Extended Power Mode <input checked="" type="checkbox"/></p>	<p>Extends PD maximum power beyond 2 x 802.3at 60 W to 72 W</p>
<p><b>Power Backup Mode</b></p> <p>Power Backup Mode <span>Redundancy</span></p>	<p>External Power Backup mode</p> <ul style="list-style-type: none"> <li><b>Redundancy:</b> In this mode the external power source backs up the internal power supply of the Midspan. In case the internal power supply fails to operate, the external source picks up the full load and all the ports continue to function normally.</li> <li><b>Maximum Power:</b> In this mode the external power source offers additional power on top of the power delivered by the internal power supply. For example, if the PD-9506G/ACDC/M Midspan uses a 430 W internal power supply, and an external power source is connected in Max Power mode (PD-RPS-450), the user available power is 860 W (430 W internal + 430 W external)</li> </ul>
<p><b>Unit maximum power Vs Unit Temperature</b></p> <p>Enable automatic unit maximum power reduction <input type="checkbox"/></p>	<p>Enables the Midspan to automatically lower the maximum power that can be provided by the unit whenever internal unit temperature becomes too high (typically due to improper cooling).</p>
<p><b>Midspan Nickname</b></p> <p>Midspan Nickname <span>Midspan PoE Device</span></p>	<p>Assists network managers to identify a Midspan by assigning a unique name for each Midspan device. Midspan nickname is displayed when browsing to view-&gt;status web page, or accessing the Midspan by Serial / Telnet / SSH.</p>
<p><b>Status View Refresh Rate</b></p> <p>Refresh Rate (seconds) <span>10</span></p>	<p>Sets the View System Status WEB page refresh rate.</p>
<p><b>Temperature Format (Fahrenheit / Celcius)</b></p> <p>Temperature format <span>Fahrenheit</span></p>	<p>Reports the Midspan temperature in View System Status WEB page in Fahrenheit or Celsius</p>
<p><b>Update &amp; Save</b></p>	<p>Updates Midspan product based parameters. <b>Note:</b> All product parameters become effective only <b>after</b> clicking this button!</p>
<p><b>Cancel</b></p>	<p>Cancels current operation and restores previous values</p>

## 4.3.17 System Configuration – Product Parameters – 96xxG Family



The screenshot shows the 'System Configuration - Product Parameters' screen. The interface includes a top navigation bar with 'Home', 'View', 'System Configuration' (selected), and 'Port Configuration'. The main content area is titled 'System Configuration - Product Parameters' and contains several configuration sections:

- System Detection Method:** A dropdown menu set to 'HDBaseT PoH'.
- Midspan Nickname:** A text input field containing 'Midspan PoE Device'.
- Power Backup Mode:** A dropdown menu set to 'Redundancy'.
- Status View Refresh Rate:** A text input field containing '10'.
- Unit maximum power Vs Unit Temperature:** A checkbox labeled 'Enable automatic unit maximum power reduction' which is currently unchecked.
- Temperature Format (Fahrenheit / Celsius):** A dropdown menu set to 'Fahrenheit'.

At the bottom, there is a 'Save Options' section with two buttons: 'Update & Save' and 'Cancel'.

**Figure 4-61: System Configuration Product Parameters Screen**

Product parameters set by the user include (see Figure 4-61):

- System Detection Method
- Power Backup Mode
- Unit maximum power Vs Unit Temperature (see note below)
- Midspan Nickname
- Status View Refresh Rate
- Temperature Format (Fahrenheit/Celsius)




**NOTE:**

**Uncheck 'Unit maximum power Vs Unit Temperature' checkbox whenever connecting 96xxG Midspan to a redundant power source such as another Midspan or RPS unit.**

## Power Over Ethernet Power View Pro User Guide

Button	Description
<p><b>System Detection Method</b></p> <p>PD Detection Method <span>HDBaseT PoH</span></p>	<p>PD Detection Method for 96xxG Midspan series:</p> <ul style="list-style-type: none"> <li>HDBaseT PoH</li> <li>HDBaseT PoH + Legacy (power also older pre PoH HDBase-T devices)</li> </ul>
<p><b>Power Backup Mode</b></p> <p>Power Backup Mode <span>Redundancy</span></p>	<p>External Power Backup mode</p> <ul style="list-style-type: none"> <li><b>Redundancy:</b> In this mode the external power source backs up the internal power supply of the Midspan. In case the internal power supply fails to operate, the external source picks up the full load and all ports continue to function normally.</li> <li><b>Maximum Power:</b> In this mode the external power source offers additional power on top of the power delivered by the internal power supply. For example, if the PD-9606G/ACDC/M Midspan uses a 950W internal power supply, and an external power source is connected in Max Power mode (PD-RPS-1000), the user available power is 1900W (950W internal + 950W external)</li> </ul>
<p><b>Unit maximum power Vs Unit Temperature</b></p> <p>Enable automatic unit maximum power reduction <input type="checkbox"/></p>	<p>Enables the Midspan to automatically lower the maximum power that unit can provide whenever internal unit temperature becomes too high (typically due to improper cooling).</p>
<p><b>Midspan Nickname</b></p> <p>Midspan Nickname <span>Midspan PoE Device</span></p>	<p>Assists network managers to identify a Midspan by assigning a unique name for each Midspan device. Midspan nickname is displayed when browsing to view-&gt;status web page, or accessing the Midspan by Serial / Telnet / SSH.</p>
<p><b>Status View Refresh Rate</b></p> <p>Refresh Rate (seconds) <span>10</span></p>	<p>Sets the View System Status WEB page refresh rate.</p>
<p><b>Temperature Format (Fahrenheit / Celcius)</b></p> <p>Temperature format <span>Fahrenheit</span></p>	<p>Reports the Midspan temperature in View System Status WEB page in Fahrenheit or Celsius</p>
<p><b>Update &amp; Save</b></p>	<p>Updates Midspan product based parameters. <b>Note:</b> All product parameters become effective only <b>after</b> clicking this button!</p>
<p><b>Cancel</b></p>	<p>Cancels current operation and restores previous values</p>

## 4.3.18 System Configuration – Product Parameters – 55xxG Family



**Microsemi** Home View **System Configuration** Port Configuration

### System Configuration - Product Parameters

**System Detection Method**  
 PD Detection Method: IEEE802.3af + IEEE802.3at

**Midspan Nickname**  
 Midspan Nickname: Midspan PoE Device

**Extended Power Mode (36W per port)**  
 Enable Extended Power Mode: ☒

**Power Backup Mode**  
 Power Backup Mode: Redundancy

**Unit maximum power Vs Unit Temperature**  
 Enable automatic unit maximum power reduction: ☐

**Status View Refresh Rate**  
 Refresh Rate (seconds): 10

**Temperature Format (Fahrenheit / Celcius)**  
 Temperature format: Fahrenheit

Save Options  
 Update & Save Cancel

**Figure 4-62: System Configuration Product Parameters Screen**

Product parameters set by the user include (see Figure 4-62):

- System Detection Method
- Extended Power Mode
- Power Backup Mode
- Unit maximum power Vs Unit Temperature (see note below)
- Midspan Nickname
- Status View Refresh Rate
- Temperature Format (Fahrenheit/Celsius)



**NOTE:**

Please uncheck 'Unit maximum power Vs Unit Temperature' checkbox whenever connecting 55xxG Midspan to a redundant power source such as another Midspan or an RPS unit.

## Power Over Ethernet Power View Pro User Guide

Button	Description
<p><b>System Detection Method</b></p> <p>PD Detection Method <span>IEEE802.3af + IEEE802.3at + Legacy</span></p>	<p>PD Detection Method for 55xxG Midspan series:</p> <ul style="list-style-type: none"> <li>IEEE 802.3af + IEEE 802.3at</li> <li>IEEE 802.3af + IEEE 802.3at + Legacy</li> </ul>
<p><b>Extended Power Mode (36W per port)</b></p> <p>Enable Extended Power Mode <input checked="" type="checkbox"/></p>	<p>Extend PD maximum power beyond 802.3at 30W to 36W</p>
<p><b>Power Backup Mode</b></p> <p>Power Backup Mode <span>Redundancy</span></p>	<p>External Power Backup mode</p> <ul style="list-style-type: none"> <li><b>Redundancy:</b> In this mode the external power source backs up the internal power supply of the Midspan. In case the internal power supply fails to operate, the external source picks up the full load and all the ports continue to function normally.</li> <li><b>Maximum Power:</b> In this mode the external power source offers additional power on top of the power delivered by the internal power supply. For example, if the PD-5524G/ACDC/M Midspan uses a 430W internal power supply, and an external power source is connected in Max Power mode (PD-RPS-450), the user available power is 860W (430W internal + 430W external)</li> </ul>
<p><b>Unit maximum power Vs Unit Temperature</b></p> <p>Enable automatic unit maximum power reduction <input type="checkbox"/></p>	<p>Enables the Midspan to automatically lower the maximum power that can be provided by the unit whenever internal unit temperature becomes too high (typically due to improper cooling).</p>
<p><b>Midspan Nickname</b></p> <p>Midspan Nickname <span>Midspan PoE Device</span></p>	<p>Assists network managers to identify a Midspan by assigning a unique name for each Midspan device. Midspan nickname is displayed when browsing to view-&gt;status web page, or accessing the Midspan by Serial / Telnet / SSH.</p>
<p><b>Status View Refresh Rate</b></p> <p>Refresh Rate (seconds) <span>10</span></p>	<p>Sets the View System Status WEB page refresh rate.</p>
<p><b>Temperature Format (Fahrenheit / Celsius)</b></p> <p>Temperature format <span>Fahrenheit</span></p>	<p>Reports the Midspan temperature in View System Status WEB page in Fahrenheit or Celsius</p>
<p><b>Update &amp; Save</b></p>	<p>Updates Midspan product based parameters. <b>Note:</b> All product parameters become effective only <b>after</b> clicking this button!</p>
<p><b>Cancel</b></p>	<p>Cancels current operation and restores previous values</p>



## 4.3.19 System Configuration Maintenance

System Configuration Maintenance screen (see Figure 4-63) offers the following options:

- Reset Manager Module
- Reset Unit
- Restoring Factory Defaults







Figure 4-63: System Configuration Maintenance Screen

## Power Over Ethernet Power View Pro User Guide

Button/Checkbox	Description
<b>Reset Manager Module</b>  <b>Note: Clicking the Reset button will Reset the Manager Module.</b>	Resets only the Manager Module without affecting Midspan PoE ports
<b>Reset Unit</b>  <b>Note: Clicking the Reset button restarts the Midspan and temporarily shuts down all PoE ports.</b>	Resets entire unit. All active PoE ports momentarily stop providing power to PoE devices (configuration does not change)
<b>Restore Factory Defaults</b>  <b>Note: Clicking the Restore button resets the Manager Module and restores the Midspan to factory defaults without changing Manager Module IP address</b>	Restore most Midspan parameters to their default value (IP isn't changed)

## Power Over Ethernet Power View Pro User Guide

### 4.4 Port Configuration Screen

Port Configuration menu enables the following (Figure 4-64):

- **Port Configuration Enable/Disable:** Provides a quick access to enable/disable one or more PoE ports.
- **Port Configuration Detailed:** Enables detailed configuration of various PoE port values such as priority, allocated power and port/PD description.
- **Port Configuration – Weekly Schedule:** Enables the user to configure weekly scheduled ports activation/deactivation.





Figure 4-64: Port Configuration Screen

## 4.4.1 Port Configuration - Enable/Disable

All ports or Individual ports can be enabled or disabled in one action.

Disabled ports are marked with a red cross on the RJ-45 port; refer to Section 4.3.4.1.




**Microsemi** Home View System Configuration **Port Configuration**

### Port Configuration - Enable/Disable Ports

#	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24
En. / Dis.	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

Actions on All Ports:


Save Options:




**Enabled ports** **Disabled ports**

#	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24
En. / Dis.	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Figure 4-65: Port Configuration Enable/Disable Screen

Button/Checkbox	Description
	<b>Enabled:</b> Enables all ports <b>Disabled:</b> Disables all ports Note: Only WEB page is effected

Button/Checkbox	Description
	<p><b>Update:</b> Clicking this button, activates the new user settings but does not store new configuration (unit reset overrides latest changes)</p> <p><b>Cancel:</b> Cancels current operation and restores previous values in cases where Update &amp; Save were not clicked</p> <p><b>Update &amp; Save:</b> Activates new setting and save updated configuration in cases where Midspan restarts.</p>



## NOTE:

If only the **Update** button is pressed, a blinking image appears near the **Save & update** button, reminding the user that latest changes were not saved. Reversing latest changes and pressing **Update**, eliminates the blinking image. Saving latest changes eliminates this image as well.

## 4.4.2 Port Configuration – Detailed

The Port Configuration Detailed screen (see Figure 4-66) enables the user to control individual ports and set-up parameters as follows:

- Enable/Disable individual PoE ports
- Provide power to PD device over two/four pair (applicable only for 95xxG/55xxG)
- Enable EEPoE for Energy efficient (applicable only for 55xxG)
- Enable PoH/802.3 at (applicable only for 96xxG)
- Set-up the priority of each port
- Allocate maximal power per port
- Add port description





Figure 4-66: Port Configuration Detailed Screen (65xx, 65xxG, 90xxG Family)



Home View System Configuration Port Configuration

## Port Configuration - Detailed

#	En. Dis.	Four Pair	Priority	Max Power	Terminal Type / Description
1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Low	72	----
2	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Low	72	----
3	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Low	72	----
4	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Low	72	----
5	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Low	72	----
6	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Low	72	----


#	En. Dis.	Four Pair	Priority	Max Power	Terminal Type / Description
7	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Low	72	----
8	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Low	72	----
9	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Low	72	----
10	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Low	72	----
11	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Low	72	----
12	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Low	72	----

Actions on All Ports

<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Low	72	
Set	Set	Set	Set	Set

Save Options

Figure 4-67: Port Configuration Detailed Screen (95xxG Family)



Home View System Configuration Port Configuration

## Port Configuration - Detailed

#	En. Dis.	PoH/ 802.3at	Max Power	Priority	Terminal Type / Description
1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	60	Low	----
2	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	95	Low	----
3	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	95	Low	----
4	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	95	Low	----
5	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	95	Low	----
6	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	95	Low	----


#	En. Dis.	PoH/ 802.3at	Max Power	Priority	Terminal Type / Description
7	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	95	Low	----
8	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	95	Low	----
9	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	95	Low	----
10	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	95	Low	----
11	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	95	Low	----
12	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	95	Low	----

Actions on All Ports

<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		Low	
Set	Set		Set	Set

Save Options

Figure 4-68: Port Configuration Detailed Screen (96xxG Family)



**Microsemi** Home View System Configuration **Port Configuration**

## Port Configuration - Detailed

#	En.	EEPoE Dis.	Mode	Priority	Max Power	Terminal Type / Description
1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		Low	36	----
2	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		Low	36	----
3	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		Low	36	----
4	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		Low	36	----
5	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		Low	36	----
6	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		Low	36	----
7	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		Low	36	----
8	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		Low	36	----
9	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		Low	36	----
10	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		Low	36	----
11	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		Low	36	----
12	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		Low	36	----


Actions on All Ports

<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Low	36	
-------------------------------------	-------------------------------------	-----	----	--

#	En.	EEPoE Dis.	Mode	Priority	Max Power	Terminal Type / Description
13	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		Low	36	----
14	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		Low	36	----
15	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		Low	36	----
16	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		Low	36	----
17	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		Low	36	----
18	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		Low	36	----
19	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		Low	36	----
20	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		Low	36	----
21	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		Low	36	----
22	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		Low	36	----
23	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		Low	36	----
24	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		Low	36	----

Save Options

**Figure 4-69: Port Configuration Detailed Screen (55xxG Family)**



**Figure 4-70: Port Configuration Detailed Screen (55xxG Family)**

To simplify the configuration of multiple ports, each parameter can be set by pressing a single button (SET), thus applying the selected values to all ports (action on all ports). See Actions on All Ports area on the lower left part of the web page, see Figure 4-66, Figure 4-67, Figure 4-68, Figure 4-69, and Figure 4-70.



**NOTE:**

1. Midspan 65xxG series enables up to 16.8 watts per port.
2. Midspan 90xxG/55xxG series enables up to 30/36 watts per port.
3. Midspan 95xxG series enables up to 60/72 watts per port.
4. Midspan 96xxG series enables up to 60 (802.3at)/95 (PoH) watts per port.

## 4.4.2.1 Ports Enable/Disable

Ports activation/deactivation is performed by the user according to actual requirements. Each PoE port can be switched to Enable or Disable state.

## 4.4.2.2 Two Pair/Four Pair (95xxG Midspan family)

Power PD device over two pair (for example traditional 802.3af/802.3at Midspan), or over four pair offering twice the 802.3at power (60/72 W).

## 4.4.2.3 EEPoE (55xxG Midspan family)

Power PD device over two pair (for example traditional 802.3af/802.3at Midspan), or over four pair offering energy efficient power for up to 36W.



### 4.4.2.4 PoH (96xxG Midspan Family)

Power HDBase-T PoH PD device over four pairs for up to 95W, or 802.3at device over four pairs for up to 60W.

### 4.4.2.5 Setting Priority

The user can assign priorities to desired PDs in cases where the Midspan is operating with a limited source of power. Priority selection is performed from the drop-down menu, located on the Priority column; three priority states are available:

- Critical
- High
- Low (default)

The Midspan allocates all available power to the PDs, according to the PoE ports sequential number, starting from port #1 up to port #24. Critical ports are powered first, followed by High Priority ports. Low priority ports are powered last. A blinking LED indicates that a port is not powered due to lack of power.

### 4.4.2.6 Allocating Maximum Power

Power allocation is performed by selecting the maximum allowed power per port from the drop-down menu, located on the Max. Power column. Available power values are:

- 65xx: Minimum = 1W, Maximum=16.8W, Default=16.8W
- 65xxG: Minimum = 1W, Maximum=16.8W, Default=16.8W
- 90xxG: Minimum = 1W, Maximum=30/36W, Default=36W
- 95xxG: Minimum = 1W, Maximum=60/72W, Default=72W
- 96xxG: Fixed 95W for PoH or 60W for 802.3at
- 55xxG: Minimum = 1W, Maximum=30/36W, Default=36W

## Power Over Ethernet Power View Pro User Guide

### 4.4.2.7 Terminal Type / Description

In this column, the operator can enter any free text such as: terminal location, name of user, telephone number, etc. representing the corresponding port. Note that the column has no effect on power itself and it functions as an assistance tool for the IT manager.

Pressing on the RJ45 icon, or the **i** icon will cause detailed Port Information web page to appear, showing Terminal Type name, and additional information described in the image below. See Figure 4-71.

The screenshot displays the PowerDsine web interface. At the top, there is a navigation bar with links: Home, View, System Configuration, and Port Configuration. The 'View' tab is selected, showing 'View - Status' and 'Midspan Nickname: Midspan PoE Device'. Below this, a diagram of the PoE device shows 12 ports. Ports 1-6 are labeled 'Data & Power Out' and 'Data In'. Ports 7-12 are labeled 'Data & Power Out'. A table below the diagram shows the status of each port:

#	1	2	3	4	5	6	7	8	9	10	11	12
Power (W)	0	0	0	0	0	0	0	0	0	0	0	0
Description												

A detailed port information window is open for Port #1, showing the following information:

Port	Enabled
Power (W)	0
Max Power (W)	0 (4-pairs)
Priority	Low
Terminal Type / Description	----
Class	0

The window also includes a 'Close' button at the bottom.

Figure 4-71: Detailed Port Information

## 4.4.3 Port Configuration - Weekly Schedule

The Weekly Schedule feature (see Figure 4-72) performs an automatic activation/deactivation of PoE ports based on a weekly activation matrix (24 x 7). Activation/Deactivation of PoE ports may be required to save power saving during weekends, for security reasons (for example turns off wireless access points during weekends, disconnect unused IP Phones, or reduce power consumption), or even to reset periodically various PoE PD devices.

**Four 24 x 7 weekly schedules schemes are available.** Each 24 x 7 scheme manages its own PoE ports, which enables different PoE ports to be turned on/off on different days and hours.



### NOTE:

In case same PoE port was assigned to be managed by two different 24x7 schemes, it will be turned on whenever port becomes enabled by one of the 24x7 weekly schedule scheme.

Prior to using this feature, the user should:

- Set the NTP Server IP address (Network Time Protocol Server)
- Set the GMT local time offset
- Update at least one out of four 24 x 7 hour matrixes to match the user specific needs
- Assign the Midspan PoE ports to be automatically turned On/Off
- Assign the PoE ports that provide power continuously




Figure 4-72: Port Configuration – Weekly Schedule



## NOTE:

1. For Weekly Schedule feature to work properly, the Midspan must have an access to NTP Server (Network Time Protocol Server).
2. Upon updating the weekly schedule NTP configuration by pressing the Update & Save button, the user should wait for a few seconds, refresh the WEB page and verify that green OK indication appears alongside the local time section (meaning that GMT time had been properly acquired).

### 4.4.3.1 Weekly Schedule Ports Activation

- **Enable Weekly Schedule:** Enables/disables the Weekly Schedule feature
- **Enable Manual Override:** Enables/disables the Manual Override key and selects the port assigned as an override key
- **Remote NTP Server:** Remote NTP (Network Time Protocol) Server IP address
- **GMT Offset:** User configured GMT offset
- **Ports On/Off Weekly Schedule:** 24 hours, 7 days checkbox matrix. The Midspan provides power only during the selected (checked) hours



## NOTE:

To simplify the configuration of the 24 x 7 matrix, the user can check all 24 ports for a specific day by checking one of the 'ALL' checkboxes.

- **Ports Assigned for Automatic Weekly Schedule Activation:** Selection of the ports to be activated/deactivated automatically by the weekly schedule feature.



## NOTE:


Disabled ports cannot be assigned for the Weekly Schedule, even if selected by the user.

**Table 4-10: Weekly Schedule Icons Reported by View-Status Web Page**

Icon/Image type	Description
	PoE port was Enabled by weekly schedule functionality
	PoE port was Disabled by weekly schedule functionality
	PoE port was assigned to act as deactivation key.

## 5 Midspan 90xxG, 95xxG, 55xxG, 96xxG – Power Backup and Power Management

Midspan 90xxG, 95xxG, 96xxG, 55xxG series can be connected to an external redundant power source (Figure 5-1) or to a secondary 90xxG, 95xxG, 96xxG, 55xxG Midspan (Figure 5-2). The same internal power supply unit must be installed in both units.



**Figure 5-1: External Power Backup**



**Figure 5-2: Secondary Midspan Power Backup**

## Power Over Ethernet Power View Pro User Guide

Table 5-1 lists the various connectivity options.

**Table 5-1: Power Backup Connectivity Options**

Midspan Type	Power Backup Type											
	RPS - 450	RPS - 1000	PD-9006G /ACDC/ M	PD-9012G /ACDC/M	PD-9024G /ACDC/M	PD-9024G /ACDC/M/F	PD-9506G /ACDC/M	PD-9512G /ACDC/M	PD-9524G /ACDC/M	PD-5524G /ACDC/M	PD-9606G /ACDC/M	PD-9612G /ACDC/M
PD-9006G/ACDC/M	√		√	√	√		√			√		
PD-9012G/ACDC/M	√		√	√	√		√			√		
PD-9024G/ACDC/M	√		√	√	√		√			√		
PD-9024G/ACDC/M/F		√				√		√	√		√	√
PD-9506G/ACDC/M	√		√	√	√		√			√		
PD-9512G/ACDC/M		√				√		√	√		√	√
PD-9524G/ACDC/M		√				√		√	√		√	√
PD-5524G/ACDC/M	√		√	√	√		√			√		
PD-9606G/ACDC/M		√				√		√	√		√	√
PD-9612G/ACDC/M		√				√		√	√		√	√

SNMP RFC3621 MIB and private MIB Object IDs which apply to unit power supply capabilities or total power consumption are reported as if the two Midspans are one. Table 5-2 summarizes the affected SNMP Object IDs.

**Table 5-2: SNMP Object IDs Affected by Midspan Power Backup Mode Connection**

SNMP Object ID	Power Backup Mode
pethMainPsePower (RFC3621)	430W/950W (Power backup mode = Redundant) 860W/1900W (Power backup mode = Maximum Power)
pethMainPseOperStatus (RFC3621)	Fault in case of power failure (Midspan is powered by RPS or 2nd Midspan)
pethMainPseConsumptionPower (RFC3621)	Total power consumption of both Midspans
pethMainPseUsageThreshold (RFC3621)	Sends a trap whenever both Midspan power consumption exceeds xy% out of pethMainPsePower OiD (total available power by both Midspans) power
mainPowerUsageBudget (private MIB)	Changing power usage budget (%) in one Midspan will change it in the 2nd Midspan as well
mainPSE_MaxPower (private MIB)	Total maximum power of both Midspans after it was reduced by pethMainPseUsageThreshold (%)

### 5.1 Viewing the Power Source Status

View the external power source status (Ok/Fail) and power source type (RPS/Midspan) in the View-Status Web page (Figure 5-3). Refer to Section 4.3 for details on View - Status Screen.





Figure 5-3: Power Source Status

## 5.2 RPS Power Backup

Connecting a Midspan 90xxG to a redundant power source (RPS) provides power backup by enabling the Midspan to be powered by the unit's internal power source and the RPS power source. Two power backup modes are available:

- **Redundancy:** Maximum power that Midspan can provide remains the same as if no RPS is being used (430 W or 950 W). This mode guarantees that all active PoE ports continue to deliver same power regardless if Midspan is powered by its internal power source or by RPS.
- **Maximum Power:** RPS power capabilities are added to the Midspan internal power source capabilities. A Midspan with a 430 watt power supply can now provide 860 watts, and Midspan with a 950 watt power supply can now provide up to 1900 watts.

Figure 5-4 displays the Power Backup Mode field found in the System Configuration Product Parameters window. Select the required mode in the drop down list.



**Microsemi** Home View **System Configuration** Port Configuration

## System Configuration - Product Parameters

**System Detection Method**

PD Detection Method

Enable pre 802.3at ☒

**Extended Power Mode (36W per port)**

Enable Extended Power Mode ☒

**Power Backup Mode**

Power Backup Mode

**Midspan Nickname**

Midspan Nickname

**Status View Refresh Rate**

Refresh Rate (in seconds)

Save Options

**Figure 5-4: Power Backup Mode**



**NOTE:**

Configuring Power Backup Mode to *Maximum Power* may cause some of the PoE ports to be shut down in case of power failure in RPS or Midspan power source, since total power consumption may exceed single Power source capabilities (430W/950W).



## 5.3 Dual 90xxG, 95xxG, 96xxG, 55xxG Midspan Power Backup

Connecting a Midspan 90xxG, 95xxG, 55xxG to a second 90xxG, 95xxG, 96xxG, 55xxG Midspan provides power backup by enabling the Midspan to be powered by its internal power source and from 2<sup>nd</sup> Midspan power source. Two power backup modes are available, Redundancy and Maximum Power. Power-Shift feature enables shifting power from one Midspan to another whenever one Midspan requires more power and the second Midspan has spare unused power.

- **Redundancy:** A single Midspan internal power source has to power both Midspans in case of a power failure in one Midspan unit. The power sum of both Midspans cannot exceed 430/950 watts. Each Midspan's initial maximum power is set to  $430/2 = 215$  watts or  $950/2 = 475$  watts (the maximum power may change during normal operation).
- **Maximum Power:** The 1<sup>st</sup> Midspan power source capabilities are added to 2<sup>nd</sup> Midspan's internal power source capabilities. Two Midspans having a 430 watt power supply can now provide 860 watts, while two Midspans having a 950 watt power supply can provide up to 1900 watts.

### NOTE:

1. Changing *power-backup* mode in one of the Midspan's will cause 2<sup>nd</sup> Midspan *power-backup* mode to be changed to same power backup mode
2. When two stand alone Midspans are configured to different *power-backup* modes, after being connected together both Midspans will switch to Redundant power-backup mode.

### 5.3.1 Midspan 90xxG/95xxG/96xxG/55xxG to Midspan 90xxG/95xxG/96xxG/55xxG Power Shift




Figure 5-5: View - Status Window (Power Shift Display)

Whenever two 90xxG, 95xxG, 96xxG, or 55xxG Midspans powers back up each other, two additional rows are added to the View - Status web page. The 1<sup>st</sup> additional row displays the extended Midspan power consumption and maximum power. The 2<sup>nd</sup> row reports total power consumption and total maximum power.

## Power Over Ethernet Power View Pro User Guide

Figure 5-5 describes two PD-9024G/ACDC/M Midspans backing up each other, while in Redundancy Power-Backup mode. Total power of both Midspans is limited to 430 watts (due to redundant mode configuration). Local Midspan maximum power was reduced by the Midspan power manager to 179 watts, while external Midspan maximum power was increased to 251 watts.

### 5.3.2 Changing Power Limit (%) by SNMP


Midspan maximum power can be limited by SNMP private MIB Object-Id *mainPowerUsageBudget* (see Figure 5-6), or by Midspan itself whenever **Dynamic UPS Power Management** is enabled.

Power shift between two 90xxG, 95xxG, 55xxG Midspans pauses whenever the power limit (%) is less than 100% and resumes automatically whenever power limit will be restored back to 100%.



#### NOTE:

Changing *power-limit (%)* in one of the 90xxG Midspan's will change automatically *power-limit* on 2<sup>nd</sup> Midspan to same value.



**Figure 5-6: Midspan Power Limit by SNMP**

Table 5-3 describes an example of two 9024G Midspans which back up each other in Redundant Mode and whose *mainPowerUsageBudget* SNMP OiD is changed from 100% to 70%.

**Table 5-3: *mainPowerUsageBudget* SNMP OiD Vs Midspan Maximum Power**

<b>mainPowerUsageBudget SNMP OiD</b>	<b>Midspan-1 Max Power</b>	<b>Midspan-2 Max Power</b>	<b>Total Power</b>	<b>Midspan Power Shift</b>
Maximum Power (Power Limit = 100%)	287 watts	143 watts	430 watts	Enabled
Maximum Power (Power Limit = 70%)	200 watts	100 watts	300 watts	Pause (Power-Limit < 100%)

## 5.3.3 Activating Dynamic UPS Power Management

*Dynamic UPS Power Management* feature should be configured only on a single 90xxG, 95xxG Midspan whenever two 90xxG, 95xxG Midspans power backup each other. When the configured Midspan detects a UPS power failure (UPS switched to battery), it will modify Power-Limit % as per the user configuration. A Power-Limit value on the 2<sup>nd</sup> 90xxG Midspan automatically follows a Power-Limit value of the Midspan which monitors the UPS over SNMP.



### **NOTE:**

The user should not change by SNMP private MIB *mainPowerUsageBudget* OiD while *Dynamic UPS Power Management* is enabled.

## 5.3.4 Power Failure and Invalid Midspan to Midspan Power Backup Connection Report

- **Power failure:** In case of a power failure in one 90xxG, 95xxG, 55xxG Midspan units, an SNMP trap (see SNMP private MIB) and SysLog message is sent to the SNMP Manager and SysLog manager, and an error message appears in View-Status web page. Another SNMP & SysLog message is sent whenever power is restored.




### **NOTE:**

Main Power LED will blink whenever 90xxG/95xxG/96xxG Midspan is being powered by external Midspan/RPS due to internal power supply failure (no AC power).

- **Invalid connection:** The following behavior occurs in cases where a 90xxG, 95xxG, 55xxG Midspan having a 450 watt power supply is connected to another 90xxG, 95xxG, 96xxG, 55xxG Midspan having 1000 watt power supply:
  - Both Midspans will reduce maximum power to 41 watts which should stop power to most PoE PD devices.
  - A Midspan report invalid configuration by sending SNMP Trap & SysLog message.
  - An error message appears on the View->Status Web page.
  - A repeating error message will appear on Terminal/Telnet/SSH screen.

## 6 SNMP Monitoring and Configuration

Multiple Midspan devices management can be performed by using 3rd party standard network management tools such as HP Openview, IBM Tivoli or SNMPc (Figure 6-1).



**Figure 6-1: SNMPc Network Management Tool**

### **NOTE:**



Due to security concerns, when unit is shipped the SNMP is disabled. Prior to enabling SNMP, modify SNMP community strings and only then enable it.

### 6.1 Enabling Midspan SNMP

The Midspan manager module supports SNMPv1, SNMPv2c, and SNMPv3.

#### **To use the SNMP:**

- Browse to the System Configuration SNMP or SNMPv3 Web page and verify that either one of them is enabled.
  - For SNMPv2c, browse to the System Configuration SNMP Web page. Make sure that community strings match your SNMP manager configuration.
  - For SNMPv3, browse to System Configuration SNMPv3 Web page and make sure username, authentication and privacy password and encryption method match your SNMP manager configuration.
- Browse to SNMP Web page. Enable PoE MIB traps and set remote manager IP address in the Trap list.

### 6.2 SNMP MIBs

Several MIBs are supported by Midspan SNMP manager.

- **RFC3621:** Power Over Ethernet MIB which provides various management capabilities (see Figure 6-2)
- **Private MIB:** Enhance PoE functionality beyond RFC3621 PoE MIB.
- **RFC1213:** MIB2 which provides general IPv4 network statistics, and information on the device being managed.
- Various SNMPv3 MIBs as RFC3413, RFC3414, RFC3415

### 6.3 RFC3621 PoE MIB

**NOTE:**

For a detailed PoE MIB description, please refer to Microsemi's Technical Note – 132 (can be found on Midspan CD) , which describes in detail PoE MIB functionality.

RFC3621 PoE MIB is located under 1.3.6.1.2.1.105 SNMP MIB tree. The MIB is divided into 3 sections (see Figure 6-2). The 1st section deals with PoE ports and provides functionality as Enable/Disable, read port status, class, etc. Each Oid is accessed as a two dimensional array table.

The 2nd section deals with power source which is responsible to provide power to a group of PoE ports. It enables reading total power consumption, power supply status, etc.

The 3rd section enable/disables PoE traps to be sent to remote SNMP managers.

## Power Over Ethernet Power View Pro User Guide





Figure 6-2: MIB Tree Structure

## 6.4 Private MIB

Midspan's private MIB extend RFC3621 PoE MIB with the following additional management functionalities (see Figure 6-3):



**Figure 6-3: MIBs Management Functionalities**

### Port Parameters

- Readout of each individual port's power consumption.
- Set maximum power that the PD device may consume.
- Read/Set provide power on two/four pairs (write applicable only for 95xxG,55xxG series)

### System Parameters

- Resolves MIB-II SysobjID description.
- Read Power Supply voltage.
- Read/Set detection method (802.3af+at or 202.3af+at plus legacy).
- Read/Set Midspan power budget percentage (%). For example setting to 50% for Midspan with 400Watt capacity, limits Midspan power to 200 Watt.

## Power Over Ethernet Power View Pro User Guide



### NOTES:

1. Power budget limitation will be canceled whenever the Midspan manager module is restarted, or the Midspan is turned off and on.
2. 65xx, 65xxG - Midspan power budget cannot be set below 37 watts. Whenever configuring power budget in percentage (%), below 37 watt (e.g. 18% for a 200 watt unit), Midspan will report 18% regardless of user power budget configuration. For 400 watts units lowest power budget percentage is 9%.
3. 90xxG, 95xxG, 96xxG, 55xxG – Midspan power budget cannot be set below 41 watts.

- Read internal Power Supply maximum power capabilities (regardless of power limitation).

### Private MIB Object IDs which are applicable only for Midspan 90xxG, 95xxG, 96xxG, 55xxG:

- Enable/Disable support for various pre 802.3at PD devices (only 90xxG).
- Enable/Disable extended power. Extend PD maximum power to 36Watt or limit to 30Watt as per 802.3at specification (90xxG, 95xxG, 55xxG).
- Report power backup type - stand alone/RPS/2<sup>nd</sup> Midspan/Invalid power backup device (90xxG, 95xxG, 96xxG, 55xxG)
- Report internal power source status (90xxG, 95xxG, 96xxG, 55xxG).
- Report external power source status (90xxG, 95xxG, 96xxG, 55xxG)
- Midspan temperature ( 95xxG, 96xxG, 55xxG)
- Midspan temperature format – Celsius/Fahrenheit (95xxG, 96xxG, 55xxG).




## 7 Software Upgrade

The following sections describe how to upgrade the system software.

### 7.1 Software upgrade types

There are two types of software upgrades associated with the Power over Ethernet (PoE) Midspan:

- **Midspan Manager Module Software:** Updates Midspan management application (including all Web pages) that provide remote Network management capabilities.
- **Midspan Firmware:** Update firmware used to manage PoE Power ports (rarely required).




**Figure 7-1: System Software Architecture**

### 7.2 Midspan Manager Module Software Upgrade

#### Internal FLASH Memory Size Requirements

Only Network Management Modules with internal FLASH memory of 4MB can be upgraded to latest IPv6 compliant software version. Midspan products such as PD-90xxG, PD-95xxG, PD-96xxG, PD-55xxG and PD-65xxG have all internal FLASH memory of 4MB and can be easily upgraded to latest IPv6 compliant software version. In case you are using another Midspan, check memory FLASH size using one of the following methods:

1. Browsing to **unit view->product information** web page with any web browser.



2. Through serial port (38400), by viewing 1<sup>st</sup> message during power up.

Mon Ver 1.07 (Jul 8 2009, 15:34:57), FLASH=4MB, MAC=00:05:5A:01:FE:78

3. By Serial/Telnet/SSH accessing to:  
**view-> View application & Boot software version**

Waiting 5 sec. Press '@' to enter MONITOR

**Figure 7-2: Identifying Flash Memory Size**

### 7.2.1 Upgrading from IPv4 to IPv6 (software version 3.xx to 4.xx)

All Network Management Module software versions starting with 3.xy (for example 3.47.10.23) are IPv4 only compliant. All Management Module software versions starting with 4.xy are IPv6 compliant (support both IPv4 & IPv6). When upgrading from v3.xy to v4.xy, same IPv4 address will be used (static IPv4 configuration), or in case DHCPv4 was in use, DHCPv4 will remain enabled. Same for other IP configuration parameters such as SNMP trap list, SysLog servers, RADIUS Servers, and NTP server.



#### NOTES:


Active PoE ports are not affected by software update (there is no intermediate power failure to PD devices).

### 7.2.2 Upgrading to Latest IPv6 Software Version (version 4.xx)

To obtain the latest version of the PowerDsine Midspan Network Management Module software, browse to <http://www.microsemi.com/PowerDsine/Support/Downloads/>, or contact [Customer.Care\\_AMSG@microsemi.com](mailto:Customer.Care_AMSG@microsemi.com).

### 7.2.3 Checklist Prior to Performing Software Update

- Make sure you can access the unit by Telnet or serial connection.
- For serial communication over USB, you need to install the USB virtual COM driver which can be found inside the Midspan CD.
- Verify Network connectivity by trying to browse or ping the Midspan unit.
- Run TFTP server on the computer which has the latest Midspan Network Manager Module software version. It is recommended to use the TFTP server application from the CD shipped with the Midspan.
- Verify firewall is turned off, or enable firewall UDP port 69.
- Unzip the Network Management Module software version or copy it from CD and place it in the root folder of the TFTP server (see image Figure 7-3)
-



**Figure 7-3: TFTP Server Root Folder Setting**



**NOTE:**

Active PoE ports will not be affected by software update (no intermediate power failure to PD devices).

## 7.2.4 Performing software update

To upgrade the software:

1. Make sure TFTP Server is running and proper files were copied to TFTP Server root folder.
2. Connect to the Midspan unit by Telnet/SSH or serial interface, using HyperTerminal or any other serial communication software (38400, 1 stop bit, flow control off). Press ESC to access the main menu.

```
Main Menu - [Midspan PoE Device]
-----
1. View menu
2. Configuration & maintenance menu
3. Ping remote host

E. Exit to debug information screen
```

## Power Over Ethernet Power View Pro User Guide

3. Select **Configuration & Maintenance Menu** (2). The following screen appears:

```
Configuration & Maintenance Menu
-----
1. Enable/Disable PoE Port
2. Network configuration

3. Download configuration file from TFTP Server (reset only Manager module)
4. Upload configuration file to TFTP Server
5. Download WEB SSL Certificate from TFTP Server (reset only Manager module)
6. Software update menu

7. Turn RADIUS,ACL Filter off. Restore all user & password to factory default
8. Restore unit to factory default (excluding IP configuration)

9. Reset Manager module
A. Reset unit

B. Enable/Disable auto ping to Default Gateway to ensure Network connectivity

ESC - Return to previous menu
```

4. Select the Software Update Menu; you will be asked to type the TFTP Server IP address. Type the appropriate TFTP server's IP address; the following screen appears:

```
Software Update Menu
-----
1. Update Midspan Manager module software <reset only Manager module>
2. Update Midspan firmware <reset unit>

ESC - Return to previous menu
```

5. Select **Update Midspan Manager Module Software**.

Software update will start by loading various files from TFTP server. At the end of the software update, Network Management Module will reset itself without effecting working PoE ports. Wait for software power up to finish, browse to the unit (or connect by serial) and verify software version number matches the software version you had upgraded to.

## 8 Troubleshooting

This paragraph provides a symptom and resolution sequence to assist in the troubleshooting of operating problems. If the steps given do not solve your problem, do not hesitate to call your local dealer for further assistance. Refer to Table 8-1.

**Table 8-1: Troubleshooting Guide**

Symptom	Corrective Steps
AC LED does not illuminate (green).	<ol style="list-style-type: none"> <li>1. Check your power source.</li> <li>2. Ensure that a proper Ethernet cable is used.</li> </ol>
Midspan Ethernet LINK LED is off.	In cases where a Network card (NIC) is connected directly to the Midspan's RJ45 connector, make sure you use a crossed Ethernet cable.
Midspan Ethernet LINK LED is on and no ping reply.	<ol style="list-style-type: none"> <li>1. Midspan is shipped with the following default IP 192.168.0.50. Change your Network card IP to 192.168.0.40 and try to Ping again.</li> <li>2. Connect to Midspan serial communication port and set Midspan IP to the same IP Network as your host computer.</li> <li>3. In case you switched very fast from one Midspan to another (both with default IP 192.168.0.50) erase IP address from your host ARP table. For winXP/Vista/Win7, open DOS window (start-&gt;run-&gt;cmd), and type arp -d 192.168.0.50.</li> </ol>
Midspan can be 'pinged' from a local Host but when trying to use the Midspan Ping utility, there is no reply.	<ol style="list-style-type: none"> <li>1. Try to turn off host Firewall.</li> <li>2. If Ping is OK, access the advanced Firewall options and enable the Ping option and TFTP (UDP port 69), SNMP TRAP ports (UDP port 162).</li> </ol>
Software update by TFTP cannot be performed.	<ol style="list-style-type: none"> <li>1. Use the Midspan Ping utility to ping the Host running the TFTP Server application</li> <li>2. Turn off Firewall, or enable UDP port 69</li> <li>3. Verify that appropriate update files package was copied to the TFTP Server root folder.</li> </ol>
Unit cannot be accessed via Telnet.	Use Web browser to view System Configuration - Security screen and make sure under the Remote Access area, in the Enable Telnet/SSH list, Telnet is selected. For further information see Figure 4-43: System Configuration Security Screen.
When accessing the unit by Telnet, Telnet session is terminated each time the Configuration option is pressed.	Log-on to Telnet via the Administrator username & password option and not via the Viewer username & password.
Log-on to unit via Telnet is okay but Telnet session is terminated after a while.	Telnet session is terminated in case no key is pressed and no activity takes place for more than three minutes.
No SNMP TRAP events are received	<ol style="list-style-type: none"> <li>1. Use WEB browser to view System Configuration-&gt;Security WEB page and verify the SNMP checkbox is selected.</li> <li>2. Check System Configuration-&gt;SNMP WEB page and verify the remote SNMP manager IP matches and Trap community string matches the Remote SNMP manager Trap configuration.</li> <li>3. Turn of Firewall on SNMP manager station, or allow UDP port 162 to pass through it.</li> </ol>

## Power Over Ethernet Power View Pro User Guide

Symptom	Corrective Steps
SysLog Server IP was set properly, but Log messages are not received.	Turn off Host Firewall, or allow UDP port 514 to pass through it.
One of the ports was disabled but after turning the unit off and back on, it suddenly turned on again.	<ol style="list-style-type: none"> <li>1. When changing port status, verify the Save &amp; Update button is pressed.</li> <li>2. Verify the PD is compatible to the detection method of the system.</li> </ol>
When using a web Browser and accessing View – Status Web page, all ports are red illuminated and a question mark appears.	If Midspan does not provide power to PoE PDs, try to update the internal firmware. If the problem persists, contact technical support.
Weekly schedule was properly configured but PoE ports do not turn on/off in accordance with the weekly schedule scheme.	<ol style="list-style-type: none"> <li>1. Verify NTP Server IP address was configured properly</li> <li>2. Verify the Time Zone Offset on the GMT window displays “Ok”.</li> <li>3. Verify your company’s Firewall does not block outgoing/incoming NTP packets (UDP Port 123)</li> </ol>
In cases where UPS operates on battery, Midspan does not turn off low priority ports.	<ol style="list-style-type: none"> <li>1. Browse to View – Status Web page and verify that UPS Power Management window does not display “???” in any one of the fields. If “???” appears, verify UPS dynamic management parameters are properly configured.</li> <li>2. Verify that Midspan SNMP configuration (SNMP v1 or SNMP v2) matches UPS SNMP agent capabilities.</li> </ol>
Cisco’s 1130AG and Cisco 1242G wireless access point shut down its radio while connected to L2/L3 Ethernet Switch through Midspan.	Add to Cisco wireless access point the following configuration line: <b><i>power inline negotiation injector override</i></b>
Not all Cisco’s 125x wireless access point radio channels are operational.	Activate the Pre 802.3at feature (supported by Midspan 90xxG family).
Can’t power PD devices when connecting 90xxG Midspan to 2 <sup>nd</sup> 90xxG Midspan or RPS for power backup	<p>Make sure you have not connected 90xxG Midspan capable of driving 1000W with 2<sup>nd</sup> Midspan/RPS capable of driving 450W.</p> <p>In case of such configuration, an error message will be reported constantly on the terminal/Telnet/SSH interface of both Midspan devices.</p>
90xxG Midspan was connected to another 90xxG Midspan/RPS but operates as a stand-alone Midspan	Make sure you have connected power cables and communication cable between 1 <sup>st</sup> Midspan to 2 <sup>nd</sup> Midspan/RPS

## Power Over Ethernet Power View Pro User Guide

*The information contained in the document is PROPRIETARY AND CONFIDENTIAL information of Microsemi and cannot be copied, published, uploaded, posted, transmitted, distributed or disclosed or used without the express duly signed written consent of Microsemi. If the recipient of this document has entered into a disclosure agreement with Microsemi, then the terms of such Agreement will also apply. This document and the information contained herein may not be modified, by any person other than authorized personnel of Microsemi. No license under any patent, copyright, trade secret or other intellectual property right is granted to or conferred upon you by disclosure or delivery of the information, either expressly, by implication, inducement, estoppels or otherwise. Any license under such intellectual property rights must be express and approved by Microsemi in writing signed by an officer of Microsemi.*

*Microsemi reserves the right to change the configuration, functionality and performance of its products at anytime without any notice. This product has been subject to limited testing and should not be used in conjunction with life-support or other mission-critical equipment or applications. Microsemi assumes no liability whatsoever, and Microsemi disclaims any express or implied warranty, relating to sale and/or use of Microsemi products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright or other intellectual property right. The product is subject to other terms and conditions which can be located on the web at <http://www.microsemi.com/legal/tnc.asp>.*

### Revision History

Revision Level / Date	Para. Affected	Description
1.1	Whole Document	IPv6 support
1.2	Whole Document	Update Pictures
1.3	4.2, 4.3, 4.4	Main Widow figures update
1.4		9524G Midspan Added
1.5	Whole Document	55xxG Midspan family Added
1.6	Whole Document	96xxG Midspan family Added

Covered under one or more of US Patents: #6,473,608; 6,986,071; 7,006,815; 7,254,734; 7,257,724; 7,259,325; 7,305,573; 7,325,150; 7,421,290; 7,437,217.

© 2012 Microsemi Corp.

All rights reserved.

For support contact: [customer.care\\_AMSG@microsemi.com](mailto:customer.care_AMSG@microsemi.com)

Visit our web site at: <http://www.microsemi.com/powerdsine> Catalog Number: PD\_NMS\_IPV6\_UG