

# Dual-Power Supply Technology SyncServer S600/S650 Series

Power is a key concern in modern data center design and management. While efficiency and cooling are high priorities, so is reliability—in particular, surviving power fluctuations or outages and returning to normal operations as fast as possible. Accurate time is a key element in bringing a mission critical data center back online quickly in the event of a power service interruption. As systems restart, one of the initial activities is often synchronizing the time to an accurate network time server. A time server with dual-corded, dual-power supplies provides several levels of time service protection in these scenarios.

## Dual-Corded, Dual-Power Supplies

In an ideal scenario, the data center has dual-power circuits. The dual-corded SyncServer S600 Series Network Time Server with hitless dual-power supplies connects to each circuit. The SyncServer power supplies load share equally, which improves overall reliability, and an active power management system constantly monitors the operation. If the power to one cord is lost or if one power supply fails, the entire load is instantly picked up by the remaining energized power supply with no interruption in time services to the network.



All SyncServers ship with a locking power cable connector as an extra measure of physical reliability.

In the event there is only a single source of power available to the SyncServer, having each power supply connected to the same circuit provides protection against a single power supply failure. Just as in the dual-corded scenario, if a power supply fails the other instantly picks up the entire load.



## Power Supply Monitoring and Alarming

Power in a data center is a closely monitored resource, so it is usually obvious when an outage occurs. However, failure of a single power supply in a dual-power supply time server can be more subtle. To remedy this, each power supply in the SyncServer is continuously monitored. In the event of a power supply failure, notification is instantly provided to the network operator through SNMP trap, email, alarm relay, or LEDs on the front of the unit. This notification allows the operator time to schedule maintenance on the SyncServer at an appropriate or convenient time.

## Assurance of Continued Time Service Operations

The SyncServer S600 Series network time servers are purposely built to deliver exact hardware based on Network Time Protocol (NTP) time stamps. The unparalleled accuracy and security is rounded out with outstanding ease-of-use features for reliable network time services ready to meet the needs of the user network and business operations today and in the future.

The dual-power supply option is available for the SyncServer S600 and SyncServer S650 configurations.

## Specifications

- Dual IEC 60320 C14 connectors
- Dual power supplies: 88 VAC–264 VAC, 50 Hz–60 Hz, 65 W each
- Load sharing
- Hitless switching



**Microsemi Corporate Headquarters**  
 One Enterprise, Aliso Viejo, CA 92656 USA  
 Within the USA: +1 (800) 713-4113  
 Outside the USA: +1 (949) 380-6100  
 Fax: +1 (949) 215-4996  
 Email: sales.support@microsemi.com  
 www.microsemi.com

©2017 Microsemi Corporation. All rights reserved. Microsemi and the Microsemi logo are registered trademarks of Microsemi Corporation. All other trademarks and service marks are the property of their respective owners.

Microsemi Corporation (Nasdaq: MSCC) offers a comprehensive portfolio of semiconductor and system solutions for aerospace & defense, communications, data center and industrial markets. Products include high-performance and radiation-hardened analog mixed-signal integrated circuits, FPGAs, SoCs and ASICs; power management products; timing and synchronization devices and precise time solutions, setting the world's standard for time; voice processing devices; RF solutions; discrete components; enterprise storage and communication solutions, security technologies and scalable anti-tamper products; Ethernet solutions; Power-over-Ethernet ICs and midspans; as well as custom design capabilities and services. Microsemi is headquartered in Aliso Viejo, California and has approximately 4,800 employees globally. Learn more at [www.microsemi.com](http://www.microsemi.com).

Microsemi makes no warranty, representation, or guarantee regarding the information contained herein or the suitability of its products and services for any particular purpose, nor does Microsemi assume any liability whatsoever arising out of the application or use of any product or circuit. The products sold hereunder and any other products sold by Microsemi have been subject to limited testing and should not be used in conjunction with mission-critical equipment or applications. Any performance specifications are believed to be reliable but are not verified, and Buyer must conduct and complete all performance and other testing of the products, alone and together with, or installed in, any end-products. Buyer shall not rely on any data and performance specifications or parameters provided by Microsemi. It is the Buyer's responsibility to independently determine suitability of any products and to test and verify the same. The information provided by Microsemi hereunder is provided "as is, where is" and with all faults, and the entire risk associated with such information is entirely with the Buyer. Microsemi does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other IP rights, whether with regard to such information itself or anything described by such information. Information provided in this document is proprietary to Microsemi, and Microsemi reserves the right to make any changes to the information in this document or to any products and services at any time without notice.